

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1426041

Luminaire Tested: P3A02RH9040DE010 E3HY1MW

Issue Date: 3/9/2026

Test Information

Test Method: LM-79-2019
Report Number: P1426041
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-658-3)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02RH9040DE010 E3HY1MW
Description: 3in Adjustable LED luminaire with, RH optic, 4000K CCT AND, 90CRI , E3HY1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 126.1 lumens
Efficiency: N/A
Efficacy: 35.0 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.53
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1426041

CATALOG NUMBER: P3A02RH9040DE010 E3HY1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1426041

CATALOG NUMBER: P3A02RH9040DE010 E3HY1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	97	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	89	101	96	91	88	93	90	87		91	88	85		89
4	99	91	86	82	97	90	86	82	88	84	81		86	83	80		84
5	94	86	81	77	93	85	80	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	78	72	68	85	77	72	68	76	71	68		75	70	67		74
8	83	74	68	65	82	73	68	65	72	68	64		71	67	64		70
9	79	71	65	62	78	70	65	61	69	65	61		68	64	61		68
10	76	68	62	59	75	67	62	59	66	62	58		66	61	58		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	60763
5°	55668
10°	48652
15°	42679
20°	21585
25°	10743
30°	9723
35°	7388
40°	5181
45°	3504
50°	2252
55°	1491
60°	1053
65°	830
70°	513
75°	424
80°	379
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3504 cd/sqm

TEST NUMBER: P1426041

CATALOG NUMBER: P3A02RH9040DE010 E3HY1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	23.0	18.3
10°-20°	47.6	37.8
20°-30°	23.2	18.4
30°-40°	17.4	13.8
40°-50°	8.9	7.1
50°-60°	3.7	2.9
60°-70°	1.5	1.2
70°-80°	0.6	0.4
80°-90°	0.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	93.9	74.5
0°-40°	111.2	88.2
0°-60°	123.9	98.3
0°-90°	126.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	126.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	277	
5°	253	23
15°	188	48
25°	44	23
35°	28	17
45°	11	9
55°	4	4
65°	2	2
75°	0	1
85°	0	0
90°	0	

TEST NUMBER: P1426041

CATALOG NUMBER: P3A02RH9040DE010 E3HY1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	277.1
2.5°	270.8
5°	252.9
7.5°	233.7
10°	218.5
12.5°	207.2
15°	188.0
17.5°	146.7
20°	92.5
22.5°	54.9
25°	44.4
27.5°	41.0
30°	38.4
32.5°	33.7
35°	27.6
37.5°	22.6
40°	18.1
42.5°	14.5
45°	11.3
47.5°	8.7
50°	6.6
52.5°	5.0
55°	3.9
57.5°	3.2
60°	2.4
62.5°	1.8
65°	1.6
67.5°	1.1
70°	0.8
72.5°	0.8
75°	0.5
77.5°	0.3
80°	0.3
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)