

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1426047

Luminaire Tested: P3A02RH9050DE010 E3HY1MW

Issue Date: 3/9/2026

Test Information

Test Method: LM-79-2019
Report Number: P1426047
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-658-3)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02RH9050DE010 E3HY1MW
Description: 3in Adjustable LED luminaire with, RH optic, 5000K CCT AND, 90CRI , E3HY1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 128.0 lumens
Efficiency: N/A
Efficacy: 35.6 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.53
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1426047

CATALOG NUMBER: P3A02RH9050DE010 E3HY1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1426047

CATALOG NUMBER: P3A02RH9050DE010 E3HY1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	97	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	89	101	96	92	88	93	90	87		91	88	85		89
4	99	91	86	82	97	90	86	82	88	84	81		86	83	80		84
5	94	86	81	77	93	85	80	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	78	72	68	85	77	72	68	76	71	68		75	70	67		74
8	83	74	68	65	82	73	68	65	72	68	64		71	67	64		70
9	79	71	65	62	78	70	65	61	69	65	61		68	64	61		68
10	76	68	62	59	75	67	62	59	66	62	58		66	61	58		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	61728
5°	56548
10°	49409
15°	43360
20°	21935
25°	10912
30°	9875
35°	7495
40°	5267
45°	3566
50°	2286
55°	1529
60°	1053
65°	830
70°	513
75°	424
80°	379
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3566 cd/sqm

TEST NUMBER: P1426047

CATALOG NUMBER: P3A02RH9050DE010 E3HY1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	23.4	18.3
10°-20°	48.4	37.8
20°-30°	23.6	18.4
30°-40°	17.6	13.8
40°-50°	9.1	7.1
50°-60°	3.7	2.9
60°-70°	1.5	1.2
70°-80°	0.6	0.4
80°-90°	0.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	95.4	74.5
0°-40°	113.0	88.3
0°-60°	125.8	98.3
0°-90°	128.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	128.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	282	
5°	257	23
15°	191	48
25°	45	24
35°	28	18
45°	12	9
55°	4	4
65°	2	2
75°	0	1
85°	0	0
90°	0	

TEST NUMBER: P1426047

CATALOG NUMBER: P3A02RH9050DE010 E3HY1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	281.5
2.5°	275.1
5°	256.9
7.5°	237.4
10°	221.9
12.5°	210.4
15°	191.0
17.5°	149.0
20°	94.0
22.5°	55.8
25°	45.1
27.5°	41.7
30°	39.0
32.5°	34.2
35°	28.0
37.5°	23.0
40°	18.4
42.5°	14.7
45°	11.5
47.5°	8.8
50°	6.7
52.5°	5.1
55°	4.0
57.5°	3.2
60°	2.4
62.5°	1.9
65°	1.6
67.5°	1.1
70°	0.8
72.5°	0.8
75°	0.5
77.5°	0.3
80°	0.3
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)