

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1263476

Luminaire Tested: P3A20R409727D010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1263476
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A20R409727D010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R40 optic, 2700K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 510.0 lumens
Efficiency: N/A
Efficacy: 17.7 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1263476

CATALOG NUMBER: P3A20R409727D010 E3DLP1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P1263476

CATALOG NUMBER: P3A20R409727D010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	93	97	94	91		94	92	89		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	83		86
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	64	82	73	68	63	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	158803
5°	155580
10°	144865
15°	126266
20°	101742
25°	76262
30°	53629
35°	35121
40°	21268
45°	12714
50°	7573
55°	6117
60°	5482
65°	4670
70°	4424
75°	3558
80°	3536
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 12714 cd/sqm

TEST NUMBER: P1263476

CATALOG NUMBER: P3A20R409727D010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	65.6	12.9
10°-20°	153.2	30.0
20°-30°	144.4	28.3
30°-40°	83.5	16.4
40°-50°	33.3	6.5
50°-60°	14.7	2.9
60°-70°	9.1	1.8
70°-80°	4.8	0.9
80°-90°	1.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	363.2	71.2
0°-40°	446.6	87.6
0°-60°	494.7	97.0
0°-90°	510.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	510.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	724	
5°	707	66
15°	556	153
25°	315	144
35°	131	83
45°	41	33
55°	16	15
65°	9	9
75°	4	5
85°	1	2
90°	0	

TEST NUMBER: P1263476

CATALOG NUMBER: P3A20R409727D010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	724.2
2.5°	720.0
5°	706.8
7.5°	682.5
10°	650.6
12.5°	607.5
15°	556.2
17.5°	498.5
20°	436.0
22.5°	373.6
25°	315.2
27.5°	261.1
30°	211.8
32.5°	168.7
35°	131.2
37.5°	99.3
40°	74.3
42.5°	55.5
45°	41.0
47.5°	29.9
50°	22.2
52.5°	18.1
55°	16.0
57.5°	14.6
60°	12.5
62.5°	10.4
65°	9.0
67.5°	7.6
70°	6.9
72.5°	5.6
75°	4.2
77.5°	3.5
80°	2.8
82.5°	2.1
85°	1.4
87.5°	0.7
90°	0.0

(END OF REPORT)