

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265834

Luminaire Tested: P3A20R409730D010 E3CB1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1265834
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-24)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A20R409730D010 E3CB1MW
Description: 3in Adjustable LED luminaire with, R40 optic, 3000K CCT AND, 97CRI , E3CB1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2128.9 lumens
Efficiency: N/A
Efficacy: 73.9 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.59
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1265834

CATALOG NUMBER: P3A20R409730D010 E3CB1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1265834

CATALOG NUMBER: P3A20R409730D010 E3CB1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					0
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	112	110	109		112	110	109	107		106	105	104		103	102	101		99	98	98
2	111	107	104	101		109	105	102	100		102	100	98		99	97	96		96	95	94
3	107	102	98	95		105	100	97	94		98	95	93		96	93	91		94	92	90
4	103	97	93	90		102	96	92	89		94	91	88		92	90	87		91	88	86
5	100	93	89	86		98	92	88	85		91	87	85		89	86	84		88	85	83
6	96	90	85	82		95	89	85	82		88	84	81		86	83	81		85	82	80
7	93	86	82	79		92	86	81	78		85	81	78		83	80	78		82	79	77
8	90	83	79	76		89	83	78	75		82	78	75		81	77	75		80	77	75
9	87	80	76	73		87	80	76	73		79	75	72		78	75	72		77	74	72
10	85	77	73	70		84	77	73	70		76	73	70		76	72	70		75	72	70

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1120963
5°	1115582
10°	1079227
15°	954830
20°	622984
25°	220682
30°	46792
35°	15419
40°	5639
45°	1892
50°	1535
55°	1720
60°	1316
65°	1557
70°	962
75°	1271
80°	1894
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 82.5°

Luminance: 2520 cd/sqm

TEST NUMBER: P1265834

CATALOG NUMBER: P3A20R409730D010 E3CB1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	476.9	22.4
10°-20°	1110.5	52.2
20°-30°	481.9	22.6
30°-40°	44.4	2.1
40°-50°	6.3	0.3
50°-60°	3.9	0.2
60°-70°	2.8	0.1
70°-80°	1.6	0.1
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2069.3	97.2
0°-40°	2113.7	99.3
0°-60°	2123.9	99.8
0°-90°	2128.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2128.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5112	
5°	5068	477
15°	4206	1111
25°	912	482
35°	58	44
45°	6	6
55°	4	4
65°	3	3
75°	2	2
85°	0	1
90°	0	

TEST NUMBER: P1265834

CATALOG NUMBER: P3A20R409730D010 E3CB1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	5112.0
2.5°	5106.0
5°	5068.1
7.5°	4987.8
10°	4846.9
12.5°	4609.0
15°	4206.0
17.5°	3537.8
20°	2669.7
22.5°	1733.3
25°	912.1
27.5°	392.4
30°	184.8
32.5°	100.0
35°	57.6
37.5°	34.8
40°	19.7
42.5°	10.6
45°	6.1
47.5°	4.5
50°	4.5
52.5°	4.5
55°	4.5
57.5°	4.5
60°	3.0
62.5°	3.0
65°	3.0
67.5°	3.0
70°	1.5
72.5°	1.5
75°	1.5
77.5°	1.5
80°	1.5
82.5°	1.5
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)