

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1263969

Luminaire Tested: P3A02R509730DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1263969
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02R509730DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R50 optic, 3000K CCT AND, 97CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 303.0 lumens
Efficiency: N/A
Efficacy: 84.2 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1263969

CATALOG NUMBER: P3A02R509730DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1263969

CATALOG NUMBER: P3A02R509730DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	102	102	100
1	114	112	109	107	112	110	108	106	105	104	102	102	101	99	98	97	97	97	97	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	91	91	90
3	105	99	95	91	103	98	94	90	95	92	89	93	90	88	91	88	86	86	86	85
4	100	94	89	85	99	92	88	85	90	87	84	88	85	83	87	84	82	82	82	80
5	96	89	84	80	94	88	83	79	86	82	79	84	81	78	83	80	77	77	77	76
6	92	84	79	75	91	83	78	75	82	78	74	81	77	74	79	76	73	73	73	72
7	88	80	75	71	87	79	74	71	78	74	70	77	73	70	76	72	70	70	70	68
8	84	76	71	67	83	76	71	67	75	70	67	74	69	66	73	69	66	66	66	65
9	81	73	67	64	80	72	67	64	71	67	63	70	66	63	70	66	63	63	63	62
10	78	69	64	61	77	69	64	61	68	64	60	67	63	60	67	63	60	60	60	59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	105891
5°	103059
10°	98350
15°	89036
20°	77030
25°	63197
30°	36309
35°	11270
40°	3034
45°	1054
50°	239
55°	76
60°	44
65°	52
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1054 cd/sqm

TEST NUMBER: P1263969

CATALOG NUMBER: P3A02R509730DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	43.9	14.5
10°-20°	108.7	35.9
20°-30°	114.2	37.7
30°-40°	32.7	10.8
40°-50°	3.2	1.1
50°-60°	0.2	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	266.8	88.0
0°-40°	299.5	98.8
0°-60°	302.9	100.0
0°-90°	303.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	303.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	483	
5°	468	44
15°	392	109
25°	261	114
35°	42	33
45°	3	3
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1263969

CATALOG NUMBER: P3A02R509730DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	482.9
1°	482.1
2°	480.0
3°	476.9
4°	472.7
5°	468.2
6°	463.4
7°	458.3
8°	453.5
9°	447.9
10°	441.7
11°	434.6
12°	426.3
13°	416.1
14°	404.9
15°	392.2
16°	378.8
17°	365.7
18°	352.4
19°	340.6
20°	330.1
21°	320.1
22°	308.6
23°	295.5
24°	280.1
25°	261.2
26°	240.6
27°	217.8
28°	195.0
29°	170.4
30°	143.4
31°	118.0
32°	94.7
32.5°	84.6
33°	74.3
34°	57.0
35°	42.1
36°	30.9
37°	23.0
37.5°	19.9
38°	17.2
39°	13.4
40°	10.6
42.5°	6.0
45°	3.4

TEST NUMBER: P1263969

CATALOG NUMBER: P3A02R509730DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	1.9
50°	0.7
52.5°	0.3
55°	0.2
57.5°	0.2
60°	0.1
62.5°	0.1
65°	0.1
67.5°	0.1
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)