

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264251

Luminaire Tested: P3A05R259730DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264251
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R259730DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3000K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 141.0 lumens
Efficiency: N/A
Efficacy: 19.6 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264251

CATALOG NUMBER: P3A05R259730DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1264251

CATALOG NUMBER: P3A05R259730DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	86	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	65	60	79	70	64	60	69	64	60		68	63	60		67
9	76	67	61	57	75	66	61	57	65	60	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	51180
5°	49108
10°	43019
15°	34575
20°	26579
25°	20106
30°	14534
35°	9664
40°	5840
45°	3411
50°	2183
55°	1759
60°	1535
65°	1349
70°	1154
75°	1101
80°	884
85°	1006

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3411 cd/sqm

TEST NUMBER: P1264251

CATALOG NUMBER: P3A05R259730DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	20.3	14.4
10°-20°	42.1	29.9
20°-30°	38.1	27.0
30°-40°	22.9	16.2
40°-50°	9.1	6.4
50°-60°	4.2	3.0
60°-70°	2.6	1.8
70°-80°	1.4	1.0
80°-90°	0.4	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	100.5	71.3
0°-40°	123.4	87.5
0°-60°	136.7	97.0
0°-90°	141.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	141.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	233	
5°	223	20
15°	152	42
25°	83	38
35°	36	23
45°	11	9
55°	5	4
65°	3	3
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1264251

CATALOG NUMBER: P3A05R259730DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	233.4
1°	233.4
2°	232.3
3°	229.9
4°	226.9
5°	223.1
6°	218.3
7°	212.8
8°	206.4
9°	200.0
10°	193.2
11°	185.3
12°	177.2
13°	169.0
14°	160.9
15°	152.3
17.5°	132.1
20°	113.9
22.5°	97.4
25°	83.1
27.5°	69.7
30°	57.4
32.5°	46.2
35°	36.1
37.5°	27.5
40°	20.4
42.5°	14.9
45°	11.0
47.5°	8.4
50°	6.4
52.5°	5.3
55°	4.6
57.5°	4.0
60°	3.5
62.5°	2.9
65°	2.6
67.5°	2.2
70°	1.8
72.5°	1.5
75°	1.3
77.5°	1.1
80°	0.7
82.5°	0.4
85°	0.4
87.5°	0.2



TEST NUMBER: P1264251

CATALOG NUMBER: P3A05R259730DE010 E3DLP1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)