

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264502

Luminaire Tested: P3A05R709730DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264502
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-47)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R709730DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R70 optic, 3000K CCT AND, 97CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 452.0 lumens
Efficiency: N/A
Efficacy: 62.8 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 0.98
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264502

CATALOG NUMBER: P3A05R709730DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1264502

CATALOG NUMBER: P3A05R709730DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	96	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	88	83	98	92	87	82	89	85	81		86	83	80		84
4	94	86	80	75	93	85	79	75	83	78	74		81	76	73		79
5	89	80	73	69	87	79	73	68	77	72	68		75	71	67		74
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	53	74	64	58	53	63	57	53		62	57	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	49	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	87493
5°	86462
10°	83966
15°	80409
20°	75303
25°	68423
30°	59098
35°	47114
40°	34293
45°	22545
50°	10575
55°	3250
60°	3158
65°	3009
70°	2885
75°	3050
80°	2778
85°	2264

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 22545 cd/sqm

TEST NUMBER: P1264502

CATALOG NUMBER: P3A05R709730DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	37.0	8.2
10°-20°	99.1	21.9
20°-30°	128.8	28.5
30°-40°	109.3	24.2
40°-50°	56.4	12.5
50°-60°	10.9	2.4
60°-70°	5.9	1.3
70°-80°	3.6	0.8
80°-90°	1.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	264.9	58.6
0°-40°	374.2	82.8
0°-60°	441.5	97.7
0°-90°	452.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	452.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	399	
5°	393	37
15°	354	99
25°	283	129
35°	176	109
45°	73	56
55°	8	11
65°	6	6
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1264502

CATALOG NUMBER: P3A05R709730DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	399.0
2.5°	397.7
5°	392.8
7.5°	385.6
10°	377.1
12.5°	366.3
15°	354.2
17.5°	339.3
20°	322.7
22.5°	303.9
25°	282.8
27.5°	259.0
30°	233.4
32.5°	205.1
35°	176.0
37.5°	147.2
40°	119.8
42.5°	94.3
45°	72.7
47.5°	53.4
50°	31.0
52.5°	13.5
55°	8.5
57.5°	8.1
60°	7.2
62.5°	6.7
65°	5.8
67.5°	5.4
70°	4.5
72.5°	4.0
75°	3.6
77.5°	2.7
80°	2.2
82.5°	1.3
85°	0.9
87.5°	0.4
90°	0.0

(END OF REPORT)