

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264720

Luminaire Tested: P3A09R409730DE010 E3DLD1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264720
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-22)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R409730DE010 E3DLD1WMH
Description: 3in Adjustable LED luminaire with, R40 optic, 3000K CCT AND, 97CRI , E3DLD1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 586.0 lumens
Efficiency: N/A
Efficacy: 52.8 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264720

CATALOG NUMBER: P3A09R409730DE010 E3DLD1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1264720

CATALOG NUMBER: P3A09R409730DE010 E3DLD1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	57	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	131546
5°	129165
10°	121752
15°	110580
20°	97145
25°	82964
30°	68719
35°	53003
40°	37728
45°	25429
50°	13850
55°	9787
60°	9210
65°	8509
70°	7565
75°	7202
80°	5809
85°	5032

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25429 cd/sqm

TEST NUMBER: P1264720

CATALOG NUMBER: P3A09R409730DE010 E3DLD1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.7	9.3
10°-20°	135.7	23.2
20°-30°	156.9	26.8
30°-40°	123.6	21.1
40°-50°	63.5	10.8
50°-60°	24.3	4.1
60°-70°	16.1	2.7
70°-80°	8.7	1.5
80°-90°	2.6	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	347.3	59.3
0°-40°	470.9	80.4
0°-60°	558.6	95.3
0°-90°	586.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	586.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	600	
5°	587	55
15°	487	136
25°	343	157
35°	198	124
45°	82	63
55°	26	24
65°	16	16
75°	8	9
85°	2	3
90°	0	

TEST NUMBER: P1264720

CATALOG NUMBER: P3A09R409730DE010 E3DLD1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	599.9
2.5°	596.6
5°	586.8
7.5°	569.7
10°	546.8
12.5°	519.9
15°	487.1
17.5°	453.0
20°	416.3
22.5°	378.9
25°	342.9
27.5°	306.8
30°	271.4
32.5°	235.4
35°	198.0
37.5°	163.2
40°	131.8
42.5°	104.9
45°	82.0
47.5°	59.7
50°	40.6
52.5°	29.5
55°	25.6
57.5°	22.9
60°	21.0
62.5°	18.4
65°	16.4
67.5°	13.8
70°	11.8
72.5°	9.8
75°	8.5
77.5°	6.6
80°	4.6
82.5°	3.9
85°	2.0
87.5°	1.3
90°	0.0

(END OF REPORT)