

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264758

Luminaire Tested: P3A09R509730DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264758
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R509730DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R50 optic, 3000K CCT AND, 97CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 911.0 lumens
Efficiency: N/A
Efficacy: 82.1 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264758

CATALOG NUMBER: P3A09R509730DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1264758

CATALOG NUMBER: P3A09R509730DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	105	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	92	88	85	90	87	84		88	85	83		87
5	96	89	84	80	94	88	83	79	86	82	79		84	81	78		83
6	92	84	79	75	91	83	78	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76
8	84	76	71	67	83	76	71	67	75	70	67		74	69	66		73
9	81	73	67	64	80	72	67	64	71	67	63		70	66	63		70
10	78	69	64	61	77	69	64	61	68	64	60		67	63	60		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	318352
5°	309883
10°	295719
15°	267720
20°	231603
25°	189979
30°	109131
35°	33890
40°	9103
45°	3194
50°	751
55°	229
60°	132
65°	156
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3194 cd/sqm

TEST NUMBER: P1264758

CATALOG NUMBER: P3A09R509730DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.9	14.5
10°-20°	326.8	35.9
20°-30°	343.4	37.7
30°-40°	98.3	10.8
40°-50°	9.6	1.1
50°-60°	0.8	0.1
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	802.0	88.0
0°-40°	900.3	98.8
0°-60°	910.7	100.0
0°-90°	911.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	911.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1452	
5°	1408	132
15°	1179	327
25°	785	343
35°	127	98
45°	10	10
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1264758

CATALOG NUMBER: P3A09R509730DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1451.8
1°	1449.6
2°	1443.2
3°	1433.8
4°	1421.3
5°	1407.8
6°	1393.3
7°	1377.9
8°	1363.4
9°	1346.7
10°	1328.1
11°	1306.6
12°	1281.8
13°	1250.9
14°	1217.5
15°	1179.3
16°	1138.8
17°	1099.6
18°	1059.4
19°	1024.0
20°	992.5
21°	962.3
22°	927.9
23°	888.4
24°	842.1
25°	785.2
26°	723.5
27°	654.7
28°	586.3
29°	512.3
30°	431.0
31°	354.8
32°	284.8
32.5°	254.2
33°	223.4
34°	171.3
35°	126.6
36°	92.9
37°	69.1
37.5°	59.8
38°	51.7
39°	40.2
40°	31.8
42.5°	18.0
45°	10.3



TEST NUMBER: P1264758
CATALOG NUMBER: P3A09R509730DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	5.8
50°	2.2
52.5°	1.0
55°	0.6
57.5°	0.6
60°	0.3
62.5°	0.3
65°	0.3
67.5°	0.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)