

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264867

Luminaire Tested: P3A09R659730DE010 E3DLP1WMH

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1264867  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A09R659730DE010 E3DLP1WMH  
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 97CRI , E3DLP1WMH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 455.0 lumens  
Efficiency: N/A  
Efficacy: 41.0 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 11.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1264867

CATALOG NUMBER: P3A09R659730DE010 E3DLP1WMH

### Luminous Intensity Polar Plot



TEST NUMBER: P1264867

CATALOG NUMBER: P3A09R659730DE010 E3DLP1WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 105 | 110 | 108 | 105 | 103 | 104 | 102 | 100 |  | 100 | 98  | 97  |  | 96  |
| 2   | 107 | 101 | 97  | 93  | 104 | 100 | 96  | 92  | 96  | 93  | 90  |  | 93  | 91  | 88  |  | 90  |
| 3   | 101 | 94  | 88  | 84  | 99  | 92  | 87  | 83  | 90  | 85  | 82  |  | 87  | 84  | 81  |  | 85  |
| 4   | 95  | 87  | 81  | 76  | 93  | 86  | 80  | 76  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 80  |
| 5   | 90  | 81  | 75  | 70  | 88  | 80  | 74  | 70  | 78  | 73  | 69  |  | 77  | 72  | 69  |  | 75  |
| 6   | 85  | 76  | 69  | 65  | 84  | 75  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 7   | 81  | 71  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 59  |  | 67  |
| 8   | 77  | 67  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 59  | 56  |  | 64  | 59  | 55  |  | 63  |
| 9   | 73  | 63  | 57  | 52  | 72  | 62  | 56  | 52  | 61  | 56  | 52  |  | 60  | 55  | 52  |  | 59  |
| 10  | 69  | 59  | 53  | 49  | 68  | 59  | 53  | 49  | 58  | 53  | 49  |  | 57  | 52  | 49  |  | 56  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 115649 |
| 5°  | 112767 |
| 10° | 105030 |
| 15° | 94121  |
| 20° | 81277  |
| 25° | 67625  |
| 30° | 53325  |
| 35° | 39511  |
| 40° | 27222  |
| 45° | 16870  |
| 50° | 9177   |
| 55° | 5773   |
| 60° | 4912   |
| 65° | 4410   |
| 70° | 3783   |
| 75° | 3304   |
| 80° | 3283   |
| 85° | 3271   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 16870 cd/sqm

TEST NUMBER: P1264867

CATALOG NUMBER: P3A09R659730DE010 E3DLP1WMH

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 47.6   | 10.5      |
| 10°-20°   | 115.2  | 25.3      |
| 20°-30°   | 127.4  | 28.0      |
| 30°-40°   | 92.5   | 20.3      |
| 40°-50°   | 43.4   | 9.5       |
| 50°-60°   | 14.6   | 3.2       |
| 60°-70°   | 8.4    | 1.8       |
| 70°-80°   | 4.4    | 1.0       |
| 80°-90°   | 1.4    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 290.2  | 63.8      |
| 0°-40°    | 382.8  | 84.1      |
| 0°-60°    | 440.7  | 96.9      |
| 0°-90°    | 455.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 455.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 527 |      |
| 5°  | 512 | 48   |
| 15° | 415 | 115  |
| 25° | 280 | 127  |
| 35° | 148 | 93   |
| 45° | 54  | 43   |
| 55° | 15  | 15   |
| 65° | 8   | 8    |
| 75° | 4   | 4    |
| 85° | 1   | 1    |
| 90° | 0   |      |

TEST NUMBER: P1264867

CATALOG NUMBER: P3A09R659730DE010 E3DLP1WMH

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 527.4 |
| 2.5°  | 524.1 |
| 5°    | 512.3 |
| 7.5°  | 494.6 |
| 10°   | 471.7 |
| 12.5° | 444.8 |
| 15°   | 414.6 |
| 17.5° | 381.8 |
| 20°   | 348.3 |
| 22.5° | 313.6 |
| 25°   | 279.5 |
| 27.5° | 244.7 |
| 30°   | 210.6 |
| 32.5° | 177.8 |
| 35°   | 147.6 |
| 37.5° | 120.0 |
| 40°   | 95.1  |
| 42.5° | 72.8  |
| 45°   | 54.4  |
| 47.5° | 39.4  |
| 50°   | 26.9  |
| 52.5° | 18.4  |
| 55°   | 15.1  |
| 57.5° | 13.1  |
| 60°   | 11.2  |
| 62.5° | 9.8   |
| 65°   | 8.5   |
| 67.5° | 7.2   |
| 70°   | 5.9   |
| 72.5° | 5.2   |
| 75°   | 3.9   |
| 77.5° | 3.3   |
| 80°   | 2.6   |
| 82.5° | 2.0   |
| 85°   | 1.3   |
| 87.5° | 0.7   |
| 90°   | 0.0   |

(END OF REPORT)