

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1268236

Luminaire Tested: P3A20R409735D010 E3DLP1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1268236
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A20R409735D010 E3DLP1LI
Description: 3in Adjustable LED luminaire with, R40 optic, 3500K CCT AND, 97CRI , E3DLP1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1157.0 lumens
Efficiency: N/A
Efficacy: 40.2 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1268236

CATALOG NUMBER: P3A20R409735D010 E3DLP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1268236

CATALOG NUMBER: P3A20R409735D010 E3DLP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	93	97	94	91		94	92	89		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	83		86
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	64	82	73	68	63	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	360256
5°	352982
10°	328651
15°	286426
20°	230833
25°	173018
30°	121639
35°	79692
40°	48233
45°	28809
50°	17193
55°	13839
60°	12455
65°	10637
70°	10130
75°	8049
80°	7956
85°	8051

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 28809 cd/sqm

TEST NUMBER: P1268236

CATALOG NUMBER: P3A20R409735D010 E3DLP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	148.9	12.9
10°-20°	347.5	30.0
20°-30°	327.5	28.3
30°-40°	189.4	16.4
40°-50°	75.4	6.5
50°-60°	33.4	2.9
60°-70°	20.6	1.8
70°-80°	10.8	0.9
80°-90°	3.4	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	823.9	71.2
0°-40°	1013.3	87.6
0°-60°	1122.1	97.0
0°-90°	1157.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1157.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1643	
5°	1604	149
15°	1262	348
25°	715	327
35°	298	189
45°	93	75
55°	36	33
65°	20	21
75°	10	11
85°	3	3
90°	0	

TEST NUMBER: P1268236

CATALOG NUMBER: P3A20R409735D010 E3DLP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1642.9
2.5°	1633.5
5°	1603.6
7.5°	1548.4
10°	1476.0
12.5°	1378.3
15°	1261.7
17.5°	1131.0
20°	989.2
22.5°	847.5
25°	715.1
27.5°	592.3
30°	480.4
32.5°	382.8
35°	297.7
37.5°	225.3
40°	168.5
42.5°	126.0
45°	92.9
47.5°	67.7
50°	50.4
52.5°	41.0
55°	36.2
57.5°	33.1
60°	28.4
62.5°	23.6
65°	20.5
67.5°	17.3
70°	15.8
72.5°	12.6
75°	9.5
77.5°	7.9
80°	6.3
82.5°	4.7
85°	3.2
87.5°	1.6
90°	0.0

(END OF REPORT)