

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1266136

Luminaire Tested: P3A02R129735DE010 E3PHLD1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1266136
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02R129735DE010 E3PHLD1MW
Description: 3in Adjustable LED luminaire with, R12 optic, 3500K CCT AND, 97CRI , E3PHLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 174.0 lumens
Efficiency: N/A
Efficacy: 47.0 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.66
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1266136

CATALOG NUMBER: P3A02R129735DE010 E3PHLD1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1266136

CATALOG NUMBER: P3A02R129735DE010 E3PHLD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95
2	104	98	93	89	102	97	92	88	93	89	86		90	87	84		87
3	98	90	83	79	96	88	83	78	85	81	77		83	79	75		81
4	92	82	76	70	90	81	75	70	79	73	69		77	72	68		75
5	86	76	69	64	84	75	68	63	73	67	63		71	66	62		70
6	81	70	63	58	79	70	63	58	68	62	58		67	61	57		65
7	77	66	59	54	75	65	58	54	64	58	53		62	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	69	58	51	46	68	57	51	46	56	50	46		55	50	46		54
10	65	54	48	44	64	54	48	44	53	47	43		52	47	43		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	50632
5°	47458
10°	38922
15°	30239
20°	23872
25°	19017
30°	15268
35°	12474
40°	10276
45°	8652
50°	7437
55°	6423
60°	5701
65°	4929
70°	4424
75°	3558
80°	2904
85°	2013

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 8652 cd/sqm

TEST NUMBER: P1266136

CATALOG NUMBER: P3A02R129735DE010 E3PHLD1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	19.3	11.1
10°-20°	37.3	21.4
20°-30°	36.3	20.8
30°-40°	29.3	16.8
40°-50°	21.8	12.5
50°-60°	15.2	8.7
60°-70°	9.5	5.5
70°-80°	4.5	2.6
80°-90°	0.8	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	92.8	53.3
0°-40°	122.2	70.2
0°-60°	159.2	91.4
0°-90°	174.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	174.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	231	
5°	216	19
15°	133	37
25°	79	36
35°	47	29
45°	28	22
55°	17	15
65°	10	10
75°	4	5
85°	1	1
90°	0	

TEST NUMBER: P1266136

CATALOG NUMBER: P3A02R129735DE010 E3PHLD1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	230.9
2.5°	227.1
5°	215.6
7.5°	197.3
10°	174.8
12.5°	152.7
15°	133.2
17.5°	116.8
20°	102.3
22.5°	89.7
25°	78.6
27.5°	68.7
30°	60.3
32.5°	53.1
35°	46.6
37.5°	40.8
40°	35.9
42.5°	31.7
45°	27.9
47.5°	24.8
50°	21.8
52.5°	19.1
55°	16.8
57.5°	14.9
60°	13.0
62.5°	11.1
65°	9.5
67.5°	8.0
70°	6.9
72.5°	5.3
75°	4.2
77.5°	3.1
80°	2.3
82.5°	1.1
85°	0.8
87.5°	0.0
90°	0.0

(END OF REPORT)