

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1267301

Luminaire Tested: P3A10R129735DE010 E3DLP1WMH

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1267301  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A10R129735DE010 E3DLP1WMH  
Description: 3in Adjustable LED luminaire with, R12 optic, 3500K CCT AND, 97CRI , E3DLP1WMH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 399.9 lumens  
Efficiency: N/A  
Efficacy: 34.2 lumens/watt  
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 11.7  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1267301

CATALOG NUMBER: P3A10R129735DE010 E3DLP1WMH

### Luminous Intensity Polar Plot



TEST NUMBER: P1267301

CATALOG NUMBER: P3A10R129735DE010 E3DLP1WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 106 | 111 | 108 | 106 | 104 | 104 | 102 | 101 |  | 100 | 99  | 98  |  | 97  |
| 2   | 108 | 103 | 98  | 95  | 105 | 101 | 97  | 94  | 98  | 95  | 92  |  | 95  | 92  | 90  |  | 92  |
| 3   | 102 | 96  | 91  | 87  | 100 | 94  | 90  | 86  | 92  | 88  | 85  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 90  | 84  | 80  | 95  | 88  | 83  | 79  | 86  | 82  | 78  |  | 84  | 81  | 78  |  | 82  |
| 5   | 93  | 84  | 78  | 74  | 91  | 83  | 78  | 74  | 81  | 77  | 73  |  | 80  | 76  | 73  |  | 78  |
| 6   | 88  | 79  | 73  | 69  | 87  | 79  | 73  | 69  | 77  | 72  | 69  |  | 76  | 71  | 68  |  | 74  |
| 7   | 84  | 75  | 69  | 65  | 83  | 74  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 8   | 80  | 71  | 65  | 61  | 79  | 71  | 65  | 61  | 69  | 64  | 61  |  | 68  | 64  | 61  |  | 68  |
| 9   | 77  | 68  | 62  | 58  | 76  | 67  | 62  | 58  | 66  | 61  | 58  |  | 65  | 61  | 57  |  | 64  |
| 10  | 74  | 64  | 59  | 55  | 73  | 64  | 59  | 55  | 63  | 58  | 55  |  | 62  | 58  | 55  |  | 62  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 172486 |
| 5°  | 159432 |
| 10° | 127274 |
| 15° | 96141  |
| 20° | 73203  |
| 25° | 55794  |
| 30° | 39956  |
| 35° | 26073  |
| 40° | 16001  |
| 45° | 9675   |
| 50° | 6413   |
| 55° | 4970   |
| 60° | 4254   |
| 65° | 3684   |
| 70° | 3334   |
| 75° | 3304   |
| 80° | 2399   |
| 85° | 1510   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9675 cd/sqm

TEST NUMBER: P1267301

CATALOG NUMBER: P3A10R129735DE010 E3DLP1WMH

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 64.2   | 16.0      |
| 10°-20°   | 118.4  | 29.6      |
| 20°-30°   | 105.4  | 26.4      |
| 30°-40°   | 62.3   | 15.6      |
| 40°-50°   | 25.6   | 6.4       |
| 50°-60°   | 12.0   | 3.0       |
| 60°-70°   | 7.3    | 1.8       |
| 70°-80°   | 3.8    | 1.0       |
| 80°-90°   | 0.9    | 0.2       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 287.9  | 72.0      |
| 0°-40°    | 350.3  | 87.6      |
| 0°-60°    | 387.8  | 97.0      |
| 0°-90°    | 399.9  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 399.9  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 787 |      |
| 5°  | 724 | 64   |
| 15° | 424 | 118  |
| 25° | 231 | 105  |
| 35° | 97  | 62   |
| 45° | 31  | 26   |
| 55° | 13  | 12   |
| 65° | 7   | 7    |
| 75° | 4   | 4    |
| 85° | 1   | 1    |
| 90° | 0   |      |

TEST NUMBER: P1267301

CATALOG NUMBER: P3A10R129735DE010 E3DLP1WMH

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 786.6 |
| 1°    | 784.7 |
| 2°    | 778.8 |
| 3°    | 767.1 |
| 4°    | 747.6 |
| 5°    | 724.3 |
| 6°    | 698.9 |
| 7°    | 669.0 |
| 8°    | 637.9 |
| 9°    | 606.0 |
| 10°   | 571.6 |
| 12.5° | 493.0 |
| 15°   | 423.5 |
| 17.5° | 363.8 |
| 20°   | 313.7 |
| 22.5° | 269.6 |
| 25°   | 230.6 |
| 27.5° | 192.9 |
| 30°   | 157.8 |
| 32.5° | 126.0 |
| 35°   | 97.4  |
| 37.5° | 74.7  |
| 40°   | 55.9  |
| 42.5° | 41.6  |
| 45°   | 31.2  |
| 47.5° | 24.0  |
| 50°   | 18.8  |
| 52.5° | 15.6  |
| 55°   | 13.0  |
| 57.5° | 11.0  |
| 60°   | 9.7   |
| 62.5° | 8.4   |
| 65°   | 7.1   |
| 67.5° | 6.5   |
| 70°   | 5.2   |
| 72.5° | 4.5   |
| 75°   | 3.9   |
| 77.5° | 2.6   |
| 80°   | 1.9   |
| 82.5° | 1.3   |
| 85°   | 0.6   |
| 87.5° | 0.6   |
| 90°   | 0.0   |

(END OF REPORT)