

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269792

Luminaire Tested: P3A13R259740DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269792
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A13R259740DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 4000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 370.0 lumens
Efficiency: N/A
Efficacy: 25.3 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269792

CATALOG NUMBER: P3A13R259740DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1269792

CATALOG NUMBER: P3A13R259740DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	87932
5°	85846
10°	79535
15°	70852
20°	60882
25°	51753
30°	42589
35°	33194
40°	23873
45°	15164
50°	8972
55°	6155
60°	5657
65°	5241
70°	4744
75°	4321
80°	4041
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15164 cd/sqm

TEST NUMBER: P1269792

CATALOG NUMBER: P3A13R259740DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	36.2	9.8
10°-20°	86.6	23.4
20°-30°	97.9	26.5
30°-40°	77.4	20.9
40°-50°	39.1	10.6
50°-60°	15.7	4.2
60°-70°	10.0	2.7
70°-80°	5.5	1.5
80°-90°	1.6	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	220.7	59.6
0°-40°	298.1	80.6
0°-60°	352.9	95.4
0°-90°	370.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	370.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	401	
5°	390	36
15°	312	87
25°	214	98
35°	124	77
45°	49	39
55°	16	16
65°	10	10
75°	5	6
85°	1	2
90°	0	

TEST NUMBER: P1269792

CATALOG NUMBER: P3A13R259740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	401.0
1°	401.0
2°	399.6
3°	397.3
4°	394.1
5°	390.0
6°	384.9
7°	378.9
8°	372.4
9°	365.1
10°	357.2
11°	348.5
12°	340.2
13°	330.5
14°	321.3
15°	312.1
17.5°	286.2
20°	260.9
22.5°	236.9
25°	213.9
27.5°	191.3
30°	168.2
32.5°	146.6
35°	124.0
37.5°	103.3
40°	83.4
42.5°	65.0
45°	48.9
47.5°	36.4
50°	26.3
52.5°	19.8
55°	16.1
57.5°	14.8
60°	12.9
62.5°	11.5
65°	10.1
67.5°	8.8
70°	7.4
72.5°	6.5
75°	5.1
77.5°	4.1
80°	3.2
82.5°	2.3
85°	1.4
87.5°	0.5



TEST NUMBER: P1269792

CATALOG NUMBER: P3A13R259740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)