

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1270336

Luminaire Tested: P3A17R609740DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1270336
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-39)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A17R609740DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R60 optic, 4000K CCT AND, 97CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1312.0 lumens
Efficiency: N/A
Efficacy: 61.9 lumens/watt
Spacing Criteria (0/90/45): 0.87 / 0.87 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1270336

CATALOG NUMBER: P3A17R609740DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1270336

CATALOG NUMBER: P3A17R609740DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	84	91	86	83		88	85	82		86
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81
5	91	82	76	71	89	81	75	71	79	74	70		78	73	70		76
6	86	77	70	66	84	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	65	61		69	64	60		68
8	77	68	61	57	76	67	61	57	66	60	57		65	60	56		64
9	74	64	57	53	72	63	57	53	62	57	53		61	56	53		60
10	70	60	54	50	69	60	54	50	59	53	50		58	53	50		57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	309800
5°	306867
10°	297924
15°	279116
20°	247051
25°	206673
30°	161974
35°	117490
40°	78175
45°	48718
50°	26370
55°	7646
60°	7105
65°	6486
70°	6411
75°	6354
80°	6314
85°	6290

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 48718 cd/sqm

TEST NUMBER: P1270336

CATALOG NUMBER: P3A17R609740DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.3	10.0
10°-20°	341.1	26.0
20°-30°	388.8	29.6
30°-40°	275.7	21.0
40°-50°	125.1	9.5
50°-60°	26.6	2.0
60°-70°	12.8	1.0
70°-80°	7.9	0.6
80°-90°	2.7	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	861.2	65.6
0°-40°	1136.9	86.7
0°-60°	1288.6	98.2
0°-90°	1312.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1312.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1413	
5°	1394	131
15°	1230	341
25°	854	389
35°	439	276
45°	157	125
55°	20	27
65°	12	13
75°	8	8
85°	2	3
90°	0	

TEST NUMBER: P1270336

CATALOG NUMBER: P3A17R609740DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1412.8
2.5°	1407.8
5°	1394.1
7.5°	1370.4
10°	1338.0
12.5°	1291.9
15°	1229.5
17.5°	1151.0
20°	1058.7
22.5°	958.9
25°	854.2
27.5°	746.9
30°	639.7
32.5°	537.4
35°	438.9
37.5°	351.6
40°	273.1
42.5°	207.0
45°	157.1
47.5°	117.2
50°	77.3
52.5°	36.2
55°	20.0
57.5°	17.5
60°	16.2
62.5°	15.0
65°	12.5
67.5°	11.2
70°	10.0
72.5°	8.7
75°	7.5
77.5°	6.2
80°	5.0
82.5°	3.7
85°	2.5
87.5°	1.2
90°	0.0

(END OF REPORT)