

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1270441

Luminaire Tested: P3A20R159740D010 E3CB1MMS

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1270441  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-4)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A20R159740D010 E3CB1MMS  
Description: 3in Adjustable LED luminaire with, R15 optic, 4000K CCT AND, 97CRI , E3CB1MMS TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 2071.0 lumens  
Efficiency: N/A  
Efficacy: 71.9 lumens/watt  
Spacing Criteria (0/90/45): 0.3 / 0.3 / 0.29  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 28.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1270441

CATALOG NUMBER: P3A20R159740D010 E3CB1MMS

### Luminous Intensity Polar Plot



TEST NUMBER: P1270441

CATALOG NUMBER: P3A20R159740D010 E3CB1MMS

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| RF  | 20  |     |     |     | 20  |     |     |     |     | 20  |     |     |     |     | 20  |     |     |     |    | 20 |
| RC  | 80  |     |     |     | 70  |     |     |     |     | 50  |     |     |     |     | 30  |     |     |     |    | 10 |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30 | 10 |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |    |    |
| 1   | 116 | 114 | 112 | 111 | 113 | 112 | 110 | 109 | 108 | 107 | 106 | 104 | 103 | 103 | 101 | 100 | 100 | 98  |    |    |
| 2   | 113 | 110 | 107 | 105 | 111 | 108 | 106 | 104 | 105 | 103 | 101 | 102 | 101 | 99  | 99  | 98  | 97  | 96  |    |    |
| 3   | 110 | 106 | 103 | 100 | 108 | 105 | 102 | 100 | 102 | 100 | 98  | 100 | 98  | 97  | 98  | 97  | 95  | 94  |    |    |
| 4   | 107 | 103 | 100 | 97  | 106 | 102 | 99  | 97  | 100 | 97  | 95  | 98  | 96  | 94  | 97  | 95  | 93  | 92  |    |    |
| 5   | 105 | 100 | 97  | 94  | 104 | 99  | 96  | 94  | 98  | 95  | 93  | 96  | 94  | 92  | 95  | 93  | 92  | 91  |    |    |
| 6   | 103 | 98  | 94  | 92  | 102 | 97  | 94  | 92  | 96  | 93  | 91  | 95  | 92  | 91  | 94  | 92  | 90  | 89  |    |    |
| 7   | 101 | 96  | 92  | 90  | 100 | 95  | 92  | 90  | 94  | 91  | 89  | 93  | 91  | 89  | 92  | 90  | 89  | 88  |    |    |
| 8   | 99  | 94  | 90  | 88  | 98  | 93  | 90  | 88  | 92  | 90  | 88  | 92  | 89  | 87  | 91  | 89  | 87  | 86  |    |    |
| 9   | 97  | 92  | 89  | 87  | 97  | 92  | 89  | 87  | 91  | 88  | 86  | 90  | 88  | 86  | 90  | 87  | 86  | 85  |    |    |
| 10  | 96  | 90  | 87  | 85  | 95  | 90  | 87  | 85  | 89  | 87  | 85  | 89  | 86  | 85  | 88  | 86  | 85  | 84  |    |    |

**AVERAGE LUMINANCE (cd/sqm):**

|     |         |
|-----|---------|
|     | 0°      |
| 0°  | 4025533 |
| 5°  | 3373797 |
| 10° | 1589193 |
| 15° | 479117  |
| 20° | 177279  |
| 25° | 68931   |
| 30° | 25700   |
| 35° | 7897    |
| 40° | 2805    |
| 45° | 1520    |
| 50° | 1126    |
| 55° | 1262    |
| 60° | 1447    |
| 65° | 830     |
| 70° | 1026    |
| 75° | 1356    |
| 80° | 0       |
| 85° | 0       |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1520 cd/sqm

TEST NUMBER: P1270441

CATALOG NUMBER: P3A20R159740D010 E3CB1MMS

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 1184.9 | 57.2      |
| 10°-20°   | 704.3  | 34.0      |
| 20°-30°   | 148.0  | 7.1       |
| 30°-40°   | 23.9   | 1.2       |
| 40°-50°   | 4.0    | 0.2       |
| 50°-60°   | 3.0    | 0.1       |
| 60°-70°   | 1.8    | 0.1       |
| 70°-80°   | 1.0    | 0.1       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 2037.2 | 98.4      |
| 0°-40°    | 2061.1 | 99.5      |
| 0°-60°    | 2068.1 | 99.9      |
| 0°-90°    | 2071.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 2071.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°    | Flux |
|-----|-------|------|
| 0°  | 18358 |      |
| 5°  | 15327 | ###  |
| 15° | 2110  | 704  |
| 25° | 285   | 148  |
| 35° | 30    | 24   |
| 45° | 5     | 4    |
| 55° | 3     | 3    |
| 65° | 2     | 2    |
| 75° | 2     | 1    |
| 85° | 0     | 0    |
| 90° | 0     |      |

TEST NUMBER: P1270441

CATALOG NUMBER: P3A20R159740D010 E3CB1MMS

**CANDELA DISTRIBUTION (FULL):**

| 0°    |         |
|-------|---------|
| 0°    | 18357.9 |
| 1°    | 18300.6 |
| 2°    | 18009.1 |
| 3°    | 17426.2 |
| 4°    | 16571.5 |
| 5°    | 15327.2 |
| 6°    | 13865.0 |
| 7°    | 12193.3 |
| 8°    | 10596.9 |
| 9°    | 8789.3  |
| 10°   | 7137.2  |
| 12.5° | 3851.0  |
| 15°   | 2110.5  |
| 17.5° | 1236.2  |
| 20°   | 759.7   |
| 22.5° | 465.0   |
| 25°   | 284.9   |
| 27.5° | 171.9   |
| 30°   | 101.5   |
| 32.5° | 57.3    |
| 35°   | 29.5    |
| 37.5° | 16.4    |
| 40°   | 9.8     |
| 42.5° | 6.5     |
| 45°   | 4.9     |
| 47.5° | 3.3     |
| 50°   | 3.3     |
| 52.5° | 3.3     |
| 55°   | 3.3     |
| 57.5° | 3.3     |
| 60°   | 3.3     |
| 62.5° | 1.6     |
| 65°   | 1.6     |
| 67.5° | 1.6     |
| 70°   | 1.6     |
| 72.5° | 1.6     |
| 75°   | 1.6     |
| 77.5° | 0.0     |
| 80°   | 0.0     |
| 82.5° | 0.0     |
| 85°   | 0.0     |
| 87.5° | 0.0     |
| 90°   | 0.0     |

(END OF REPORT)