

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1268854

Luminaire Tested: P3A02R709740DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1268854
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-45)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02R709740DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R70 optic, 4000K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 83.0 lumens
Efficiency: N/A
Efficacy: 23.0 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1268854

CATALOG NUMBER: P3A02R709740DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1268854

CATALOG NUMBER: P3A02R709740DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	97	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	88	83	98	92	87	83	89	85	81		87	83	80		84
4	95	86	80	76	93	85	80	75	83	78	74		81	77	73		79
5	89	80	74	69	88	79	73	69	78	72	68		76	71	68		74
6	85	75	68	64	83	74	68	64	73	67	63		71	66	63		70
7	80	70	64	59	79	69	63	59	68	62	58		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	62	55	51	71	61	55	51	60	55	51		59	54	51		58
10	69	58	52	48	67	58	52	48	57	51	48		56	51	48		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	19472
5°	19106
10°	18013
15°	16345
20°	14305
25°	12073
30°	9875
35°	7656
40°	5496
45°	3473
50°	1740
55°	1070
60°	921
65°	830
70°	769
75°	678
80°	631
85°	503

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3473 cd/sqm

TEST NUMBER: P1268854

CATALOG NUMBER: P3A02R709740DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	8.1	9.8
10°-20°	20.0	24.2
20°-30°	22.8	27.5
30°-40°	17.8	21.5
40°-50°	8.8	10.6
50°-60°	2.7	3.2
60°-70°	1.6	1.9
70°-80°	0.9	1.0
80°-90°	0.2	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	51.0	61.4
0°-40°	68.8	82.9
0°-60°	80.3	96.8
0°-90°	83.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	83.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	89	
5°	87	8
15°	72	20
25°	50	23
35°	29	18
45°	11	9
55°	3	3
65°	2	2
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1268854

CATALOG NUMBER: P3A02R709740DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	88.8
2.5°	88.3
5°	86.8
7.5°	84.4
10°	80.9
12.5°	76.9
15°	72.0
17.5°	66.8
20°	61.3
22.5°	55.5
25°	49.9
27.5°	44.3
30°	39.0
32.5°	33.7
35°	28.6
37.5°	23.8
40°	19.2
42.5°	14.9
45°	11.2
47.5°	7.9
50°	5.1
52.5°	3.3
55°	2.8
57.5°	2.4
60°	2.1
62.5°	1.8
65°	1.6
67.5°	1.4
70°	1.2
72.5°	0.9
75°	0.8
77.5°	0.7
80°	0.5
82.5°	0.3
85°	0.2
87.5°	0.1
90°	0.0

(END OF REPORT)