

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269042

Luminaire Tested: P3A05R309740DE010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269042
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R309740DE010 E3DLP1H
Description: 3in Adjustable LED luminaire with, R30 optic, 4000K CCT AND, 97CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 313.0 lumens
Efficiency: N/A
Efficacy: 43.5 lumens/watt
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.7
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269042

CATALOG NUMBER: P3A05R309740DE010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1269042

CATALOG NUMBER: P3A05R309740DE010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	85	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	73	90	83	77	73	81	76	72		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	74	68	64	72	67	63		71	67	63		70
8	80	70	64	60	78	70	64	60	69	63	60		67	63	60		67
9	76	67	61	57	75	66	60	57	65	60	56		64	60	56		63
10	73	63	58	54	72	63	57	54	62	57	53		61	57	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	106965
5°	103632
10°	93363
15°	77231
20°	59809
25°	44857
30°	32562
35°	21710
40°	13339
45°	7815
50°	4810
55°	3900
60°	3421
65°	2750
70°	2500
75°	2457
80°	1894
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7815 cd/sqm

TEST NUMBER: P1269042

CATALOG NUMBER: P3A05R309740DE010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	43.3	13.8
10°-20°	93.7	29.9
20°-30°	85.2	27.2
30°-40°	51.6	16.5
40°-50°	20.7	6.6
50°-60°	9.2	2.9
60°-70°	5.5	1.8
70°-80°	3.0	1.0
80°-90°	0.9	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	222.3	71.0
0°-40°	273.8	87.5
0°-60°	303.6	97.0
0°-90°	313.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	313.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	488	
5°	471	43
15°	340	94
25°	185	85
35°	81	52
45°	25	21
55°	10	9
65°	5	6
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1269042

CATALOG NUMBER: P3A05R309740DE010 E3DLP1H


CANDELA DISTRIBUTION (FULL):

0°	
0°	487.8
1°	487.3
2°	485.3
3°	481.9
4°	477.1
5°	470.8
6°	463.0
7°	454.8
8°	444.1
9°	432.0
10°	419.3
11°	404.8
12°	389.2
13°	373.7
14°	356.7
15°	340.2
17.5°	297.0
20°	256.3
22.5°	218.4
25°	185.4
27.5°	155.3
30°	128.6
32.5°	103.9
35°	81.1
37.5°	62.1
40°	46.6
42.5°	34.0
45°	25.2
47.5°	18.9
50°	14.1
52.5°	11.2
55°	10.2
57.5°	8.7
60°	7.8
62.5°	6.3
65°	5.3
67.5°	4.9
70°	3.9
72.5°	3.4
75°	2.9
77.5°	2.4
80°	1.5
82.5°	1.0
85°	1.0
87.5°	0.5



TEST NUMBER: P1269042
CATALOG NUMBER: P3A05R309740DE010 E3DLP1H

CANDELA DISTRIBUTION (continued):



(END OF REPORT)