

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269387

Luminaire Tested: P3A09R259740DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269387
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R259740DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 4000K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 223.0 lumens
Efficiency: N/A
Efficacy: 20.1 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269387

CATALOG NUMBER: P3A09R259740DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1269387

CATALOG NUMBER: P3A09R259740DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	86	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	65	60	79	70	64	60	69	64	60		68	63	60		67
9	76	67	61	57	75	66	61	57	65	60	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	80958
5°	77680
10°	68046
15°	54688
20°	42027
25°	31792
30°	22966
35°	15258
40°	9246
45°	5396
50°	3446
55°	2791
60°	2456
65°	2179
70°	1795
75°	1779
80°	1263
85°	1761

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 5396 cd/sqm

TEST NUMBER: P1269387

CATALOG NUMBER: P3A09R259740DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	32.1	14.4
10°-20°	66.6	29.9
20°-30°	60.2	27.0
30°-40°	36.2	16.2
40°-50°	14.4	6.4
50°-60°	6.6	3.0
60°-70°	4.1	1.8
70°-80°	2.1	1.0
80°-90°	0.6	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	159.0	71.3
0°-40°	195.2	87.5
0°-60°	216.2	97.0
0°-90°	223.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	223.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	369	
5°	353	32
15°	241	67
25°	131	60
35°	57	36
45°	17	14
55°	7	7
65°	4	4
75°	2	2
85°	1	1
90°	0	

TEST NUMBER: P1269387

CATALOG NUMBER: P3A09R259740DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	369.2
1°	369.2
2°	367.5
3°	363.7
4°	358.8
5°	352.9
6°	345.2
7°	336.5
8°	326.5
9°	316.4
10°	305.6
11°	293.1
12°	280.2
13°	267.3
14°	254.5
15°	240.9
17.5°	208.9
20°	180.1
22.5°	154.0
25°	131.4
27.5°	110.2
30°	90.7
32.5°	73.0
35°	57.0
37.5°	43.5
40°	32.3
42.5°	23.6
45°	17.4
47.5°	13.2
50°	10.1
52.5°	8.3
55°	7.3
57.5°	6.3
60°	5.6
62.5°	4.5
65°	4.2
67.5°	3.5
70°	2.8
72.5°	2.4
75°	2.1
77.5°	1.7
80°	1.0
82.5°	0.7
85°	0.7
87.5°	0.3



TEST NUMBER: P1269387

CATALOG NUMBER: P3A09R259740DE010 E3DLP1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)