

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269388

Luminaire Tested: P3A09R259740DE010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269388
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R259740DE010 E3DLP1H
Description: 3in Adjustable LED luminaire with, R25 optic, 4000K CCT AND, 97CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 455.0 lumens
Efficiency: N/A
Efficacy: 41.0 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269388

CATALOG NUMBER: P3A09R259740DE010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1269388

CATALOG NUMBER: P3A09R259740DE010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	86	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	65	60	79	70	64	60	69	64	60		68	63	60		67
9	76	67	61	57	75	66	61	57	65	60	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	165184
5°	158485
10°	138831
15°	111601
20°	85734
25°	64867
30°	46868
35°	31133
40°	18893
45°	11009
50°	7027
55°	5696
60°	4956
65°	4410
70°	3654
75°	3643
80°	2652
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11009 cd/sqm

TEST NUMBER: P1269388

CATALOG NUMBER: P3A09R259740DE010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	65.5	14.4
10°-20°	135.9	29.9
20°-30°	122.9	27.0
30°-40°	73.8	16.2
40°-50°	29.3	6.5
50°-60°	13.5	3.0
60°-70°	8.2	1.8
70°-80°	4.4	1.0
80°-90°	1.2	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	324.4	71.3
0°-40°	398.2	87.5
0°-60°	441.1	97.0
0°-90°	455.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	455.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	753	
5°	720	66
15°	492	136
25°	268	123
35°	116	74
45°	36	29
55°	15	14
65°	8	8
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1269388

CATALOG NUMBER: P3A09R259740DE010 E3DLP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	753.3
1°	753.3
2°	749.8
3°	742.0
4°	732.0
5°	720.0
6°	704.4
7°	686.6
8°	666.1
9°	645.5
10°	623.5
11°	598.0
12°	571.7
13°	545.5
14°	519.2
15°	491.6
17.5°	426.3
20°	367.4
22.5°	314.2
25°	268.1
27.5°	224.9
30°	185.1
32.5°	149.0
35°	116.3
37.5°	88.7
40°	66.0
42.5°	48.2
45°	35.5
47.5°	27.0
50°	20.6
52.5°	17.0
55°	14.9
57.5°	12.8
60°	11.3
62.5°	9.2
65°	8.5
67.5°	7.1
70°	5.7
72.5°	5.0
75°	4.3
77.5°	3.5
80°	2.1
82.5°	1.4
85°	1.4
87.5°	0.7



TEST NUMBER: P1269388

CATALOG NUMBER: P3A09R259740DE010 E3DLP1H

CANDELA DISTRIBUTION (continued):



(END OF REPORT)