

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269447

Luminaire Tested: P3A09R359740DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269447
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R359740DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R35 optic, 4000K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 225.0 lumens
Efficiency: N/A
Efficacy: 20.3 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.72
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269447

CATALOG NUMBER: P3A09R359740DE010 E3DLP1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P1269447

CATALOG NUMBER: P3A09R359740DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	97	93	97	94	91		94	92	89		91
3	102	95	90	86	100	94	89	85	91	87	84		89	85	82		86
4	97	89	83	79	95	88	82	78	86	81	77		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	77	72	68	76	71	67		75	70	67		73
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	70	64	60	78	69	63	59	68	63	59		67	62	59		66
9	76	66	60	56	75	66	60	56	65	59	56		64	59	56		63
10	72	63	57	53	71	62	57	53	61	56	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	72319
5°	70548
10°	64483
15°	54734
20°	43334
25°	32784
30°	23852
35°	16142
40°	9904
45°	5706
50°	3411
55°	2791
60°	2412
65°	2179
70°	1795
75°	1779
80°	1768
85°	1761

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5706 cd/sqm

TEST NUMBER: P1269447

CATALOG NUMBER: P3A09R359740DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.6	13.2
10°-20°	66.5	29.5
20°-30°	62.2	27.6
30°-40°	38.1	16.9
40°-50°	15.0	6.7
50°-60°	6.6	2.9
60°-70°	4.1	1.8
70°-80°	2.2	1.0
80°-90°	0.7	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	158.3	70.3
0°-40°	196.3	87.3
0°-60°	217.9	96.9
0°-90°	225.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	225.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	330	
5°	320	30
15°	241	66
25°	136	62
35°	60	38
45°	18	15
55°	7	7
65°	4	4
75°	2	2
85°	1	1
90°	0	

TEST NUMBER: P1269447

CATALOG NUMBER: P3A09R359740DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	329.8
1°	330.2
2°	329.1
3°	327.0
4°	323.9
5°	320.5
6°	316.0
7°	310.8
8°	304.5
9°	297.6
10°	289.6
11°	281.3
12°	272.3
13°	262.6
14°	251.9
15°	241.1
17.5°	213.4
20°	185.7
22.5°	159.0
25°	135.5
27.5°	113.6
30°	94.2
32.5°	76.2
35°	60.3
37.5°	46.1
40°	34.6
42.5°	24.9
45°	18.4
47.5°	13.2
50°	10.0
52.5°	8.3
55°	7.3
57.5°	6.2
60°	5.5
62.5°	4.9
65°	4.2
67.5°	3.5
70°	2.8
72.5°	2.4
75°	2.1
77.5°	1.7
80°	1.4
82.5°	1.0
85°	0.7
87.5°	0.3



TEST NUMBER: P1269447

CATALOG NUMBER: P3A09R359740DE010 E3DLP1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)