

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269500

Luminaire Tested: P3A09R459740DE010 E3DLD1LI

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1269500  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A09R459740DE010 E3DLD1LI  
Description: 3in Adjustable LED luminaire with, R45 optic, 4000K CCT AND, 97CRI , E3DLD1LI TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 615.0 lumens  
Efficiency: N/A  
Efficacy: 55.4 lumens/watt  
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 11.1  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1269500  
CATALOG NUMBER: P3A09R459740DE010 E3DLD1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P1269500  
 CATALOG NUMBER: P3A09R459740DE010 E3DLD1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91				91
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83				83
3	99	92	86	82	97	90	85	81	88	83	80	85	81	78	83	80	77	75				75
4	94	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69				69
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63				63
6	83	73	66	61	81	72	66	61	71	65	61	69	64	60	68	63	60	58				58
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	64	59	55	54				54
8	74	64	57	52	73	63	57	52	62	56	52	61	56	52	60	55	52	50				50
9	70	60	53	49	69	59	53	49	58	52	48	57	52	48	56	52	48	47				47
10	67	56	50	45	66	56	49	45	55	49	45	54	49	45	53	48	45	44				44

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	130384
5°	128087
10°	121196
15°	110534
20°	97752
25°	84876
30°	72872
35°	60713
40°	45256
45°	27693
50°	12827
55°	10016
60°	9648
65°	8821
70°	8207
75°	7795
80°	7198
85°	5284

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 27693 cd/sqm



TEST NUMBER: P1269500  
 CATALOG NUMBER: P3A09R459740DE010 E3DLD1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	54.4	8.8
10°-20°	135.6	22.0
20°-30°	161.1	26.2
30°-40°	140.0	22.8
40°-50°	70.2	11.4
50°-60°	24.4	4.0
60°-70°	17.1	2.8
70°-80°	9.5	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	351.0	57.1
0°-40°	490.9	79.8
0°-60°	585.5	95.2
0°-90°	615.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	615.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	595	
5°	582	54
15°	487	136
25°	351	161
35°	227	140
45°	89	70
55°	26	24
65°	17	17
75°	9	10
85°	2	3
90°	0	



TEST NUMBER: P1269500  
CATALOG NUMBER: P3A09R459740DE010 E3DLD1LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	594.6
2.5°	591.8
5°	581.9
7.5°	566.3
10°	544.3
12.5°	517.4
15°	486.9
17.5°	452.9
20°	418.9
22.5°	384.1
25°	350.8
27.5°	318.9
30°	287.8
32.5°	258.0
35°	226.8
37.5°	193.5
40°	158.1
42.5°	123.3
45°	89.3
47.5°	58.8
50°	37.6
52.5°	29.1
55°	26.2
57.5°	24.1
60°	22.0
62.5°	19.8
65°	17.0
67.5°	14.9
70°	12.8
72.5°	10.6
75°	9.2
77.5°	7.1
80°	5.7
82.5°	4.3
85°	2.1
87.5°	1.4
90°	0.0

(END OF REPORT)