

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1426593

Luminaire Tested: P3A13RH9830DE010 E3HY1MW

Issue Date: 3/9/2026

Test Information

Test Method: LM-79-2019
Report Number: P1426593
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-658-3)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A13RH9830DE010 E3HY1MW
Description: 3in Adjustable LED luminaire with, RH optic, 3000K CCT AND, 98CRI , E3HY1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 348.0 lumens
Efficiency: N/A
Efficacy: 24.0 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.53
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1426593

CATALOG NUMBER: P3A13RH9830DE010 E3HY1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1426593

CATALOG NUMBER: P3A13RH9830DE010 E3HY1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	97	106	102	98	96	99	96	93		96	93	91		93
3	103	97	93	89	101	96	92	88	93	90	87		91	88	85		89
4	99	91	86	82	97	90	86	82	88	84	81		86	83	80		84
5	94	86	81	77	93	85	80	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	72		78	74	71		77
7	86	78	72	68	85	77	72	68	76	71	68		75	70	67		74
8	83	74	68	65	82	73	68	65	72	68	64		71	67	64		70
9	79	71	65	62	78	70	65	61	69	65	61		68	64	61		68
10	76	68	62	59	75	67	62	59	66	62	59		66	61	58		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	167816
5°	153753
10°	134355
15°	117844
20°	59645
25°	29687
30°	26840
35°	20398
40°	14341
45°	9675
50°	6209
55°	4167
60°	2851
65°	2283
70°	1410
75°	1271
80°	884
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9675 cd/sqm

TEST NUMBER: P1426593

CATALOG NUMBER: P3A13RH9830DE010 E3HY1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	63.6	18.3
10°-20°	131.6	37.8
20°-30°	64.2	18.4
30°-40°	47.9	13.8
40°-50°	24.7	7.1
50°-60°	10.2	2.9
60°-70°	4.1	1.2
70°-80°	1.5	0.4
80°-90°	0.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	259.3	74.5
0°-40°	307.2	88.3
0°-60°	342.1	98.3
0°-90°	348.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	348.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	765	
5°	698	64
15°	519	132
25°	123	64
35°	76	48
45°	31	25
55°	11	10
65°	4	4
75°	2	2
85°	0	0
90°	0	

TEST NUMBER: P1426593

CATALOG NUMBER: P3A13RH9830DE010 E3HY1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	765.3
2.5°	747.9
5°	698.5
7.5°	645.5
10°	603.4
12.5°	572.2
15°	519.1
17.5°	405.2
20°	255.6
22.5°	151.8
25°	122.7
27.5°	113.3
30°	106.0
32.5°	92.9
35°	76.2
37.5°	62.4
40°	50.1
42.5°	39.9
45°	31.2
47.5°	24.0
50°	18.2
52.5°	13.8
55°	10.9
57.5°	8.7
60°	6.5
62.5°	5.1
65°	4.4
67.5°	2.9
70°	2.2
72.5°	2.2
75°	1.5
77.5°	0.7
80°	0.7
82.5°	0.7
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)