

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273041

Luminaire Tested: P3A02R409830DE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273041
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02R409830DE010 E3D1WH
Description: 3in Adjustable LED luminaire with, R40 optic, 3000K CCT AND, 98CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 250.1 lumens
Efficiency: N/A
Efficacy: 69.5 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273041

CATALOG NUMBER: P3A02R409830DE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1273041

CATALOG NUMBER: P3A02R409830DE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	77		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	76	72	69	76	72	69		75	72	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	127424
5°	126502
10°	123200
15°	110057
20°	72970
25°	27340
30°	7318
35°	2864
40°	1031
45°	496
50°	136
55°	76
60°	44
65°	52
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 496 cd/sqm

TEST NUMBER: P1273041

CATALOG NUMBER: P3A02R409830DE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.2	21.7
10°-20°	128.4	51.4
20°-30°	58.3	23.3
30°-40°	7.6	3.0
40°-50°	1.3	0.5
50°-60°	0.2	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	240.9	96.4
0°-40°	248.5	99.4
0°-60°	250.0	100.0
0°-90°	250.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	250.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	581	
5°	575	54
15°	485	128
25°	113	58
35°	11	8
45°	2	1
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1273041

CATALOG NUMBER: P3A02R409830DE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	581.1
1°	580.8
2°	579.9
3°	578.6
4°	576.9
5°	574.7
6°	572.2
7°	569.1
8°	565.2
9°	560.0
10°	553.3
11°	545.5
12°	535.1
13°	522.2
14°	505.4
15°	484.8
16°	458.4
17°	428.4
18°	392.4
19°	354.3
20°	312.7
21°	271.1
22°	230.2
23°	189.4
24°	149.3
25°	113.0
26°	83.7
27°	61.3
28°	46.0
29°	35.8
30°	28.9
31°	23.9
32°	20.0
32.5°	18.2
33°	16.5
34°	13.4
35°	10.7
36°	8.4
37°	6.7
37.5°	6.0
38°	5.3
39°	4.4
40°	3.6
42.5°	2.4
45°	1.6



TEST NUMBER: P1273041

CATALOG NUMBER: P3A02R409830DE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	1.0
50°	0.4
52.5°	0.2
55°	0.2
57.5°	0.1
60°	0.1
62.5°	0.1
65°	0.1
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)