

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273053

Luminaire Tested: P3A02R409830DE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273053
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-22)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02R409830DE010 E3DLD1WH
Description: 3in Adjustable LED luminaire with, R40 optic, 3000K CCT AND, 98CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 160.1 lumens
Efficiency: N/A
Efficacy: 44.5 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273053

CATALOG NUMBER: P3A02R409830DE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1273053

CATALOG NUMBER: P3A02R409830DE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	66	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	57	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	35918
5°	35263
10°	33244
15°	30193
20°	26532
25°	22646
30°	18762
35°	14482
40°	10305
45°	6946
50°	3787
55°	2676
60°	2500
65°	2335
70°	2052
75°	1949
80°	1642
85°	1258

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6946 cd/sqm

TEST NUMBER: P1273053

CATALOG NUMBER: P3A02R409830DE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	14.9	9.3
10°-20°	37.1	23.1
20°-30°	42.8	26.8
30°-40°	33.8	21.1
40°-50°	17.3	10.8
50°-60°	6.6	4.2
60°-70°	4.4	2.7
70°-80°	2.4	1.5
80°-90°	0.7	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	94.8	59.2
0°-40°	128.6	80.3
0°-60°	152.6	95.3
0°-90°	160.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	160.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	164	
5°	160	15
15°	133	37
25°	94	43
35°	54	34
45°	22	17
55°	7	7
65°	4	4
75°	2	2
85°	0	1
90°	0	

TEST NUMBER: P1273053

CATALOG NUMBER: P3A02R409830DE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	163.8
2.5°	162.9
5°	160.2
7.5°	155.6
10°	149.3
12.5°	142.0
15°	133.0
17.5°	123.7
20°	113.7
22.5°	103.5
25°	93.6
27.5°	83.8
30°	74.1
32.5°	64.3
35°	54.1
37.5°	44.6
40°	36.0
42.5°	28.6
45°	22.4
47.5°	16.3
50°	11.1
52.5°	8.1
55°	7.0
57.5°	6.3
60°	5.7
62.5°	5.0
65°	4.5
67.5°	3.8
70°	3.2
72.5°	2.7
75°	2.3
77.5°	1.8
80°	1.3
82.5°	1.1
85°	0.5
87.5°	0.4
90°	0.0

(END OF REPORT)