

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273524

Luminaire Tested: P3A05R659830DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273524
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R659830DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 98CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 442.0 lumens
Efficiency: N/A
Efficacy: 61.4 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273524

CATALOG NUMBER: P3A05R659830DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1273524

CATALOG NUMBER: P3A05R659830DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	118433
5°	109971
10°	106344
15°	102498
20°	94742
25°	86328
30°	66694
35°	38655
40°	15343
45°	6543
50°	1535
55°	191
60°	175
65°	104
70°	128
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 6543 cd/sqm

TEST NUMBER: P1273524

CATALOG NUMBER: P3A05R659830DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	47.1	10.7
10°-20°	125.8	28.5
20°-30°	159.2	36.0
30°-40°	90.6	20.5
40°-50°	18.0	4.1
50°-60°	0.9	0.2
60°-70°	0.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	332.1	75.1
0°-40°	422.8	95.6
0°-60°	441.7	99.9
0°-90°	442.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	442.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	540	
5°	500	47
15°	452	126
25°	357	159
35°	144	91
45°	21	18
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1273524

CATALOG NUMBER: P3A05R659830DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	540.1
1°	536.1
2°	527.4
3°	517.2
4°	507.2
5°	499.6
6°	494.0
7°	489.4
8°	485.4
9°	481.4
10°	477.6
11°	473.4
12°	469.1
13°	463.8
14°	458.2
15°	451.5
16°	443.5
17°	434.7
18°	425.3
19°	415.3
20°	406.0
21°	396.6
22°	388.1
23°	379.2
24°	368.8
25°	356.8
26°	342.5
27°	325.2
28°	305.8
29°	285.0
30°	263.4
31°	239.6
32°	216.0
32.5°	203.8
33°	192.0
34°	168.0
35°	144.4
36°	122.6
37°	101.0
37.5°	89.9
38°	81.0
39°	65.6
40°	53.6
42.5°	33.1
45°	21.1

TEST NUMBER: P1273524

CATALOG NUMBER: P3A05R659830DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	12.4
50°	4.5
52.5°	0.9
55°	0.5
57.5°	0.4
60°	0.4
62.5°	0.4
65°	0.2
67.5°	0.2
70°	0.2
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)