

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1273597

Luminaire Tested: P3A09R159830DE010 E3DLP1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1273597
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R159830DE010 E3DLP1LI
Description: 3in Adjustable LED luminaire with, R15 optic, 3000K CCT AND, 98CRI , E3DLP1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 337.0 lumens
Efficiency: N/A
Efficacy: 30.6 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1273597

CATALOG NUMBER: P3A09R159830DE010 E3DLP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1273597

CATALOG NUMBER: P3A09R159830DE010 E3DLP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	106	111	108	106	104	104	102	101		100	99	98		97
2	108	103	98	95	105	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	93	84	78	74	91	83	78	74	81	77	73		80	76	73		78
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74
7	84	75	69	65	83	74	69	65	73	68	64		72	67	64		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		68
9	77	68	62	58	76	67	62	58	66	61	58		65	61	57		64
10	74	64	59	55	73	64	59	55	63	58	55		62	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	145317
5°	134316
10°	107235
15°	80999
20°	61675
25°	47011
30°	33676
35°	21978
40°	13482
45°	8156
50°	5424
55°	4167
60°	3596
65°	3113
70°	2821
75°	2796
80°	2020
85°	1258

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8156 cd/sqm

TEST NUMBER: P1273597

CATALOG NUMBER: P3A09R159830DE010 E3DLP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.1	16.0
10°-20°	99.7	29.6
20°-30°	88.8	26.3
30°-40°	52.5	15.6
40°-50°	21.6	6.4
50°-60°	10.1	3.0
60°-70°	6.2	1.8
70°-80°	3.2	1.0
80°-90°	0.8	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	242.6	72.0
0°-40°	295.1	87.6
0°-60°	326.8	97.0
0°-90°	337.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	337.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	663	
5°	610	54
15°	357	100
25°	194	89
35°	82	53
45°	26	22
55°	11	10
65°	6	6
75°	3	3
85°	0	1
90°	0	

TEST NUMBER: P1273597

CATALOG NUMBER: P3A09R159830DE010 E3DLP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	662.7
1°	661.1
2°	656.2
3°	646.3
4°	629.9
5°	610.2
6°	588.8
7°	563.7
8°	537.4
9°	510.6
10°	481.6
12.5°	415.4
15°	356.8
17.5°	306.5
20°	264.3
22.5°	227.1
25°	194.3
27.5°	162.5
30°	133.0
32.5°	106.2
35°	82.1
37.5°	62.9
40°	47.1
42.5°	35.0
45°	26.3
47.5°	20.2
50°	15.9
52.5°	13.1
55°	10.9
57.5°	9.3
60°	8.2
62.5°	7.1
65°	6.0
67.5°	5.5
70°	4.4
72.5°	3.8
75°	3.3
77.5°	2.2
80°	1.6
82.5°	1.1
85°	0.5
87.5°	0.5
90°	0.0

(END OF REPORT)