

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274128

Luminaire Tested: P3A13R509830DE010 E3D1LI

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274128
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A13R509830DE010 E3D1LI
Description: 3in Adjustable LED luminaire with, R50 optic, 3000K CCT AND, 98CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1008.1 lumens
Efficiency: N/A
Efficacy: 69.5 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274128

CATALOG NUMBER: P3A13R509830DE010 E3D1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1274128

CATALOG NUMBER: P3A13R509830DE010 E3D1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	105	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	92	88	85	90	87	84		88	85	83		87
5	96	89	84	80	94	88	83	79	86	82	79		84	81	78		83
6	92	84	79	75	91	83	78	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76
8	84	76	71	67	83	76	71	67	74	70	67		74	69	66		73
9	81	73	67	64	80	72	67	64	71	67	63		70	66	63		70
10	78	69	64	61	77	69	64	61	68	64	60		67	63	60		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	352252
5°	342878
10°	327204
15°	296211
20°	256269
25°	210206
30°	120753
35°	37504
40°	10076
45°	3535
50°	853
55°	268
60°	175
65°	208
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3535 cd/sqm

TEST NUMBER: P1274128
 CATALOG NUMBER: P3A13R509830DE010 E3D1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	145.9	14.5
10°-20°	361.5	35.9
20°-30°	380.0	37.7
30°-40°	108.8	10.8
40°-50°	10.6	1.1
50°-60°	0.9	0.1
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	887.4	88.0
0°-40°	996.2	98.8
0°-60°	1007.7	100.0
0°-90°	1008.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1008.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1606	
5°	1558	146
15°	1305	362
25°	869	380
35°	140	109
45°	11	11
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1274128

CATALOG NUMBER: P3A13R509830DE010 E3D1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1606.4
1°	1603.9
2°	1596.8
3°	1586.5
4°	1572.6
5°	1557.7
6°	1541.7
7°	1524.6
8°	1508.6
9°	1490.1
10°	1469.5
11°	1445.7
12°	1418.3
13°	1384.1
14°	1347.2
15°	1304.8
16°	1260.0
17°	1216.6
18°	1172.2
19°	1133.1
20°	1098.2
21°	1064.8
22°	1026.7
23°	983.0
24°	931.8
25°	868.8
26°	800.5
27°	724.4
28°	648.7
29°	566.9
30°	476.9
31°	392.6
32°	315.1
32.5°	281.3
33°	247.2
34°	189.6
35°	140.1
36°	102.8
37°	76.5
37.5°	66.1
38°	57.3
39°	44.5
40°	35.2
42.5°	19.9
45°	11.4

TEST NUMBER: P1274128

CATALOG NUMBER: P3A13R509830DE010 E3D1LI

CANDELA DISTRIBUTION (continued):

	0°
47.5°	6.4
50°	2.5
52.5°	1.1
55°	0.7
57.5°	0.7
60°	0.4
62.5°	0.4
65°	0.4
67.5°	0.4
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)