

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274252

Luminaire Tested: P3A13R709830DE010 E3DL1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274252
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-45)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A13R709830DE010 E3DL1WH
Description: 3in Adjustable LED luminaire with, R70 optic, 3000K CCT AND, 98CRI , E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 522.0 lumens
Efficiency: N/A
Efficacy: 36.0 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274252

CATALOG NUMBER: P3A13R709830DE010 E3DL1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1274252

CATALOG NUMBER: P3A13R709830DE010 E3DL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	97	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	88	83	98	92	87	83	89	85	81		87	83	80		84
4	95	86	80	76	93	85	80	75	83	78	74		81	77	73		79
5	89	80	74	69	88	79	73	69	78	72	68		76	71	68		74
6	85	75	68	64	83	74	68	64	73	67	63		71	66	63		70
7	80	70	64	59	79	69	63	59	68	62	58		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	62	55	51	71	61	55	51	60	55	51		59	54	51		58
10	69	58	52	48	67	58	52	48	57	51	48		56	51	48		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	122446
5°	120185
10°	113336
15°	102861
20°	89981
25°	75900
30°	62136
35°	48211
40°	34493
45°	21832
50°	10882
55°	6652
60°	5745
65°	5292
70°	4680
75°	4321
80°	3662
85°	3774

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 21832 cd/sqm

TEST NUMBER: P1274252

CATALOG NUMBER: P3A13R709830DE010 E3DL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	51.0	9.8
10°-20°	126.1	24.2
20°-30°	143.6	27.5
30°-40°	112.3	21.5
40°-50°	55.2	10.6
50°-60°	17.0	3.2
60°-70°	10.1	1.9
70°-80°	5.4	1.0
80°-90°	1.6	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	320.6	61.4
0°-40°	432.9	82.9
0°-60°	505.0	96.7
0°-90°	522.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	522.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	558	
5°	546	51
15°	453	126
25°	314	144
35°	180	112
45°	70	55
55°	17	17
65°	10	10
75°	5	5
85°	2	2
90°	0	

TEST NUMBER: P1274252

CATALOG NUMBER: P3A13R709830DE010 E3DL1WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	558.4
2.5°	555.5
5°	546.0
7.5°	530.8
10°	509.0
12.5°	483.6
15°	453.1
17.5°	420.4
20°	385.6
22.5°	349.3
25°	313.7
27.5°	278.8
30°	245.4
32.5°	212.0
35°	180.1
37.5°	149.6
40°	120.5
42.5°	93.7
45°	70.4
47.5°	49.4
50°	31.9
52.5°	21.1
55°	17.4
57.5°	15.2
60°	13.1
62.5°	11.6
65°	10.2
67.5°	8.7
70°	7.3
72.5°	5.8
75°	5.1
77.5°	4.4
80°	2.9
82.5°	2.2
85°	1.5
87.5°	0.7
90°	0.0

(END OF REPORT)