

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1274265

Luminaire Tested: P3A17R159830DE010 E3CD1MB

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1274265
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-4)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A17R159830DE010 E3CD1MB
Description: 3in Adjustable LED luminaire with, R15 optic, 3000K CCT AND, 98CRI , E3CD1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1485.9 lumens
Efficiency: N/A
Efficacy: 72.8 lumens/watt
Spacing Criteria (0/90/45): 0.3 / 0.3 / 0.29
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1274265

CATALOG NUMBER: P3A17R159830DE010 E3CD1MB

Luminous Intensity Polar Plot



TEST NUMBER: P1274265

CATALOG NUMBER: P3A17R159830DE010 E3CD1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102
1	116	114	112	111	113	112	110	109	108	107	106	104	103	103	101	100	100
2	113	110	107	105	111	108	106	104	105	103	101	102	101	99	99	98	97
3	110	106	103	100	108	105	102	100	102	100	98	100	98	97	98	97	95
4	107	103	100	97	106	102	99	97	100	97	95	98	96	94	97	95	93
5	105	100	97	94	104	99	96	94	98	95	93	96	94	92	95	93	92
6	103	98	94	92	102	97	94	92	96	93	91	95	92	91	94	92	90
7	101	96	92	90	100	95	92	90	94	91	89	93	91	89	92	90	89
8	99	94	90	88	98	93	90	88	92	90	88	92	89	87	91	89	87
9	97	92	89	87	97	92	89	87	91	88	86	90	88	86	90	87	86
10	96	90	87	85	95	90	87	85	89	87	85	89	86	85	88	86	85

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2888431
5°	2420795
10°	1140282
15°	343793
20°	127201
25°	49454
30°	18433
35°	5648
40°	2004
45°	1085
50°	785
55°	879
60°	1009
65°	623
70°	769
75°	1017
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1085 cd/sqm

TEST NUMBER: P1274265

CATALOG NUMBER: P3A17R159830DE010 E3CD1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	850.2	57.2
10°-20°	505.4	34.0
20°-30°	106.2	7.1
30°-40°	17.1	1.2
40°-50°	2.9	0.2
50°-60°	2.1	0.1
60°-70°	1.3	0.1
70°-80°	0.8	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1461.8	98.4
0°-40°	1478.9	99.5
0°-60°	1483.8	99.9
0°-90°	1485.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1485.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13172	
5°	10998	850
15°	1514	505
25°	204	106
35°	21	17
45°	4	3
55°	2	2
65°	1	1
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P1274265

CATALOG NUMBER: P3A17R159830DE010 E3CD1MB

CANDELA DISTRIBUTION (FULL):

0°	
0°	13172.3
1°	13131.2
2°	12922.0
3°	12503.8
4°	11890.5
5°	10997.7
6°	9948.5
7°	8749.0
8°	7603.6
9°	6306.5
10°	5121.1
12.5°	2763.2
15°	1514.4
17.5°	887.0
20°	545.1
22.5°	333.7
25°	204.4
27.5°	123.4
30°	72.8
32.5°	41.1
35°	21.1
37.5°	11.7
40°	7.0
42.5°	4.7
45°	3.5
47.5°	2.3
50°	2.3
52.5°	2.3
55°	2.3
57.5°	2.3
60°	2.3
62.5°	1.2
65°	1.2
67.5°	1.2
70°	1.2
72.5°	1.2
75°	1.2
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)