

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1295858

Luminaire Tested: P3A13R20W2N902765DE010 E3DL1GPH_4000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1295858
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-7)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A13R20W2N902765DE010 E3DL1GPH_4000K
Description: 3in Adjustable Tunable White LED luminaire with, R20 optic, 4000K CCT AND, 90CRI ,
E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 394.0 lumens
Efficiency: N/A
Efficacy: 32.0 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.46
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 12.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1295858

CATALOG NUMBER: P3A13R20W2N902765DE010 E3DL1GPH_4000K

Luminous Intensity Polar Plot





TEST NUMBER: P1295858

CATALOG NUMBER: P3A13R20W2N902765DE010 E3DL1GPH_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95						
2	110	106	102	100	108	104	101	98	101	98	96	98	96	94	95	94	92	91						
3	106	100	96	93	104	99	95	92	97	93	91	94	92	89	92	90	88	87						
4	102	96	91	88	100	95	90	87	92	89	86	91	88	85	89	86	84	83						
5	98	91	87	83	97	90	86	83	89	85	82	87	84	81	86	83	81	79						
6	95	87	83	79	93	87	82	79	85	81	78	84	81	78	83	80	77	76						
7	91	84	79	76	90	83	79	76	82	78	75	81	78	75	80	77	75	73						
8	88	81	76	73	87	80	76	73	79	75	72	78	75	72	78	74	72	71						
9	85	78	73	70	85	77	73	70	77	73	70	76	72	69	75	72	69	68						
10	83	75	71	68	82	75	70	67	74	70	67	73	70	67	73	69	67	66						

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	303134
5°	275566
10°	203648
15°	125971
20°	71943
25°	41083
30°	23042
35°	12528
40°	6870
45°	3783
50°	2217
55°	1606
60°	1491
65°	1401
70°	1218
75°	1271
80°	1010
85°	1006

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3783 cd/sqm

TEST NUMBER: P1295858

CATALOG NUMBER: P3A13R20W2N902765DE010 E3DL1GPH_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	108.4	27.5
10°-20°	154.8	39.3
20°-30°	80.8	20.5
30°-40°	31.2	7.9
40°-50°	10.1	2.6
50°-60°	4.0	1.0
60°-70°	2.6	0.7
70°-80°	1.5	0.4
80°-90°	0.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	343.9	87.3
0°-40°	375.2	95.2
0°-60°	389.3	98.8
0°-90°	394.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	394.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1382	
5°	1252	108
15°	555	155
25°	170	81
35°	47	31
45°	12	10
55°	4	4
65°	3	3
75°	2	2
85°	0	1
90°	0	



TEST NUMBER: P1295858

CATALOG NUMBER: P3A13R20W2N902765DE010 E3DL1GPH_4000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1382.4
1°	1379.8
2°	1363.4
3°	1338.3
4°	1299.4
5°	1251.9
6°	1195.5
7°	1133.1
8°	1060.8
9°	990.4
10°	914.6
12.5°	727.0
15°	554.9
17.5°	415.3
20°	308.3
22.5°	228.4
25°	169.8
27.5°	125.2
30°	91.0
32.5°	65.8
35°	46.8
37.5°	33.9
40°	24.0
42.5°	17.1
45°	12.2
47.5°	8.8
50°	6.5
52.5°	4.9
55°	4.2
57.5°	3.8
60°	3.4
62.5°	3.0
65°	2.7
67.5°	2.3
70°	1.9
72.5°	1.9
75°	1.5
77.5°	1.1
80°	0.8
82.5°	0.8
85°	0.4
87.5°	0.4
90°	0.0

(END OF REPORT)