

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1288253

Luminaire Tested: P3A05R20W2N902765DE010 E3D1WH_2700K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1288253
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-8)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R20W2N902765DE010 E3D1WH_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R20 optic, 2700K CCT AND, 90CRI ,
E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 450.0 lumens
Efficiency: N/A
Efficacy: 76.3 lumens/watt
Spacing Criteria (0/90/45): 0.35 / 0.35 / 0.34
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1288253

CATALOG NUMBER: P3A05R20W2N902765DE010 E3D1WH_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1288253

CATALOG NUMBER: P3A05R20W2N902765DE010 E3D1WH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	115	114	112	110	113	111	110	108	107	106	105	104	103	102	100	100	99	97		
2	112	109	106	104	110	107	105	103	104	102	101	101	100	98	99	98	96	95		
3	109	105	102	99	107	104	101	98	101	99	97	99	97	95	97	95	94	93		
4	106	101	98	95	105	100	97	95	99	96	94	97	94	93	95	93	92	91		
5	104	98	95	92	102	98	94	92	96	93	91	95	92	90	93	91	90	89		
6	101	96	92	89	100	95	92	89	94	91	89	93	90	88	92	89	88	87		
7	99	93	90	87	98	93	89	87	92	89	86	91	88	86	90	87	86	85		
8	97	91	87	85	96	91	87	85	90	87	85	89	86	84	88	86	84	83		
9	95	89	85	83	94	89	85	83	88	85	83	87	84	82	87	84	82	81		
10	93	87	84	81	92	87	83	81	86	83	81	86	83	81	85	83	81	80		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	682621
5°	574729
10°	358978
15°	134212
20°	46064
25°	19211
30°	9039
35°	4042
40°	1918
45°	992
50°	375
55°	76
60°	88
65°	104
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 992 cd/sqm

TEST NUMBER: P1288253

CATALOG NUMBER: P3A05R20W2N902765DE010 E3D1WH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	217.1	48.2
10°-20°	178.9	39.7
20°-30°	40.6	9.0
30°-40°	10.3	2.3
40°-50°	2.6	0.6
50°-60°	0.3	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	436.6	97.0
0°-40°	447.0	99.3
0°-60°	449.9	100.0
0°-90°	450.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	450.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3113	
5°	2611	217
15°	591	179
25°	79	41
35°	15	10
45°	3	3
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1288253

CATALOG NUMBER: P3A05R20W2N902765DE010 E3D1WH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	3113.0
1°	3086.6
2°	3008.8
3°	2897.3
4°	2760.4
5°	2611.0
6°	2444.6
7°	2260.9
8°	2046.6
9°	1834.2
10°	1612.2
11°	1375.9
12°	1139.9
13°	940.1
14°	749.0
15°	591.2
16°	466.6
17°	368.1
18°	295.8
19°	240.5
20°	197.4
21°	165.0
22°	137.8
23°	114.5
24°	95.5
25°	79.4
27.5°	51.9
30°	35.7
32.5°	22.0
35°	15.1
37.5°	9.7
40°	6.7
42.5°	4.6
45°	3.2
47.5°	2.1
50°	1.1
52.5°	0.5
55°	0.2
57.5°	0.2
60°	0.2
62.5°	0.2
65°	0.2
67.5°	0.0
70°	0.0
72.5°	0.0



TEST NUMBER: P1288253

CATALOG NUMBER: P3A05R20W2N902765DE010 E3D1WH_2700K

CANDELA DISTRIBUTION (continued):

	0°
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)