

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1288496

Luminaire Tested: P3A05R25W2N902750DE010 E3DLP1WMH_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1288496
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R25W2N902750DE010 E3DLP1WMH_3000K
Description: 3in Adjustable Tunable White LED luminaire with, R25 optic, 3000K CCT AND, 90CRI ,
E3DLP1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 254.0 lumens
Efficiency: N/A
Efficacy: 43.1 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1288496

CATALOG NUMBER: P3A05R25W2N902750DE010 E3DLP1WMH_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1288496

CATALOG NUMBER: P3A05R25W2N902750DE010 E3DLP1WMH_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10		0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102		100
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97	96	95		93
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92	90	88		86
3	102	95	90	86	100	94	89	86	91	87	84		89	86	83		87	84	82		80
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82	79	76		75
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78	74	71		70
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74	70	67		66
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70	66	63		62
8	80	70	65	60	79	70	64	60	69	64	60		68	63	60		67	63	60		58
9	76	67	61	57	75	66	61	57	65	60	57		64	60	57		64	59	56		55
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61	57	54		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	92208
5°	88466
10°	77509
15°	62293
20°	47861
25°	36220
30°	26181
35°	17373
40°	10534
45°	6140
50°	3923
55°	3173
60°	2763
65°	2491
70°	2052
75°	2033
80°	1515
85°	2013

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 6140 cd/sqm

TEST NUMBER: P1288496

CATALOG NUMBER: P3A05R25W2N902750DE010 E3DLP1WMH_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	36.6	14.4
10°-20°	75.9	29.9
20°-30°	68.6	27.0
30°-40°	41.2	16.2
40°-50°	16.4	6.4
50°-60°	7.5	3.0
60°-70°	4.6	1.8
70°-80°	2.5	1.0
80°-90°	0.7	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	181.1	71.3
0°-40°	222.3	87.5
0°-60°	246.2	96.9
0°-90°	254.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	254.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	420	
5°	402	37
15°	274	76
25°	150	69
35°	65	41
45°	20	16
55°	8	8
65°	5	5
75°	2	2
85°	1	1
90°	0	



TEST NUMBER: P1288496

CATALOG NUMBER: P3A05R25W2N902750DE010 E3DLP1WMH_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	420.5
1°	420.5
2°	418.6
3°	414.2
4°	408.7
5°	401.9
6°	393.2
7°	383.3
8°	371.8
9°	360.3
10°	348.1
11°	333.8
12°	319.2
13°	304.5
14°	289.9
15°	274.4
17.5°	238.0
20°	205.1
22.5°	175.4
25°	149.7
27.5°	125.5
30°	103.4
32.5°	83.2
35°	64.9
37.5°	49.5
40°	36.8
42.5°	26.9
45°	19.8
47.5°	15.0
50°	11.5
52.5°	9.5
55°	8.3
57.5°	7.1
60°	6.3
62.5°	5.1
65°	4.8
67.5°	4.0
70°	3.2
72.5°	2.8
75°	2.4
77.5°	2.0
80°	1.2
82.5°	0.8
85°	0.8
87.5°	0.4



TEST NUMBER: P1288496

CATALOG NUMBER: P3A05R25W2N902750DE010 E3DLP1WMH_3000K

CANDELA DISTRIBUTION (continued):



(END OF REPORT)