

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1289634

Luminaire Tested: P3A05R40W2N902765DE010 E3DLD1MW_3500K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1289634
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-22)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R40W2N902765DE010 E3DLD1MW_3500K
Description: 3in Adjustable Tunable White LED luminaire with, R40 optic, 3500K CCT AND, 90CRI ,
E3DLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 359.0 lumens
Efficiency: N/A
Efficacy: 60.8 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1289634

CATALOG NUMBER: P3A05R40W2N902765DE010 E3DLD1MW_3500K

Luminous Intensity Polar Plot



CATALOG NUMBER: P3A05R40W2N902765DE010 E3DLD1MW_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20		
RC	80					70					50					30					0		
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		0				
RCR																							
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102		100
1	112	109	106	104		110	107	104	102		103	101	99		99	98	96		96	94	93		91
2	106	100	96	92		104	98	94	91		95	92	89		92	89	87		89	87	85		83
3	100	92	87	82		98	91	86	81		88	84	80		86	82	79		83	80	78		76
4	94	85	79	74		92	84	78	74		82	77	73		80	75	72		78	74	71		69
5	89	79	73	68		87	78	72	67		76	71	67		75	70	66		73	69	66		64
6	84	74	67	62		82	73	67	62		71	66	61		70	65	61		68	64	61		59
7	79	69	62	57		78	68	62	57		67	61	57		65	60	57		64	60	56		55
8	75	64	58	53		74	64	58	53		63	57	53		62	56	53		61	56	52		51
9	71	60	54	50		70	60	54	50		59	53	49		58	53	49		57	52	49		48
10	67	57	51	46		66	56	50	46		56	50	46		55	50	46		54	49	46		45

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	80586
5°	79133
10°	74592
15°	67742
20°	59505
25°	50834
30°	42108
35°	32471
40°	23100
45°	15568
50°	8494
55°	6002
60°	5657
65°	5189
70°	4616
75°	4406
80°	3536
85°	3019

MAXIMUM LUMINANCE 45°-90°:

Luminance: 15568 cd/sqm

TEST NUMBER: P1289634

CATALOG NUMBER: P3A05R40W2N902765DE010 E3DLD1MW_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	33.5	9.3
10°-20°	83.1	23.2
20°-30°	96.1	26.8
30°-40°	75.7	21.1
40°-50°	38.9	10.8
50°-60°	14.9	4.1
60°-70°	9.8	2.7
70°-80°	5.3	1.5
80°-90°	1.6	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	212.8	59.3
0°-40°	288.5	80.4
0°-60°	342.3	95.3
0°-90°	359.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	359.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	368	
5°	360	34
15°	298	83
25°	210	96
35°	121	76
45°	50	39
55°	16	15
65°	10	10
75°	5	5
85°	1	2
90°	0	

TEST NUMBER: P1289634

CATALOG NUMBER: P3A05R40W2N902765DE010 E3DLD1MW_3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	367.5
2.5°	365.5
5°	359.5
7.5°	349.0
10°	335.0
12.5°	318.5
15°	298.4
17.5°	277.5
20°	255.0
22.5°	232.2
25°	210.1
27.5°	188.0
30°	166.3
32.5°	144.2
35°	121.3
37.5°	100.0
40°	80.7
42.5°	64.3
45°	50.2
47.5°	36.6
50°	24.9
52.5°	18.1
55°	15.7
57.5°	14.1
60°	12.9
62.5°	11.2
65°	10.0
67.5°	8.4
70°	7.2
72.5°	6.0
75°	5.2
77.5°	4.0
80°	2.8
82.5°	2.4
85°	1.2
87.5°	0.8
90°	0.0

(END OF REPORT)