

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1289914

Luminaire Tested: P3A05R45W2N902765DE010 E3DLD1WH_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1289914
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R45W2N902765DE010 E3DLD1WH_3000K
Description: 3in Adjustable Tunable White LED luminaire with, R45 optic, 3000K CCT AND, 90CRI ,
E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 343.0 lumens
Efficiency: N/A
Efficacy: 58.1 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1289914

CATALOG NUMBER: P3A05R45W2N902765DE010 E3DLD1WH_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1289914

CATALOG NUMBER: P3A05R45W2N902765DE010 E3DLD1WH_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20				20				20
RC	80				70				50				30				10				0				0				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0				0				0
RCR																													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100											
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91											
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83											
3	99	92	86	82	97	90	85	81	88	83	80	85	81	78	83	80	77	75											
4	94	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69											
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63											
6	83	73	66	61	81	72	66	61	71	65	61	69	64	60	68	63	60	58											
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	64	59	55	54											
8	74	64	57	52	73	63	57	52	62	56	52	61	56	52	60	55	52	50											
9	70	60	53	49	69	59	53	49	58	52	48	57	52	48	56	52	48	47											
10	67	56	50	45	66	56	49	45	55	49	45	54	49	45	53	48	45	44											

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	72713
5°	71428
10°	67601
15°	61658
20°	54511
25°	47350
30°	40639
35°	33863
40°	25219
45°	15443
50°	7164
55°	5582
60°	5394
65°	4929
70°	4552
75°	4321
80°	4041
85°	3019

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15443 cd/sqm

TEST NUMBER: P1289914

CATALOG NUMBER: P3A05R45W2N902765DE010 E3DLD1WH_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.3	8.8
10°-20°	75.6	22.0
20°-30°	89.8	26.2
30°-40°	78.0	22.8
40°-50°	39.1	11.4
50°-60°	13.6	4.0
60°-70°	9.5	2.8
70°-80°	5.3	1.5
80°-90°	1.6	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	195.8	57.1
0°-40°	273.8	79.8
0°-60°	326.5	95.2
0°-90°	343.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	343.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	332	
5°	324	30
15°	272	76
25°	196	90
35°	126	78
45°	50	39
55°	15	14
65°	10	10
75°	5	5
85°	1	2
90°	0	

TEST NUMBER: P1289914

CATALOG NUMBER: P3A05R45W2N902765DE010 E3DLD1WH_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	331.6
2.5°	330.1
5°	324.5
7.5°	315.8
10°	303.6
12.5°	288.6
15°	271.6
17.5°	252.6
20°	233.6
22.5°	214.2
25°	195.7
27.5°	177.9
30°	160.5
32.5°	143.9
35°	126.5
37.5°	107.9
40°	88.1
42.5°	68.8
45°	49.8
47.5°	32.8
50°	21.0
52.5°	16.2
55°	14.6
57.5°	13.4
60°	12.3
62.5°	11.1
65°	9.5
67.5°	8.3
70°	7.1
72.5°	5.9
75°	5.1
77.5°	4.0
80°	3.2
82.5°	2.4
85°	1.2
87.5°	0.8
90°	0.0

(END OF REPORT)