

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1291674

Luminaire Tested: P3A09R15W2N902765DE010 E3CB1MB_3500K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1291674
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-4)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R15W2N902765DE010 E3CB1MB_3500K
Description: 3in Adjustable Tunable White LED luminaire with, R15 optic, 3500K CCT AND, 90CRI ,
E3CB1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 748.0 lumens
Efficiency: N/A
Efficacy: 83.1 lumens/watt
Spacing Criteria (0/90/45): 0.3 / 0.3 / 0.29
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1291674

CATALOG NUMBER: P3A09R15W2N902765DE010 E3CB1MB_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P1291674

CATALOG NUMBER: P3A09R15W2N902765DE010 E3CB1MB_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	116	114	112	111	113	112	110	109	108	107	106	104	103	103	101	100	100	98						
2	113	110	107	105	111	108	106	104	105	103	101	102	101	99	99	98	97	96						
3	110	106	103	100	108	105	102	100	102	100	98	100	98	97	98	97	95	94						
4	107	103	100	97	106	102	99	97	100	97	95	98	96	94	97	95	93	92						
5	105	100	97	94	104	99	96	94	98	95	93	96	94	92	95	93	92	91						
6	103	98	94	92	102	97	94	92	96	93	91	95	92	91	94	92	90	89						
7	101	96	92	90	100	95	92	90	94	91	89	93	91	89	92	90	89	88						
8	99	94	90	88	98	93	90	88	92	90	88	92	89	87	91	89	87	86						
9	97	92	89	87	97	92	89	86	91	88	86	90	88	86	90	87	86	85						
10	96	90	87	85	95	90	87	85	89	87	85	89	86	85	88	86	85	84						

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1453941
5°	1218531
10°	573982
15°	173054
20°	64032
25°	24897
30°	9293
35°	2838
40°	1002
45°	558
50°	409
55°	459
60°	526
65°	311
70°	385
75°	508
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 558 cd/sqm

TEST NUMBER: P1291674

CATALOG NUMBER: P3A09R15W2N902765DE010 E3CB1MB_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	428.0	57.2
10°-20°	254.4	34.0
20°-30°	53.4	7.1
30°-40°	8.6	1.2
40°-50°	1.5	0.2
50°-60°	1.1	0.1
60°-70°	0.7	0.1
70°-80°	0.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	735.8	98.4
0°-40°	744.4	99.5
0°-60°	747.0	99.9
0°-90°	748.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	748.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6630	
5°	5536	428
15°	762	254
25°	103	53
35°	11	9
45°	2	1
55°	1	1
65°	1	1
75°	1	0
85°	0	0
90°	0	

TEST NUMBER: P1291674

CATALOG NUMBER: P3A09R15W2N902765DE010 E3CB1MB_3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	6630.5
1°	6609.8
2°	6504.5
3°	6294.0
4°	5985.3
5°	5535.8
6°	5007.7
7°	4403.9
8°	3827.4
9°	3174.5
10°	2577.8
12.5°	1390.9
15°	762.3
17.5°	446.5
20°	274.4
22.5°	167.9
25°	102.9
27.5°	62.1
30°	36.7
32.5°	20.7
35°	10.6
37.5°	5.9
40°	3.5
42.5°	2.4
45°	1.8
47.5°	1.2
50°	1.2
52.5°	1.2
55°	1.2
57.5°	1.2
60°	1.2
62.5°	0.6
65°	0.6
67.5°	0.6
70°	0.6
72.5°	0.6
75°	0.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)