

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1292297

Luminaire Tested: P3A09R25W2N902750DE010 E3PH1MW_3500K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1292297
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-3)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A09R25W2N902750DE010 E3PH1MW_3500K
Description: 3in Adjustable Tunable White LED luminaire with, R25 optic, 3500K CCT AND, 90CRI ,
E3PH1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 629.0 lumens
Efficiency: N/A
Efficacy: 69.9 lumens/watt
Spacing Criteria (0/90/45): 0.36 / 0.36 / 0.36
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1292297

CATALOG NUMBER: P3A09R25W2N902750DE010 E3PH1MW_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P1292297

CATALOG NUMBER: P3A09R25W2N902750DE010 E3PH1MW_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	116	114	112	111	113	112	110	109	108	107	106	104	103	102	101	100	99	98			
2	113	109	107	105	111	108	105	103	105	103	101	102	100	99	99	98	97	96			
3	110	106	103	100	108	104	102	99	102	100	98	100	98	96	98	96	95	94			
4	107	103	99	97	106	102	99	96	100	97	95	98	96	94	96	95	93	92			
5	105	100	96	94	103	99	96	93	97	95	93	96	94	92	95	93	91	90			
6	102	97	94	91	101	97	93	91	95	93	91	94	92	90	93	91	89	89			
7	100	95	92	89	99	95	91	89	94	91	89	93	90	88	92	89	88	87			
8	98	93	90	87	98	93	89	87	92	89	87	91	88	87	90	88	86	85			
9	97	91	88	86	96	91	88	85	90	87	85	89	87	85	89	86	85	84			
10	95	89	86	84	94	89	86	84	88	86	84	88	85	83	87	85	83	83			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	962028
5°	821636
10°	518004
15°	241091
20°	49634
25°	10138
30°	2152
35°	455
40°	258
45°	0
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 0 cd/sqm

TEST NUMBER: P1292297

CATALOG NUMBER: P3A09R25W2N902750DE010 E3PH1MW_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	311.1	49.5
10°-20°	288.9	45.9
20°-30°	27.3	4.3
30°-40°	1.6	0.3
40°-50°	0.1	0.0
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	627.3	99.7
0°-40°	628.9	100.0
0°-60°	629.0	100.0
0°-90°	629.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	629.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4387	
5°	3733	311
15°	1062	289
25°	42	27
35°	2	2
45°	0	0
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1292297

CATALOG NUMBER: P3A09R25W2N902750DE010 E3PH1MW_3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	4387.2
2.5°	4224.0
5°	3732.7
7.5°	3068.9
10°	2326.4
12.5°	1680.5
15°	1062.0
17.5°	513.5
20°	212.7
22.5°	84.6
25°	41.9
27.5°	19.7
30°	8.5
32.5°	3.4
35°	1.7
37.5°	0.9
40°	0.9
42.5°	0.0
45°	0.0
47.5°	0.0
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)