

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1292739

Luminaire Tested: P3A09R30W2N902765DE010 E3DL1H\_6500K

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1292739  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-15)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A09R30W2N902765DE010 E3DL1H\_6500K  
Description: 3in Adjustable Tunable White LED luminaire with, R30 optic, 6500K CCT AND, 90CRI ,  
E3DL1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 623.0 lumens  
Efficiency: N/A  
Efficacy: 69.2 lumens/watt  
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.54  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1292739

CATALOG NUMBER: P3A09R30W2N902765DE010 E3DL1H\_6500K

### Luminous Intensity Polar Plot



TEST NUMBER: P1292739

CATALOG NUMBER: P3A09R30W2N902765DE010 E3DL1H\_6500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |     |     |  | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 | 102 | 102 |  | 100 |
| 1   | 114 | 112 | 110 | 108 | 112 | 110 | 108 | 106 | 106 | 104 | 103 |  | 102 | 101 | 100 |  | 99  | 98  | 97  |  | 95  |
| 2   | 110 | 105 | 102 | 99  | 107 | 104 | 101 | 98  | 101 | 98  | 96  |  | 98  | 96  | 94  |  | 95  | 93  | 92  |  | 90  |
| 3   | 105 | 100 | 96  | 92  | 103 | 98  | 95  | 91  | 96  | 93  | 90  |  | 94  | 91  | 89  |  | 91  | 89  | 87  |  | 86  |
| 4   | 101 | 95  | 90  | 87  | 99  | 94  | 89  | 86  | 92  | 88  | 85  |  | 90  | 87  | 84  |  | 88  | 85  | 83  |  | 82  |
| 5   | 97  | 90  | 85  | 82  | 96  | 89  | 85  | 81  | 88  | 84  | 81  |  | 86  | 83  | 80  |  | 85  | 82  | 79  |  | 78  |
| 6   | 94  | 86  | 81  | 78  | 92  | 85  | 81  | 77  | 84  | 80  | 77  |  | 83  | 79  | 76  |  | 81  | 78  | 76  |  | 75  |
| 7   | 90  | 82  | 77  | 74  | 89  | 82  | 77  | 74  | 81  | 76  | 73  |  | 80  | 76  | 73  |  | 78  | 75  | 73  |  | 71  |
| 8   | 87  | 79  | 74  | 71  | 86  | 79  | 74  | 71  | 78  | 73  | 70  |  | 77  | 73  | 70  |  | 76  | 72  | 70  |  | 69  |
| 9   | 84  | 76  | 71  | 68  | 83  | 75  | 71  | 68  | 75  | 70  | 67  |  | 74  | 70  | 67  |  | 73  | 70  | 67  |  | 66  |
| 10  | 81  | 73  | 68  | 65  | 80  | 73  | 68  | 65  | 72  | 68  | 65  |  | 71  | 67  | 65  |  | 71  | 67  | 65  |  | 63  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 363545 |
| 5°  | 346004 |
| 10° | 291043 |
| 15° | 209899 |
| 20° | 130188 |
| 25° | 74037  |
| 30° | 41120  |
| 35° | 22379  |
| 40° | 11794  |
| 45° | 6388   |
| 50° | 3411   |
| 55° | 2256   |
| 60° | 2061   |
| 65° | 2127   |
| 70° | 1859   |
| 75° | 1525   |
| 80° | 1515   |
| 85° | 1510   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6388 cd/sqm

TEST NUMBER: P1292739

CATALOG NUMBER: P3A09R30W2N902765DE010 E3DL1H\_6500K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 141.5  | 22.7      |
| 10°-20°   | 251.6  | 40.4      |
| 20°-30°   | 145.4  | 23.3      |
| 30°-40°   | 55.2   | 8.9       |
| 40°-50°   | 16.9   | 2.7       |
| 50°-60°   | 5.7    | 0.9       |
| 60°-70°   | 3.8    | 0.6       |
| 70°-80°   | 2.1    | 0.3       |
| 80°-90°   | 0.7    | 0.1       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 538.6  | 86.4      |
| 0°-40°    | 593.8  | 95.3      |
| 0°-60°    | 616.4  | 98.9      |
| 0°-90°    | 623.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 623.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1658 |      |
| 5°  | 1572 | 142  |
| 15° | 925  | 252  |
| 25° | 306  | 145  |
| 35° | 84   | 55   |
| 45° | 21   | 17   |
| 55° | 6    | 6    |
| 65° | 4    | 4    |
| 75° | 2    | 2    |
| 85° | 1    | 1    |
| 90° | 0    |      |

TEST NUMBER: P1292739

CATALOG NUMBER: P3A09R30W2N902765DE010 E3DL1H\_6500K

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1657.9 |
| 1°    | 1656.7 |
| 2°    | 1646.7 |
| 3°    | 1627.9 |
| 4°    | 1604.3 |
| 5°    | 1571.9 |
| 6°    | 1530.8 |
| 7°    | 1484.8 |
| 8°    | 1433.6 |
| 9°    | 1372.4 |
| 10°   | 1307.1 |
| 11°   | 1236.5 |
| 12°   | 1161.7 |
| 13°   | 1083.5 |
| 14°   | 1004.0 |
| 15°   | 924.6  |
| 17.5° | 729.2  |
| 20°   | 557.9  |
| 22.5° | 413.7  |
| 25°   | 306.0  |
| 27.5° | 222.5  |
| 30°   | 162.4  |
| 32.5° | 117.1  |
| 35°   | 83.6   |
| 37.5° | 58.3   |
| 40°   | 41.2   |
| 42.5° | 28.8   |
| 45°   | 20.6   |
| 47.5° | 14.1   |
| 50°   | 10.0   |
| 52.5° | 7.1    |
| 55°   | 5.9    |
| 57.5° | 5.3    |
| 60°   | 4.7    |
| 62.5° | 4.1    |
| 65°   | 4.1    |
| 67.5° | 3.5    |
| 70°   | 2.9    |
| 72.5° | 2.4    |
| 75°   | 1.8    |
| 77.5° | 1.8    |
| 80°   | 1.2    |
| 82.5° | 1.2    |
| 85°   | 0.6    |
| 87.5° | 0.0    |



TEST NUMBER: P1292739

CATALOG NUMBER: P3A09R30W2N902765DE010 E3DL1H\_6500K

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)