

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1303519

Luminaire Tested: P3DUS09R609035DE010 E3CBUS1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1303519
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-93)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3DUS09R609035DE010 E3CBUS1MW
Description: 3in Adjustable LED luminaire with, R60 optic, 3500K CCT AND, 90CRI , E3CBUS1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1032.0 lumens
Efficiency: N/A
Efficacy: 93.0 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.84
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1303519

CATALOG NUMBER: P3DUS09R609035DE010 E3CBUS1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1303519

CATALOG NUMBER: P3DUS09R609035DE010 E3CBUS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	109	107		111	109	107	105		105	103	102		101	100	99		98	97	96
2	109	104	100	97		107	102	99	96		99	96	94		96	94	92		94	92	90
3	104	98	93	89		102	96	92	89		94	90	87		91	88	86		89	87	85
4	99	92	87	83		97	91	86	82		89	85	81		87	83	80		85	82	79
5	94	86	81	77		93	86	80	77		84	79	76		82	78	75		81	77	75
6	90	82	76	72		89	81	76	72		79	75	71		78	74	71		77	73	70
7	86	77	71	68		85	76	71	67		75	70	67		74	70	67		73	69	66
8	82	73	67	63		81	72	67	63		71	67	63		70	66	63		69	66	63
9	78	69	64	60		77	69	63	60		68	63	60		67	63	59		66	62	59
10	75	66	60	57		74	65	60	56		64	60	56		64	59	56		63	59	56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	290657
5°	282060
10°	284586
15°	274576
20°	232280
25°	188624
30°	139464
35°	96690
40°	34608
45°	0
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 0 cd/sqm

TEST NUMBER: P1303519

CATALOG NUMBER: P3DUS09R609035DE010 E3CBUS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	122.4	11.9
10°-20°	330.6	32.0
20°-30°	352.2	34.1
30°-40°	213.9	20.7
40°-50°	12.7	1.2
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	805.3	78.0
0°-40°	1019.3	98.8
0°-60°	1032.0	100.0
0°-90°	1032.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1032.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1326	
5°	1281	122
15°	1210	331
25°	780	352
35°	361	214
45°	0	13
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1303519

CATALOG NUMBER: P3DUS09R609035DE010 E3CBUS1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1325.5
2.5°	1305.9
5°	1281.4
7.5°	1274.9
10°	1278.1
12.5°	1263.4
15°	1209.5
17.5°	1114.7
20°	995.4
22.5°	881.0
25°	779.6
27.5°	661.9
30°	550.8
32.5°	464.2
35°	361.2
37.5°	235.4
40°	120.9
42.5°	9.8
45°	0.0
47.5°	0.0
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)