

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1303633

Luminaire Tested: P3DUS02R209040DE010 E3CBUS1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1303633
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-86)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3DUS02R209040DE010 E3CBUS1MW
Description: 3in Adjustable LED luminaire with, R20 optic, 4000K CCT AND, 90CRI , E3CBUS1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 354.0 lumens
Efficiency: N/A
Efficacy: 98.3 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.33
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1303633

CATALOG NUMBER: P3DUS02R209040DE010 E3CBUS1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1303633

CATALOG NUMBER: P3DUS02R209040DE010 E3CBUS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	116	114	112	111	113	112	110	109	108	107	106		104	103	102		101	100	100	98
2	113	109	107	105	111	108	106	104	105	103	101		102	101	99		99	98	97	96
3	110	106	103	100	108	105	102	100	102	100	98		100	98	97		98	96	95	94
4	107	103	99	97	106	102	99	96	100	97	95		98	96	94		96	95	93	92
5	105	100	97	94	104	99	96	94	98	95	93		96	94	92		95	93	91	91
6	103	98	94	92	102	97	94	91	96	93	91		95	92	90		93	91	90	89
7	101	95	92	90	100	95	92	89	94	91	89		93	90	89		92	90	88	87
8	99	93	90	88	98	93	90	88	92	89	87		91	89	87		91	88	87	86
9	97	92	88	86	96	91	88	86	90	88	86		90	87	85		89	87	85	84
10	95	90	87	85	95	90	86	84	89	86	84		88	86	84		88	86	84	83

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	599689
5°	508099
10°	295519
15°	101476
20°	29239
25°	8952
30°	2456
35°	1365
40°	658
45°	186
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 186 cd/sqm

TEST NUMBER: P1303633

CATALOG NUMBER: P3DUS02R209040DE010 E3CBUS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	189.0	53.4
10°-20°	140.6	39.7
20°-30°	20.6	5.8
30°-40°	3.3	0.9
40°-50°	0.5	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	350.2	98.9
0°-40°	353.5	99.9
0°-60°	354.0	100.0
0°-90°	354.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	354.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2735	
5°	2308	189
15°	447	141
25°	37	21
35°	5	3
45°	1	1
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1303633

CATALOG NUMBER: P3DUS02R209040DE010 E3CBUS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	2734.8
2.5°	2622.0
5°	2308.3
7.5°	1862.5
10°	1327.2
12.5°	823.9
15°	447.0
17.5°	231.2
20°	125.3
22.5°	68.9
25°	37.0
27.5°	17.7
30°	9.7
32.5°	6.8
35°	5.1
37.5°	3.4
40°	2.3
42.5°	1.1
45°	0.6
47.5°	0.0
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)