

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1304849

Luminaire Tested: P3DUS02R20B2750DE010 E3CBUS1MW_3000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1304849
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-86)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3DUS02R20B2750DE010 E3CBUS1MW_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R20 optic, 3000K CCT AND, 90CRI , E3CBUS1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 269.0 lumens
Efficiency: N/A
Efficacy: 92.8 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.33
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 2.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1304849

CATALOG NUMBER: P3DUS02R20B2750DE010 E3CBUS1MW_3000K

Luminous Intensity Polar Plot



CATALOG NUMBER: P3DUS02R20B2750DE010 E3CBUS1MW_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	116	114	112	111	113	112	110	109	108	107	106	104	103	102	101	100	100	98		
2	113	109	107	105	111	108	106	104	105	103	101	102	101	99	99	98	97	96		
3	110	106	103	100	108	105	102	100	102	100	98	100	98	97	98	96	95	94		
4	107	103	99	97	106	102	99	96	100	97	95	98	96	94	96	95	93	92		
5	105	100	97	94	104	99	96	94	98	95	93	96	94	92	95	93	91	91		
6	103	98	94	92	102	97	94	91	96	93	91	95	92	90	93	91	90	89		
7	101	95	92	90	100	95	92	89	94	91	89	93	90	89	92	90	88	87		
8	99	93	90	88	98	93	90	88	92	89	87	91	89	87	91	88	87	86		
9	97	92	88	86	96	91	88	86	90	88	86	90	87	85	89	87	85	84		
10	95	90	87	85	95	90	86	84	89	86	84	88	86	84	88	86	84	83		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	455687
5°	386087
10°	224556
15°	77095
20°	22215
25°	6799
30°	1874
35°	1044
40°	487
45°	124
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Luminance: 124 cd/sqm

TEST NUMBER: P1304849

CATALOG NUMBER: P3DUS02R20B2750DE010 E3CBUS1MW_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	143.6	53.4
10°-20°	106.9	39.7
20°-30°	15.7	5.8
30°-40°	2.5	0.9
40°-50°	0.4	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	266.1	98.9
0°-40°	268.6	99.9
0°-60°	269.0	100.0
0°-90°	269.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	269.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2078	
5°	1754	144
15°	340	107
25°	28	16
35°	4	2
45°	0	0
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1304849

CATALOG NUMBER: P3DUS02R20B2750DE010 E3CBUS1MW_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	2078.1
2.5°	1992.4
5°	1754.0
7.5°	1415.3
10°	1008.5
12.5°	626.1
15°	339.6
17.5°	175.7
20°	95.2
22.5°	52.4
25°	28.1
27.5°	13.4
30°	7.4
32.5°	5.2
35°	3.9
37.5°	2.6
40°	1.7
42.5°	0.9
45°	0.4
47.5°	0.0
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)