

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1306380

Luminaire Tested: P3SQAS02R259027DE010 E3SQCD1MB

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1306380
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-23)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3SQAS02R259027DE010 E3SQCD1MB
Description: 3in Adjustable LED luminaire with, R25 optic, 2700K CCT AND, 90CRI , E3SQCD1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 297.0 lumens
Efficiency: N/A
Efficacy: 82.5 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.45 / 0.41
Luminous Opening: Rectangular (W 0.25' x L: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1306380

CATALOG NUMBER: P3SQAS02R259027DE010 E3SQCD1MB

Luminous Intensity Polar Plot



TEST NUMBER: P1306380

CATALOG NUMBER: P3SQAS02R259027DE010 E3SQCD1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	110	113	111	110	108	107	106	105		103	103	102		100
2	112	108	105	103	110	107	104	102	104	102	100		101	99	98		98
3	108	104	101	98	107	103	100	97	100	98	96		98	96	94		96
4	105	100	97	94	104	99	96	93	97	95	92		96	93	91		94
5	103	97	93	90	101	96	93	90	95	92	89		93	91	89		92
6	100	94	90	87	99	93	90	87	92	89	87		91	88	86		90
7	97	91	87	85	96	91	87	84	90	86	84		89	86	84		88
8	95	89	85	82	94	88	85	82	87	84	82		87	84	82		86
9	93	86	83	80	92	86	82	80	85	82	80		85	82	80		84
10	91	84	81	78	90	84	80	78	83	80	78		83	80	78		82

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	245727	245727	245727
5°	226577	227096	227563
10°	175929	176558	177520
15°	86938	90593	90629
20°	29269	31230	29856
25°	12124	13473	12466
30°	4753	5986	4813
35°	1240	2439	1304
40°	472	967	472
45°	49	268	49
50°	0	54	0
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 45°

Vertical Angle: 45°

Luminance: 268 cd/sqm

TEST NUMBER: P1306380

CATALOG NUMBER: P3SQAS02R259027DE010 E3SQCD1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	115.6	38.9
10°-20°	139.8	47.1
20°-30°	34.1	11.5
30°-40°	6.6	2.2
40°-50°	0.8	0.3
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	289.6	97.5
0°-40°	296.2	99.7
0°-60°	297.0	100.0
0°-90°	297.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	297.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1427	1427	1427	1427	1427	
5°	1311	1312	1314	1319	1316	115
15°	488	499	508	513	508	137
25°	64	67	71	68	66	32
35°	6	8	12	8	6	5
45°	0	1	1	1	0	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P1306380

CATALOG NUMBER: P3SQAS02R259027DE010 E3SQCD1MB

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1426.8	1426.8	1426.8	1426.8	1426.8
1°	1421.4	1422.3	1422.5	1423.9	1421.1
2°	1408.4	1408.6	1409.3	1412.0	1409.5
3°	1384.5	1386.1	1386.3	1389.9	1390.6
4°	1351.9	1352.8	1354.6	1360.8	1355.3
5°	1310.6	1312.5	1313.6	1319.3	1316.3
6°	1259.6	1260.0	1262.6	1269.2	1265.1
7°	1207.6	1207.4	1207.6	1212.9	1211.7
8°	1145.0	1143.8	1147.5	1153.9	1158.2
9°	1079.6	1081.2	1083.5	1089.6	1084.6
10°	1006.0	1010.3	1009.6	1010.1	1015.1
11°	921.2	922.6	922.8	927.6	926.9
12°	821.6	821.6	829.2	836.9	834.4
13°	721.2	728.2	723.2	724.8	734.8
14°	604.0	609.5	616.4	622.7	617.7
15°	487.6	499.2	508.1	513.1	508.3
17.5°	279.4	283.2	290.7	291.7	288.7
20°	159.7	164.5	170.4	168.6	162.9
22.5°	100.5	101.9	107.8	104.8	103.4
25°	63.8	67.2	70.9	67.9	65.6
27.5°	39.6	41.9	45.8	42.6	40.1
30°	23.9	26.0	30.1	25.7	24.2
32.5°	12.5	15.5	18.9	15.7	12.5
35°	5.9	8.4	11.6	8.4	6.2
37.5°	3.6	4.6	7.1	4.6	3.6
40°	2.1	3.0	4.3	3.0	2.1
42.5°	0.9	1.6	2.1	1.6	1.1
45°	0.2	0.7	1.1	0.7	0.2
47.5°	0.0	0.0	0.7	0.2	0.0
50°	0.0	0.0	0.2	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1306380

CATALOG NUMBER: P3SQAS02R259027DE010 E3SQCD1MB

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)