

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1315826

Luminaire Tested: P3SQAS02R359827DE010 E3SQPH1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1315826
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-5)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3SQAS02R359827DE010 E3SQPH1MW
Description: 3in Adjustable LED luminaire with, R35 optic, 2700K CCT AND, 98CRI , E3SQPH1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 193.0 lumens
Efficiency: N/A
Efficacy: 53.6 lumens/watt
Spacing Criteria (0/90/45): 0.57 / 0.56 / 0.51
Luminous Opening: Rectangular (W 0.25' x L: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1315826

CATALOG NUMBER: P3SQAS02R359827DE010 E3SQPH1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1315826

CATALOG NUMBER: P3SQAS02R359827DE010 E3SQPH1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	113	111	109	108	107	106	104		103	102	101		100
2	111	108	105	102	109	106	103	101	103	101	99		100	98	97		97
3	108	103	100	97	106	102	99	96	99	97	94		97	95	93		95
4	104	99	95	92	103	98	94	92	96	93	91		94	92	90		93
5	101	95	91	88	100	95	91	88	93	90	87		92	89	87		90
6	98	92	88	85	97	91	88	85	90	87	84		89	86	84		88
7	96	89	85	82	94	89	85	82	87	84	81		86	83	81		85
8	93	86	82	79	92	86	82	79	85	81	79		84	81	79		83
9	90	84	80	77	89	83	79	77	82	79	76		82	79	76		81
10	88	81	77	75	87	81	77	74	80	77	74		80	76	74		79

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	109516	109516	109516
5°	107635	107393	107169
10°	98649	95677	93351
15°	70642	68377	67557
20°	32751	33888	35061
25°	7772	11060	11535
30°	2287	2605	2943
35°	526	841	778
40°	112	225	157
45°	49	49	49
50°	54	0	54
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 52.5°
Luminance: 57 cd/sqm

TEST NUMBER: P1315826

CATALOG NUMBER: P3SQAS02R359827DE010 E3SQPH1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.1	29.6
10°-20°	102.1	52.9
20°-30°	30.7	15.9
30°-40°	2.9	1.5
40°-50°	0.2	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	189.9	98.4
0°-40°	192.8	99.9
0°-60°	193.0	100.0
0°-90°	193.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	193.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	636	636	636	636	636	
5°	623	622	621	620	620	58
15°	396	393	384	382	379	105
25°	41	45	58	61	61	26
35°	2	3	4	4	4	2
45°	0	0	0	0	0	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P1315826

CATALOG NUMBER: P3SQAS02R359827DE010 E3SQPH1MW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	635.9	635.9	635.9	635.9	635.9
1°	635.5	635.5	635.2	635.2	634.5
2°	634.0	634.2	633.5	633.4	632.9
3°	631.7	631.2	631.2	630.9	630.5
4°	628.1	627.1	626.7	626.9	626.2
5°	622.6	622.4	621.2	620.4	619.9
6°	616.6	615.4	612.9	610.8	610.3
7°	607.6	605.1	603.0	598.5	597.8
8°	596.6	592.6	588.0	581.7	581.3
9°	583.2	576.7	570.2	561.7	558.7
10°	564.1	558.1	547.1	539.6	533.8
11°	540.3	532.8	520.0	511.0	506.2
12°	513.3	506.4	491.4	483.3	476.4
13°	478.8	473.0	459.0	450.0	444.7
14°	438.7	434.4	421.1	417.1	415.3
15°	396.2	393.2	383.5	381.9	378.9
17.5°	291.6	286.6	281.1	282.1	283.1
20°	178.7	185.7	184.9	188.5	191.3
22.5°	89.1	98.1	108.6	114.9	118.0
25°	40.9	45.1	58.2	60.7	60.7
27.5°	20.6	21.6	27.4	27.9	29.3
30°	11.5	12.3	13.1	14.6	14.8
32.5°	5.8	6.8	7.1	8.0	7.6
35°	2.5	3.3	4.0	4.3	3.7
37.5°	1.2	1.5	2.2	2.0	1.5
40°	0.5	0.7	1.0	0.8	0.7
42.5°	0.3	0.3	0.5	0.3	0.3
45°	0.2	0.2	0.2	0.2	0.2
47.5°	0.2	0.2	0.0	0.2	0.2
50°	0.2	0.0	0.0	0.0	0.2
52.5°	0.2	0.0	0.0	0.0	0.2
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1315826
CATALOG NUMBER: P3SQAS02R359827DE010 E3SQPH1MW

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)