

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1317608

Luminaire Tested: P3SQAS02R509835DE010 E3SQCD1MB

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1317608
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-27)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3SQAS02R509835DE010 E3SQCD1MB
Description: 3in Adjustable LED luminaire with, R50 optic, 3500K CCT AND, 98CRI , E3SQCD1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 261.0 lumens
Efficiency: N/A
Efficacy: 72.5 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.78
Luminous Opening: Rectangular (W 0.25' x L: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1317608

CATALOG NUMBER: P3SQAS02R509835DE010 E3SQCD1MB

Luminous Intensity Polar Plot



TEST NUMBER: P1317608

CATALOG NUMBER: P3SQAS02R509835DE010 E3SQCD1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	106	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	90	87	84		89	85	83		87
5	96	89	84	80	95	88	83	79	86	82	79		85	81	78		83
6	92	84	79	75	91	83	79	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76
8	85	76	71	67	83	76	71	67	75	70	67		74	70	67		73
9	81	73	67	64	80	72	67	64	71	67	64		70	66	63		70
10	78	69	64	61	77	69	64	61	68	64	60		67	63	60		67

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	69802	69802	69802
5°	68582	68392	68201
10°	66139	65422	65562
15°	60853	60086	60247
20°	54341	53828	54121
25°	42281	44067	41825
30°	22909	25574	22492
35°	7232	8599	7064
40°	1596	2226	1506
45°	49	682	49
50°	0	107	0
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 45°

Vertical Angle: 45°

Luminance: 682 cd/sqm

TEST NUMBER: P1317608

CATALOG NUMBER: P3SQAS02R509835DE010 E3SQCD1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	37.1	14.2
10°-20°	94.3	36.2
20°-30°	99.4	38.1
30°-40°	28.4	10.9
40°-50°	1.8	0.7
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	230.9	88.5
0°-40°	259.2	99.3
0°-60°	261.0	100.0
0°-90°	261.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	261.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	405	405	405	405	405	
5°	397	396	396	395	394	37
15°	341	339	337	338	338	95
25°	222	231	232	229	220	97
35°	34	37	41	35	34	27
45°	0	1	3	1	0	1
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P1317608

CATALOG NUMBER: P3SQAS02R509835DE010 E3SQCD1MB

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	405.3	405.3	405.3	405.3	405.3
1°	405.5	405.7	405.3	405.7	404.8
2°	404.9	404.6	404.2	404.4	403.8
3°	402.9	402.7	401.9	402.1	401.4
4°	400.3	399.7	399.1	398.8	398.0
5°	396.7	396.3	395.6	395.2	394.5
6°	393.7	393.0	391.7	391.3	390.6
7°	389.8	389.4	387.8	387.4	387.0
8°	386.8	385.7	383.7	383.8	382.9
9°	382.9	381.4	379.4	379.4	379.5
10°	378.2	376.0	374.1	374.7	374.9
11°	372.1	370.6	367.8	369.1	369.1
12°	365.4	363.5	361.4	362.6	363.3
13°	357.5	356.0	354.2	355.3	354.9
14°	349.9	347.1	345.8	347.2	346.7
15°	341.3	339.0	337.0	337.5	337.9
17.5°	318.3	315.9	314.4	314.6	316.3
20°	296.5	295.5	293.7	294.4	295.3
22.5°	270.7	271.1	268.8	269.4	271.6
25°	222.5	230.8	231.9	229.3	220.1
27.5°	164.8	177.2	180.9	174.9	163.7
30°	115.2	118.5	128.6	117.2	113.1
32.5°	67.6	72.6	78.0	70.2	67.4
35°	34.4	36.8	40.9	34.7	33.6
37.5°	15.9	17.0	18.7	15.9	14.9
40°	7.1	8.4	9.9	8.0	6.7
42.5°	2.2	3.9	5.2	3.5	2.1
45°	0.2	0.9	2.8	0.9	0.2
47.5°	0.0	0.2	1.1	0.2	0.0
50°	0.0	0.0	0.4	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1317608

CATALOG NUMBER: P3SQAS02R509835DE010 E3SQCD1MB

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)