

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1319371

Luminaire Tested: P3SQAS02R20B2750DE010 E3SQPH1MB_3500K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1319371
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3SQAS02R20B2750DE010 E3SQPH1MB_3500K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R20 optic, 3500K CCT AND, 80CRI , E3SQPH1MB TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 229.0 lumens
Efficiency: N/A
Efficacy: 79.0 lumens/watt
Spacing Criteria (0/90/45): 0.35 / 0.36 / 0.33
Luminous Opening: Rectangular (W 0.25' x L: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 2.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1319371

CATALOG NUMBER: P3SQAS02R20B2750DE010 E3SQPH1MB_3500K

Luminous Intensity Polar Plot



TEST NUMBER: P1319371

CATALOG NUMBER: P3SQAS02R20B2750DE010 E3SQPH1MB_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	102	102	100
1	116	114	112	111	113	112	110	109	108	107	106	104	103	102	101	100	100	100	100	98
2	113	109	107	105	111	108	106	104	105	103	101	102	101	99	99	98	97	97	97	96
3	110	106	103	100	108	105	102	100	102	100	98	100	98	97	98	96	95	95	95	94
4	107	103	99	97	106	102	99	96	100	97	95	98	96	94	96	95	93	93	93	92
5	105	100	97	94	104	99	96	94	98	95	93	96	94	92	95	93	92	92	92	91
6	103	98	94	92	102	97	94	91	96	93	91	95	92	90	93	91	90	90	90	89
7	101	95	92	90	100	95	92	89	94	91	89	93	90	89	92	90	88	88	88	87
8	99	93	90	88	98	93	90	88	92	89	87	91	89	87	91	88	87	87	87	86
9	97	92	88	86	96	91	88	86	91	88	86	90	87	86	89	87	85	85	85	85
10	95	90	87	85	95	90	87	85	89	86	84	88	86	84	88	86	84	84	84	83

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	293640	293640	293640
5°	253668	256036	256987
10°	152705	154139	161798
15°	52812	51582	55700
20°	13874	13049	13086
25°	3021	3649	4143
30°	1293	1293	1332
35°	736	652	694
40°	315	360	405
45°	97	146	146
50°	54	54	54
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°

Vertical Angle: 45°

Luminance: 146 cd/sqm

TEST NUMBER: P1319371

CATALOG NUMBER: P3SQAS02R20B2750DE010 E3SQPH1MB_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	121.9	53.3
10°-20°	92.8	40.5
20°-30°	11.5	5.0
30°-40°	2.2	0.9
40°-50°	0.5	0.2
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	226.3	98.8
0°-40°	228.4	99.8
0°-60°	229.0	100.0
0°-90°	229.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	229.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1705	1705	1705	1705	1705	
5°	1467	1466	1481	1480	1486	121
15°	296	286	289	307	312	93
25°	16	18	19	20	22	11
35°	4	4	3	3	3	2
45°	0	1	1	1	1	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P1319371

CATALOG NUMBER: P3SQAS02R20B2750DE010 E3SQPH1MB_3500K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1705.0	1705.0	1705.0	1705.0	1705.0
1°	1697.0	1695.0	1696.6	1693.1	1700.3
2°	1669.9	1667.8	1667.8	1665.8	1666.8
3°	1619.3	1622.5	1620.5	1616.2	1621.7
4°	1550.3	1554.0	1557.3	1557.5	1558.3
5°	1467.3	1466.3	1481.0	1479.9	1486.5
6°	1372.6	1371.4	1377.7	1388.3	1401.4
7°	1268.6	1253.7	1270.6	1292.0	1309.6
8°	1133.9	1137.8	1149.4	1174.7	1188.8
9°	1019.7	997.0	1021.7	1051.9	1067.2
10°	873.2	854.8	881.4	913.2	925.2
12.5°	549.6	533.7	542.3	575.7	581.0
15°	296.2	285.6	289.3	306.6	312.4
17.5°	151.2	141.6	139.5	150.6	151.8
20°	75.7	73.4	71.2	72.2	71.4
22.5°	35.1	38.2	37.7	35.7	38.2
25°	15.9	18.2	19.2	20.0	21.8
27.5°	9.8	9.4	10.8	11.6	11.8
30°	6.5	6.3	6.5	6.7	6.7
32.5°	4.7	4.5	4.3	4.3	4.5
35°	3.5	3.5	3.1	3.3	3.3
37.5°	2.4	2.4	2.2	2.4	2.4
40°	1.4	1.6	1.6	1.6	1.8
42.5°	0.8	1.0	1.0	1.0	1.0
45°	0.4	0.6	0.6	0.6	0.6
47.5°	0.2	0.2	0.2	0.4	0.4
50°	0.2	0.2	0.2	0.2	0.2
52.5°	0.2	0.0	0.0	0.0	0.2
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)