

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMARK

Report Number: P1067664

Luminaire Tested: **NAV-SA3D-722-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1067664
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMARK
Catalog Number: NAV-SA3D-722-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 3xLight Square PACKAGE
70CRI 2200K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 2200K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11593.9 lumens
Efficiency: N/A
Efficacy: 72.1 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 160.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.3 fc
 Type III - Short - N/A

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	69.0	0.0	69.0
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	11524.9	0.0	11524.9
	% Fixture	99.4	0.0	99.4
Total	Lumens	11593.8	0.0	11593.8
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.4	0.0
10°-20°	17.0	0.1
20°-30°	216.4	1.9
30°-40°	729.3	6.3
40°-50°	2202.5	19.0
50°-60°	3885.9	33.5
60°-70°	3423.4	29.5
70°-80°	1089.8	9.4
80°-90°	26.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	11593.8	100.0
0°-180°	11593.9	100.0



REPORT NUMBER: P1067664


CATALOG NUMBER: NAV-SA3D-722-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	226.5	2.0			
FM	(30°-60°)	6790.9	58.6			
FH	(60°-80°)	4486.2	38.7			G2/5000
FVH	(80°-90°)	21.3	0.2			G1/100
BL	(0°-30°)	10.3	0.1	B0/110		
BM	(30°-60°)	26.7	0.2	B0/220		
BH	(60°-80°)	27.0	0.2	B0/110		G0/110
BVH	(80°-90°)	4.9	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	25.5
5°	36.4	36.4	36.4	32.7	32.7	32.7	29.1	29.1	29.1	29.1	29.1
7.5°	43.6	40.0	40.0	36.4	36.4	36.4	32.7	32.7	32.7	32.7	29.1
10°	50.9	47.3	47.3	43.6	43.6	40.0	40.0	36.4	36.4	32.7	32.7
12.5°	58.2	54.5	50.9	47.3	47.3	43.6	43.6	40.0	40.0	36.4	36.4
15°	65.4	61.8	58.2	54.5	50.9	50.9	47.3	43.6	40.0	40.0	36.4
17.5°	76.4	69.1	65.4	58.2	54.5	50.9	47.3	43.6	43.6	40.0	40.0
20°	80.0	72.7	69.1	61.8	58.2	54.5	50.9	47.3	43.6	43.6	40.0
22.5°	94.5	80.0	76.4	69.1	65.4	61.8	54.5	50.9	47.3	43.6	40.0
25°	116.3	94.5	83.6	72.7	69.1	61.8	58.2	50.9	47.3	43.6	40.0
27.5°	141.8	105.4	94.5	80.0	72.7	65.4	58.2	50.9	47.3	43.6	40.0
30°	174.5	123.6	105.4	87.3	80.0	72.7	61.8	54.5	50.9	47.3	40.0
32.5°	243.6	152.7	123.6	94.5	83.6	76.4	65.4	54.5	50.9	47.3	40.0
35°	294.5	185.4	149.1	109.1	94.5	83.6	69.1	54.5	50.9	47.3	40.0
37.5°	341.8	189.1	152.7	116.3	101.8	87.3	69.1	54.5	50.9	47.3	40.0
40°	418.1	196.3	152.7	109.1	98.2	83.6	72.7	58.2	54.5	47.3	43.6
42.5°	563.6	225.4	163.6	101.8	90.9	83.6	72.7	61.8	54.5	50.9	43.6
45°	938.0	334.5	221.8	105.4	94.5	83.6	72.7	61.8	58.2	50.9	47.3
47.5°	1596.1	581.7	345.4	109.1	98.2	83.6	72.7	58.2	54.5	50.9	43.6
50°	2043.3	745.3	436.3	127.3	109.1	94.5	76.4	58.2	54.5	50.9	47.3
52.5°	2170.6	792.6	472.7	149.1	127.3	105.4	80.0	58.2	54.5	54.5	50.9
55°	1988.8	770.8	472.7	174.5	145.4	120.0	90.9	61.8	58.2	58.2	54.5
57.5°	1690.7	712.6	450.8	189.1	160.0	127.3	98.2	65.4	61.8	61.8	58.2
60°	1392.5	599.9	407.2	210.9	178.2	145.4	112.7	80.0	76.4	72.7	65.4
62.5°	1105.3	483.6	356.3	225.4	192.7	156.3	123.6	87.3	83.6	80.0	76.4
65°	832.6	421.8	330.9	236.3	200.0	163.6	127.3	90.9	87.3	87.3	83.6
67.5°	639.9	385.4	316.3	243.6	207.2	170.9	134.5	98.2	94.5	90.9	87.3
70°	505.4	356.3	298.1	240.0	207.2	174.5	138.2	105.4	98.2	94.5	87.3
72.5°	421.8	323.6	276.3	229.1	203.6	178.2	152.7	127.3	112.7	101.8	87.3
75°	352.7	290.9	250.9	207.2	189.1	174.5	156.3	138.2	120.0	101.8	83.6
77.5°	232.7	210.9	192.7	174.5	163.6	152.7	138.2	127.3	109.1	94.5	76.4
80°	98.2	90.9	94.5	94.5	94.5	94.5	90.9	90.9	80.0	69.1	54.5
82.5°	21.8	18.2	21.8	21.8	21.8	21.8	18.2	18.2	18.2	14.5	14.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5
5°	29.1	29.1	29.1	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5
7.5°	29.1	29.1	29.1	25.5	25.5	25.5	25.5	21.8	21.8	21.8	21.8
10°	29.1	29.1	29.1	25.5	25.5	25.5	25.5	21.8	21.8	21.8	21.8
12.5°	32.7	32.7	29.1	29.1	25.5	25.5	25.5	21.8	21.8	21.8	21.8
15°	32.7	32.7	29.1	29.1	25.5	25.5	25.5	21.8	21.8	21.8	21.8
17.5°	36.4	32.7	32.7	29.1	25.5	25.5	25.5	21.8	21.8	21.8	21.8
20°	36.4	32.7	32.7	29.1	25.5	25.5	25.5	21.8	21.8	21.8	21.8
22.5°	36.4	32.7	32.7	29.1	25.5	25.5	21.8	21.8	18.2	18.2	14.5
25°	36.4	32.7	32.7	29.1	25.5	25.5	21.8	21.8	18.2	14.5	14.5
27.5°	36.4	32.7	32.7	29.1	25.5	21.8	21.8	18.2	14.5	10.9	10.9
30°	36.4	32.7	32.7	29.1	25.5	21.8	18.2	14.5	10.9	10.9	7.3
32.5°	36.4	32.7	29.1	25.5	21.8	18.2	18.2	14.5	10.9	7.3	7.3
35°	36.4	32.7	29.1	25.5	21.8	18.2	18.2	14.5	10.9	7.3	7.3
37.5°	36.4	32.7	29.1	25.5	21.8	18.2	14.5	10.9	7.3	7.3	3.6
40°	36.4	32.7	29.1	25.5	21.8	18.2	14.5	10.9	7.3	7.3	3.6
42.5°	36.4	32.7	29.1	25.5	21.8	18.2	14.5	10.9	7.3	7.3	3.6
45°	40.0	36.4	32.7	25.5	21.8	18.2	18.2	14.5	10.9	7.3	7.3
47.5°	40.0	36.4	32.7	25.5	21.8	18.2	18.2	14.5	10.9	7.3	7.3
50°	43.6	40.0	36.4	29.1	25.5	21.8	18.2	10.9	7.3	7.3	3.6
52.5°	47.3	43.6	40.0	36.4	32.7	25.5	18.2	10.9	3.6	3.6	3.6
55°	50.9	47.3	47.3	43.6	40.0	29.1	21.8	10.9	0.0	0.0	0.0
57.5°	54.5	50.9	50.9	47.3	43.6	32.7	21.8	10.9	0.0	0.0	0.0
60°	61.8	58.2	54.5	47.3	43.6	32.7	21.8	10.9	0.0	0.0	0.0
62.5°	72.7	65.4	54.5	47.3	36.4	29.1	18.2	10.9	0.0	0.0	0.0
65°	80.0	69.1	58.2	43.6	32.7	25.5	18.2	7.3	0.0	0.0	0.0
67.5°	83.6	69.1	58.2	43.6	29.1	21.8	14.5	7.3	0.0	0.0	0.0
70°	80.0	65.4	54.5	40.0	25.5	18.2	14.5	7.3	0.0	0.0	0.0
72.5°	72.7	61.8	47.3	36.4	21.8	18.2	10.9	7.3	0.0	0.0	0.0
75°	65.4	54.5	40.0	29.1	14.5	10.9	7.3	3.6	0.0	0.0	0.0
77.5°	58.2	47.3	32.7	21.8	7.3	7.3	3.6	3.6	0.0	0.0	0.0
80°	43.6	32.7	21.8	10.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	10.9	7.3	7.3	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	21.8	21.8	21.8	21.8	21.8	21.8	21.8	21.8	21.8	21.8	21.8
5°	21.8	21.8	21.8	21.8	18.2	18.2	18.2	18.2	18.2	18.2	18.2
7.5°	21.8	21.8	21.8	21.8	18.2	18.2	18.2	18.2	14.5	14.5	14.5
10°	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2	14.5	14.5	14.5
12.5°	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2	14.5	14.5	14.5
15°	18.2	18.2	18.2	18.2	18.2	18.2	18.2	14.5	14.5	10.9	10.9
17.5°	18.2	18.2	18.2	18.2	14.5	14.5	14.5	10.9	10.9	7.3	7.3
20°	18.2	18.2	18.2	14.5	14.5	10.9	10.9	7.3	7.3	3.6	3.6
22.5°	14.5	10.9	10.9	7.3	7.3	3.6	3.6	3.6	0.0	0.0	0.0
25°	10.9	7.3	7.3	3.6	3.6	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	7.3	3.6	3.6	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	7.3	3.6	3.6	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	21.8	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2
5°	18.2	18.2	18.2	18.2	14.5	14.5	14.5	14.5	14.5	14.5	14.5
7.5°	14.5	14.5	14.5	14.5	14.5	14.5	10.9	10.9	10.9	10.9	10.9
10°	14.5	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	7.3	7.3
12.5°	14.5	10.9	10.9	10.9	7.3	7.3	7.3	7.3	7.3	3.6	3.6
15°	10.9	7.3	7.3	7.3	3.6	3.6	3.6	3.6	3.6	0.0	0.0
17.5°	7.3	3.6	3.6	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2	18.2	21.8	21.8
5°	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
7.5°	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9
10°	7.3	7.3	7.3	7.3	7.3	7.3	3.6	3.6	3.6	3.6	3.6
12.5°	3.6	3.6	3.6	3.6	3.6	3.6	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	21.8	21.8	21.8	21.8	21.8	25.5	25.5	29.1	29.1	32.7	32.7
5°	14.5	14.5	18.2	18.2	18.2	18.2	21.8	21.8	21.8	25.5	25.5
7.5°	10.9	10.9	10.9	10.9	10.9	14.5	14.5	18.2	18.2	21.8	21.8
10°	3.6	3.6	7.3	7.3	7.3	7.3	10.9	10.9	10.9	14.5	18.2
12.5°	0.0	0.0	3.6	3.6	3.6	3.6	7.3	7.3	7.3	10.9	14.5
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	7.3	10.9
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	7.3
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	36.4	36.4	40.0	40.0	43.6	43.6	47.3	47.3	47.3	47.3	47.3
5°	29.1	29.1	32.7	36.4	36.4	40.0	43.6	43.6	43.6	43.6	43.6
7.5°	25.5	25.5	29.1	32.7	32.7	36.4	40.0	40.0	43.6	43.6	43.6
10°	18.2	21.8	25.5	29.1	29.1	32.7	36.4	36.4	40.0	40.0	40.0
12.5°	14.5	18.2	21.8	25.5	25.5	29.1	32.7	32.7	36.4	36.4	40.0
15°	10.9	14.5	18.2	21.8	21.8	25.5	29.1	29.1	32.7	36.4	40.0
17.5°	7.3	10.9	14.5	18.2	18.2	21.8	25.5	29.1	32.7	32.7	36.4
20°	7.3	7.3	10.9	14.5	14.5	18.2	21.8	25.5	29.1	29.1	32.7
22.5°	3.6	3.6	7.3	10.9	10.9	14.5	18.2	21.8	25.5	25.5	29.1
25°	0.0	0.0	3.6	7.3	7.3	10.9	14.5	14.5	18.2	18.2	21.8
27.5°	0.0	0.0	3.6	3.6	7.3	7.3	10.9	10.9	14.5	14.5	18.2
30°	0.0	0.0	3.6	3.6	7.3	7.3	10.9	10.9	14.5	14.5	14.5
32.5°	0.0	0.0	0.0	3.6	3.6	3.6	7.3	7.3	10.9	10.9	14.5
35°	0.0	0.0	0.0	3.6	3.6	3.6	7.3	7.3	10.9	10.9	10.9
37.5°	0.0	0.0	0.0	3.6	3.6	3.6	7.3	7.3	7.3	7.3	10.9
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	3.6	3.6
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	3.6	3.6
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	3.6	3.6
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	7.3	7.3	7.3
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	3.6	7.3
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	3.6	3.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.6	3.6	3.6	3.6	3.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	47.3	47.3
5°	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	43.6	43.6
7.5°	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	43.6	43.6
10°	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6
12.5°	40.0	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6
15°	40.0	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6
17.5°	36.4	40.0	40.0	40.0	43.6	43.6	43.6	43.6	43.6	43.6	43.6
20°	32.7	36.4	36.4	36.4	40.0	40.0	40.0	40.0	43.6	43.6	43.6
22.5°	29.1	32.7	32.7	32.7	36.4	36.4	36.4	36.4	40.0	40.0	40.0
25°	25.5	25.5	29.1	29.1	32.7	32.7	32.7	32.7	32.7	32.7	32.7
27.5°	18.2	21.8	21.8	21.8	25.5	25.5	25.5	25.5	29.1	29.1	29.1
30°	18.2	18.2	18.2	18.2	21.8	21.8	21.8	21.8	25.5	25.5	25.5
32.5°	14.5	18.2	18.2	18.2	21.8	21.8	21.8	21.8	25.5	25.5	25.5
35°	14.5	14.5	14.5	14.5	18.2	18.2	18.2	18.2	21.8	21.8	21.8
37.5°	10.9	14.5	14.5	14.5	18.2	18.2	18.2	18.2	21.8	21.8	21.8
40°	10.9	10.9	10.9	10.9	14.5	14.5	14.5	14.5	18.2	18.2	18.2
42.5°	10.9	10.9	10.9	10.9	14.5	14.5	14.5	14.5	18.2	18.2	18.2
45°	10.9	10.9	10.9	10.9	14.5	14.5	14.5	14.5	18.2	18.2	18.2
47.5°	10.9	10.9	10.9	10.9	14.5	14.5	14.5	14.5	18.2	18.2	18.2
50°	10.9	10.9	10.9	10.9	14.5	14.5	14.5	14.5	18.2	18.2	18.2
52.5°	7.3	7.3	7.3	7.3	10.9	10.9	10.9	10.9	14.5	14.5	14.5
55°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	10.9	10.9	10.9
57.5°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	10.9	10.9	10.9
60°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
62.5°	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
65°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	3.6	3.6
67.5°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
70°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
72.5°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
75°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
77.5°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
80°	10.9	10.9	10.9	10.9	10.9	7.3	7.3	7.3	7.3	7.3	7.3
82.5°	7.3	10.9	10.9	10.9	10.9	7.3	7.3	7.3	7.3	7.3	7.3
85°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
87.5°	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3	7.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	47.3	47.3	43.6	43.6	43.6	43.6	43.6	43.6	43.6	47.3	47.3
5°	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	47.3	47.3
7.5°	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	47.3	47.3
10°	43.6	43.6	43.6	43.6	40.0	40.0	43.6	43.6	43.6	47.3	47.3
12.5°	43.6	43.6	43.6	43.6	40.0	40.0	43.6	43.6	47.3	47.3	50.9
15°	43.6	43.6	40.0	40.0	40.0	40.0	43.6	43.6	47.3	47.3	50.9
17.5°	43.6	43.6	40.0	40.0	40.0	40.0	43.6	43.6	47.3	47.3	50.9
20°	43.6	43.6	40.0	40.0	40.0	40.0	40.0	40.0	43.6	47.3	47.3
22.5°	40.0	40.0	40.0	40.0	36.4	36.4	40.0	40.0	43.6	47.3	47.3
25°	32.7	36.4	36.4	36.4	36.4	36.4	40.0	40.0	43.6	47.3	47.3
27.5°	29.1	32.7	32.7	32.7	32.7	36.4	36.4	40.0	43.6	47.3	47.3
30°	25.5	29.1	29.1	29.1	32.7	36.4	36.4	40.0	43.6	47.3	47.3
32.5°	25.5	29.1	29.1	29.1	32.7	32.7	36.4	36.4	40.0	43.6	47.3
35°	25.5	25.5	29.1	29.1	29.1	32.7	32.7	36.4	40.0	43.6	47.3
37.5°	25.5	25.5	29.1	29.1	29.1	32.7	32.7	36.4	40.0	43.6	47.3
40°	21.8	25.5	25.5	29.1	29.1	32.7	32.7	36.4	40.0	47.3	50.9
42.5°	21.8	21.8	25.5	25.5	29.1	32.7	32.7	36.4	40.0	47.3	50.9
45°	21.8	25.5	25.5	29.1	32.7	36.4	36.4	40.0	43.6	47.3	50.9
47.5°	21.8	25.5	25.5	29.1	36.4	36.4	40.0	40.0	43.6	47.3	50.9
50°	21.8	25.5	25.5	29.1	40.0	40.0	40.0	40.0	43.6	47.3	50.9
52.5°	18.2	21.8	21.8	25.5	32.7	36.4	40.0	43.6	47.3	50.9	54.5
55°	14.5	18.2	18.2	21.8	29.1	32.7	40.0	47.3	50.9	54.5	58.2
57.5°	14.5	14.5	18.2	18.2	25.5	32.7	43.6	50.9	54.5	58.2	61.8
60°	10.9	10.9	14.5	14.5	21.8	29.1	40.0	50.9	54.5	61.8	65.4
62.5°	7.3	10.9	10.9	14.5	18.2	29.1	40.0	50.9	58.2	65.4	69.1
65°	7.3	7.3	10.9	10.9	18.2	25.5	36.4	43.6	54.5	65.4	76.4
67.5°	10.9	10.9	14.5	14.5	18.2	25.5	36.4	43.6	54.5	69.1	80.0
70°	10.9	10.9	14.5	14.5	21.8	29.1	36.4	43.6	54.5	69.1	80.0
72.5°	10.9	10.9	14.5	14.5	21.8	25.5	32.7	40.0	50.9	61.8	72.7
75°	7.3	10.9	10.9	10.9	18.2	21.8	29.1	36.4	47.3	58.2	69.1
77.5°	7.3	7.3	7.3	7.3	14.5	18.2	25.5	29.1	40.0	50.9	61.8
80°	7.3	7.3	7.3	7.3	10.9	14.5	21.8	25.5	36.4	47.3	58.2
82.5°	7.3	7.3	3.6	3.6	7.3	10.9	14.5	18.2	29.1	36.4	47.3
85°	7.3	7.3	3.6	3.6	3.6	7.3	7.3	10.9	14.5	18.2	21.8
87.5°	7.3	7.3	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	47.3	47.3	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9
5°	47.3	50.9	50.9	54.5	54.5	54.5	58.2	58.2	58.2	58.2	58.2
7.5°	47.3	50.9	50.9	54.5	54.5	54.5	58.2	58.2	58.2	61.8	61.8
10°	47.3	50.9	50.9	54.5	54.5	58.2	61.8	61.8	65.4	65.4	65.4
12.5°	50.9	54.5	54.5	58.2	58.2	61.8	65.4	65.4	69.1	72.7	72.7
15°	50.9	54.5	58.2	58.2	61.8	65.4	69.1	69.1	72.7	76.4	80.0
17.5°	50.9	54.5	58.2	58.2	61.8	65.4	72.7	76.4	80.0	87.3	90.9
20°	50.9	54.5	58.2	58.2	61.8	69.1	72.7	80.0	83.6	90.9	98.2
22.5°	50.9	54.5	58.2	61.8	65.4	72.7	80.0	83.6	90.9	101.8	109.1
25°	50.9	54.5	58.2	61.8	65.4	72.7	80.0	87.3	94.5	109.1	123.6
27.5°	50.9	54.5	61.8	65.4	69.1	76.4	87.3	94.5	101.8	127.3	152.7
30°	50.9	54.5	61.8	65.4	69.1	80.0	90.9	98.2	109.1	152.7	192.7
32.5°	50.9	58.2	61.8	69.1	72.7	83.6	98.2	109.1	120.0	181.8	240.0
35°	50.9	58.2	61.8	69.1	72.7	87.3	101.8	116.3	130.9	221.8	312.7
37.5°	50.9	58.2	61.8	69.1	72.7	94.5	116.3	138.2	160.0	254.5	349.0
40°	54.5	61.8	65.4	72.7	76.4	98.2	120.0	141.8	163.6	258.1	352.7
42.5°	54.5	61.8	65.4	72.7	76.4	94.5	116.3	134.5	152.7	258.1	363.6
45°	54.5	61.8	69.1	72.7	80.0	98.2	116.3	130.9	149.1	283.6	414.5
47.5°	54.5	61.8	69.1	72.7	80.0	98.2	116.3	134.5	152.7	374.5	592.6
50°	54.5	61.8	69.1	72.7	80.0	101.8	123.6	145.4	167.2	559.9	952.6
52.5°	58.2	61.8	69.1	72.7	76.4	101.8	127.3	152.7	178.2	727.2	1272.5
55°	61.8	65.4	69.1	72.7	76.4	109.1	141.8	174.5	207.2	781.7	1352.5
57.5°	65.4	69.1	72.7	72.7	76.4	116.3	160.0	200.0	240.0	778.1	1312.5
60°	69.1	72.7	76.4	80.0	83.6	123.6	167.2	207.2	247.2	705.3	1163.5
62.5°	76.4	83.6	90.9	94.5	101.8	141.8	178.2	218.1	254.5	578.1	898.0
65°	87.3	94.5	98.2	105.4	109.1	145.4	185.4	221.8	258.1	479.9	698.1
67.5°	90.9	98.2	101.8	109.1	112.7	149.1	185.4	221.8	258.1	407.2	552.6
70°	90.9	98.2	105.4	109.1	116.3	152.7	185.4	221.8	254.5	352.7	450.8
72.5°	83.6	94.5	101.8	112.7	120.0	152.7	181.8	214.5	243.6	312.7	381.8
75°	80.0	94.5	105.4	120.0	130.9	152.7	178.2	200.0	221.8	272.7	323.6
77.5°	72.7	90.9	109.1	127.3	145.4	160.0	170.9	185.4	196.3	229.1	261.8
80°	69.1	87.3	105.4	123.6	141.8	149.1	152.7	160.0	163.6	167.2	170.9
82.5°	54.5	69.1	83.6	94.5	109.1	101.8	98.2	90.9	83.6	80.0	76.4
85°	25.5	29.1	29.1	32.7	32.7	32.7	29.1	29.1	25.5	21.8	18.2
87.5°	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	50.9	50.9	50.9	50.9	47.3	47.3	47.3	47.3	43.6	43.6	43.6
5°	58.2	58.2	58.2	58.2	54.5	54.5	54.5	54.5	50.9	50.9	50.9
7.5°	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8
10°	69.1	69.1	69.1	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7
12.5°	76.4	76.4	80.0	80.0	83.6	83.6	87.3	87.3	90.9	90.9	90.9
15°	83.6	87.3	90.9	94.5	94.5	98.2	101.8	105.4	109.1	112.7	116.3
17.5°	98.2	101.8	109.1	116.3	123.6	130.9	141.8	156.3	167.2	178.2	192.7
20°	109.1	120.0	141.8	167.2	189.1	210.9	265.4	320.0	374.5	429.0	483.6
22.5°	130.9	152.7	225.4	301.8	374.5	447.2	618.1	789.0	956.2	1127.1	1279.8
25°	174.5	221.8	389.0	556.3	719.9	887.1	1192.6	1501.6	1807.0	2112.4	2396.0
27.5°	240.0	327.2	599.9	876.2	1148.9	1421.6	1865.2	2312.4	2756.0	3203.2	3599.5
30°	334.5	476.3	883.5	1294.4	1701.6	2108.8	2668.7	3232.2	3792.2	4352.1	4715.7
32.5°	454.5	665.4	1181.6	1697.9	2214.2	2730.5	3348.6	3966.7	4581.1	5199.2	5584.6
35°	581.7	850.8	1472.5	2097.9	2719.6	3345.0	3995.8	4646.6	5297.4	5948.2	6420.9
37.5°	654.4	959.9	1697.9	2436.0	3170.4	3908.5	4621.1	5337.4	6050.0	6762.6	7337.1
40°	723.5	1090.7	1941.5	2792.3	3643.1	4493.9	5326.5	6159.1	6991.7	7824.3	8562.4
42.5°	825.3	1287.1	2279.7	3272.2	4261.2	5253.8	6348.1	7446.2	8540.6	9634.9	10769.3
45°	1036.2	1657.9	2945.0	4232.1	5515.5	6802.6	8355.1	9911.3	11463.8	13019.9	14474.2
47.5°	1545.2	2494.2	4250.3	6006.4	7762.5	9518.6	11307.4	13096.2	14885.1	16673.9	18404.5
50°	2392.4	3828.5	6024.6	8220.6	10413.0	12609.0	14394.2	16179.4	17961.0	19746.2	21465.9
52.5°	3188.6	5104.7	7464.3	9827.6	12187.3	14550.6	16132.2	17713.7	19295.3	20876.9	22542.1
55°	3461.3	5566.4	7955.2	10347.6	12736.3	15128.7	16652.1	18179.1	19702.5	21225.9	22953.0
57.5°	3221.3	5130.1	7537.1	9944.0	12347.3	14754.2	16455.7	18160.9	19862.5	21567.7	23418.3
60°	2697.8	4228.5	6755.4	9285.9	11812.8	14339.7	16259.4	18179.1	20098.8	22018.6	23865.6
62.5°	2137.9	3374.0	6050.0	8726.0	11401.9	14077.9	16030.3	17986.4	19938.9	21891.3	23309.3
65°	1639.8	2581.4	5213.8	7849.7	10482.1	13118.1	14717.8	16321.2	17921.0	19524.4	20506.0
67.5°	1218.0	1883.4	4184.8	6489.9	8791.4	11092.9	12270.9	13452.5	14630.6	15812.2	16575.7
70°	898.0	1341.6	2908.7	4475.7	6039.1	7606.1	8686.0	9765.8	10842.0	11921.9	12714.5
72.5°	621.7	858.1	1796.1	2737.8	3675.8	4613.9	5708.2	6802.6	7893.4	8987.8	9889.4
75°	425.4	527.2	967.1	1407.1	1847.0	2286.9	3115.9	3944.9	4773.8	5602.8	6079.1
77.5°	316.3	370.9	501.7	636.3	767.2	898.0	1058.0	1218.0	1378.0	1538.0	1745.2
80°	174.5	174.5	192.7	207.2	225.4	240.0	283.6	330.9	374.5	421.8	479.9
82.5°	80.0	83.6	90.9	98.2	101.8	109.1	116.3	123.6	130.9	138.2	138.2
85°	21.8	25.5	25.5	21.8	21.8	18.2	18.2	21.8	21.8	21.8	21.8
87.5°	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	43.6	40.0	40.0	40.0	36.4	36.4	36.4	36.4	36.4	36.4	36.4
5°	50.9	50.9	50.9	50.9	47.3	47.3	47.3	47.3	47.3	43.6	43.6
7.5°	61.8	58.2	58.2	58.2	58.2	58.2	58.2	58.2	58.2	54.5	54.5
10°	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	69.1	69.1
12.5°	90.9	90.9	90.9	90.9	94.5	94.5	90.9	90.9	90.9	87.3	87.3
15°	120.0	123.6	127.3	127.3	130.9	130.9	130.9	127.3	127.3	123.6	120.0
17.5°	203.6	214.5	229.1	243.6	258.1	269.1	269.1	261.8	254.5	247.2	240.0
20°	541.7	596.3	654.4	712.6	774.4	818.1	789.0	767.2	745.3	719.9	698.1
22.5°	1436.2	1588.9	1745.2	1854.3	1963.3	2039.7	1977.9	1857.9	1737.9	1621.6	1501.6
25°	2679.6	2959.6	3243.2	3359.5	3479.5	3566.7	3526.7	3345.0	3163.2	2985.0	2803.2
27.5°	3995.8	4388.4	4784.7	4886.5	4988.4	5064.7	5050.2	4813.8	4577.5	4341.2	4104.8
30°	5079.2	5442.8	5806.4	5908.2	6010.0	6079.1	6002.7	5766.4	5530.1	5293.8	5057.4
32.5°	5973.7	6359.1	6748.1	6882.6	7017.1	7108.0	7017.1	6733.5	6450.0	6170.0	5886.4
35°	6893.5	7362.5	7835.2	8006.1	8177.0	8286.0	8133.3	7784.3	7435.3	7089.9	6740.8
37.5°	7911.6	8482.4	9056.8	9289.5	9525.9	9689.5	9573.1	9136.8	8696.9	8260.6	7820.7
40°	9304.1	10042.1	10783.9	11202.0	11616.5	11911.0	11703.7	11198.3	10689.3	10183.9	9674.9
42.5°	11907.3	13041.7	14176.1	14776.0	15372.3	15804.9	15572.2	14950.5	14328.8	13707.1	13085.3
45°	15928.5	17379.2	18833.6	19709.8	20589.7	21236.8	20967.8	20186.1	19400.8	18619.1	17837.4
47.5°	20135.2	21865.8	23596.5	24294.6	24996.3	25541.7	25476.2	24501.8	23527.4	22556.7	21582.3
50°	23189.3	24909.0	26628.8	27228.7	27832.2	28279.4	28112.2	26872.4	25628.9	24389.1	23145.7
52.5°	24207.3	25868.9	27534.1	28250.4	28966.6	29501.1	29297.5	27901.3	26505.2	25112.6	23716.5
55°	24680.0	26407.0	28134.0	29006.6	29882.8	30522.7	30228.2	28697.6	27163.2	25632.6	24098.2
57.5°	25269.0	27119.6	28970.2	29926.5	30882.7	31573.5	31180.8	29595.6	28010.4	26428.8	24843.6
60°	25712.5	27555.9	29402.9	30170.1	30940.9	31479.0	31100.8	29559.3	28014.0	26472.4	24930.8
62.5°	24730.9	26148.8	27566.8	28137.6	28708.5	29123.0	28908.4	27446.8	25985.2	24523.6	23062.0
65°	21491.4	22473.0	23458.3	23843.7	24225.5	24520.0	24454.6	23222.0	21989.5	20760.6	19528.0
67.5°	17342.9	18106.4	18873.6	19418.9	19967.9	20393.3	20346.1	19222.6	18099.1	16975.7	15852.2
70°	13510.7	14303.3	15095.9	15783.1	16473.9	17008.4	16939.3	15895.8	14848.7	13805.2	12758.1
72.5°	10794.8	11696.4	12598.1	12990.8	13383.5	13659.8	13456.2	12667.2	11874.6	11085.6	10293.0
75°	6555.4	7028.0	7504.3	7500.7	7500.7	7457.1	7253.5	6802.6	6351.8	5900.9	5450.1
77.5°	1952.4	2159.7	2366.9	2566.9	2770.5	2923.2	2883.2	2646.9	2406.9	2170.6	1930.6
80°	538.1	592.6	650.8	676.3	701.7	734.4	818.1	759.9	701.7	647.2	589.0
82.5°	138.2	138.2	138.2	134.5	130.9	123.6	112.7	105.4	98.2	90.9	83.6
85°	21.8	18.2	18.2	18.2	14.5	14.5	14.5	14.5	10.9	10.9	7.3
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
2.5°	36.4	36.4	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	29.1
5°	43.6	43.6	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	36.4
7.5°	54.5	54.5	50.9	50.9	50.9	50.9	47.3	47.3	47.3	47.3	43.6
10°	69.1	65.4	65.4	61.8	61.8	61.8	58.2	58.2	58.2	54.5	54.5
12.5°	87.3	83.6	83.6	80.0	76.4	76.4	72.7	69.1	65.4	65.4	61.8
15°	116.3	112.7	109.1	105.4	101.8	94.5	90.9	83.6	80.0	76.4	72.7
17.5°	221.8	203.6	185.4	167.2	152.7	138.2	123.6	109.1	101.8	94.5	87.3
20°	618.1	534.5	454.5	374.5	323.6	272.7	221.8	170.9	149.1	130.9	109.1
22.5°	1338.0	1170.7	1007.1	839.9	705.3	574.5	439.9	305.4	254.5	207.2	156.3
25°	2486.9	2167.0	1850.6	1530.7	1276.2	1021.7	767.2	512.7	418.1	323.6	229.1
27.5°	3690.4	3275.9	2861.4	2446.9	2043.3	1636.1	1228.9	825.3	661.7	501.7	338.1
30°	4617.5	4177.6	3741.3	3301.3	2792.3	2283.3	1770.6	1261.6	1003.5	745.3	483.6
32.5°	5413.7	4937.4	4464.8	3988.5	3399.5	2810.5	2221.5	1632.5	1308.9	985.3	658.1
35°	6202.7	5661.0	5122.9	4581.1	3948.5	3315.9	2683.2	2050.6	1639.8	1228.9	814.4
37.5°	7162.6	6500.9	5842.8	5184.7	4533.9	3886.7	3235.9	2585.1	2061.5	1541.6	1018.0
40°	8835.1	7991.5	7151.7	6308.2	5548.3	4792.0	4032.1	3272.2	2614.2	1956.1	1294.4
42.5°	12027.3	10969.3	9914.9	8856.9	7806.1	6755.4	5701.0	4650.2	3712.2	2777.8	1839.7
45°	16481.2	15125.0	13772.5	12416.3	11122.0	9831.3	8536.9	7242.6	5817.3	4392.1	2963.2
47.5°	20098.8	18611.8	17128.4	15641.3	14205.2	12772.7	11336.5	9900.3	8075.2	6253.6	4428.4
50°	21731.3	20313.3	18899.0	17481.0	16041.3	14597.8	13154.4	11714.6	9620.4	7529.8	5435.6
52.5°	22280.3	20840.5	19404.4	17964.6	16535.7	15106.8	13678.0	12249.1	10071.2	7897.0	5719.2
55°	22582.1	21062.3	19546.2	18026.4	16488.5	14946.9	13405.3	11867.3	9700.4	7537.1	5370.1
57.5°	23192.9	21538.6	19888.0	18233.7	16481.2	14728.7	12972.6	11220.2	9082.3	6944.4	4806.6
60°	23305.6	21676.8	20051.6	18426.4	16488.5	14550.6	12609.0	10671.1	8547.8	6428.1	4304.8
62.5°	21702.2	20342.4	18986.3	17626.5	15684.9	13743.4	11798.2	9856.7	7824.3	5791.9	3755.8
65°	18353.6	17179.3	16008.5	14834.2	13248.9	11667.4	10082.1	8496.9	6682.6	4872.0	3057.7
67.5°	14703.3	13554.4	12409.1	11260.1	10067.6	8878.7	7686.1	6493.6	5093.8	3694.0	2294.2
70°	11656.5	10551.2	9449.5	8344.2	7289.8	6231.8	5173.8	4119.4	3250.4	2385.1	1516.1
72.5°	9238.6	8180.6	7126.2	6068.2	5112.0	4155.7	3199.5	2243.3	1810.6	1381.6	949.0
75°	4901.1	4352.1	3806.7	3257.7	2719.6	2177.9	1636.1	1098.0	927.1	756.3	581.7
77.5°	1690.7	1450.7	1214.4	974.4	810.8	647.2	483.6	320.0	301.8	287.2	269.1
80°	512.7	436.3	359.9	283.6	250.9	218.1	185.4	152.7	141.8	130.9	116.3
82.5°	80.0	72.7	69.1	61.8	58.2	58.2	54.5	50.9	43.6	40.0	32.7
85°	7.3	3.6	3.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	32.7	32.7
2.5°	29.1	29.1
5°	36.4	36.4
7.5°	43.6	43.6
10°	50.9	50.9
12.5°	58.2	58.2
15°	69.1	65.4
17.5°	80.0	76.4
20°	87.3	80.0
22.5°	105.4	90.9
25°	134.5	112.7
27.5°	174.5	138.2
30°	225.4	174.5
32.5°	334.5	243.6
35°	403.6	294.5
37.5°	494.5	341.8
40°	636.3	414.5
42.5°	901.7	563.6
45°	1538.0	934.4
47.5°	2606.9	1592.5
50°	3341.3	2043.3
52.5°	3544.9	2167.0
55°	3206.8	1988.8
57.5°	2668.7	1690.7
60°	2185.1	1392.5
62.5°	1723.4	1101.7
65°	1243.5	832.6
67.5°	894.4	639.9
70°	650.8	501.7
72.5°	516.3	418.1
75°	410.8	349.0
77.5°	254.5	232.7
80°	105.4	98.2
82.5°	25.5	21.8
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1067664

CATALOG NUMBER: NAV-SA3D-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-2

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-722-U-5WQ

Data in this report applies to families of products including GSS-SB1A-722-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-722-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2200K CCT 26 LEDS

Spectral Parameters

CCT (K): 2160
 CIE u' : 0.2927
 CIE v' : 0.5388
 Duv: 0.0015
 CIE x: 0.5130
 CIE y: 0.4197
 CIE z: 0.0674
 Peak Wavelength (nm): 609
 Dominant Wavelength (nm): 587
 Purity: 79.96089
 R_f: 70.6
 R_g: 97.6

CRI (Ra): 71.9
 R1: 68.7
 R2: 82.6
 R3: 95.5
 R4: 66.4
 R5: 65.4
 R6: 75.9
 R7: 77.2
 R8: 43.5
 R9: -17.8
 R10: 60.5
 R11: 60.2
 R12: 48.2
 R13: 70.7
 R14: 96.8
 R15: 61.8



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-2


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-2

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2200K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-2

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 0.8

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.21


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2





TM-30-18

Summary

$R_f = 70.6$
 $R_g = 97.6$
 $CIE R_a = 71.9$
 $R_g = -17.8$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 87	CES26 = 60	CES51 = 74	CES76 = 58
CES02 = 65	CES27 = 77	CES52 = 77	CES77 = 82
CES03 = 32	CES28 = 85	CES53 = 65	CES78 = 65
CES04 = 72	CES29 = 50	CES54 = 77	CES79 = 86
CES05 = 52	CES30 = 49	CES55 = 74	CES80 = 85
CES06 = 53	CES31 = 55	CES56 = 64	CES81 = 61
CES07 = 44	CES32 = 55	CES57 = 60	CES82 = 93
CES08 = 43	CES33 = 55	CES58 = 64	CES83 = 83
CES09 = 29	CES34 = 75	CES59 = 84	CES84 = 93
CES10 = 79	CES35 = 88	CES60 = 89	CES85 = 81
CES11 = 62	CES36 = 78	CES61 = 84	CES86 = 55
CES12 = 68	CES37 = 82	CES62 = 68	CES87 = 79
CES13 = 45	CES38 = 54	CES63 = 68	CES88 = 72
CES14 = 75	CES39 = 90	CES64 = 69	CES89 = 62
CES15 = 72	CES40 = 86	CES65 = 66	CES90 = 67
CES16 = 49	CES41 = 75	CES66 = 64	CES91 = 89
CES17 = 51	CES42 = 83	CES67 = 63	CES92 = 67
CES18 = 57	CES43 = 68	CES68 = 71	CES93 = 78
CES19 = 74	CES44 = 98	CES69 = 81	CES94 = 52
CES20 = 68	CES45 = 76	CES70 = 65	CES95 = 76
CES21 = 89	CES46 = 68	CES71 = 64	CES96 = 78
CES22 = 81	CES47 = 60	CES72 = 88	CES97 = 76
CES23 = 92	CES48 = 47	CES73 = 59	CES98 = 71
CES24 = 92	CES49 = 65	CES74 = 85	CES99 = 65
CES25 = 74	CES50 = 74	CES75 = 66	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)