

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMARK

Report Number: P1067665

Luminaire Tested: **NAV-SA4A-722-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1067665
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMARK
Catalog Number: NAV-SA4A-722-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 4xLight Square PACKAGE
70CRI 2200K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 2200K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8984.6 lumens
Efficiency: N/A
Efficacy: 83.7 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 107.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	53.4	0.0	53.4
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	8931.1	0.0	8931.1
	% Fixture	99.4	0.0	99.4
Total	Lumens	8984.5	0.0	8984.5
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.7	0.0
10°-20°	13.2	0.1
20°-30°	167.7	1.9
30°-40°	565.2	6.3
40°-50°	1706.8	19.0
50°-60°	3011.3	33.5
60°-70°	2653.0	29.5
70°-80°	844.5	9.4
80°-90°	20.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	8984.5	100.0
0°-180°	8984.6	100.0



REPORT NUMBER: P1067665


CATALOG NUMBER: NAV-SA4A-722-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	175.5	2.0			
FM	(30°-60°)	5262.5	58.6			
FH	(60°-80°)	3476.5	38.7			G2/5000
FVH	(80°-90°)	16.5	0.2			G1/100
BL	(0°-30°)	8.0	0.1	B0/110		
BM	(30°-60°)	20.7	0.2	B0/220		
BH	(60°-80°)	20.9	0.2	B0/110		G0/110
BVH	(80°-90°)	3.8	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	19.7
5°	28.2	28.2	28.2	25.4	25.4	25.4	22.5	22.5	22.5	22.5	22.5
7.5°	33.8	31.0	31.0	28.2	28.2	28.2	25.4	25.4	25.4	25.4	22.5
10°	39.4	36.6	36.6	33.8	33.8	31.0	31.0	28.2	28.2	25.4	25.4
12.5°	45.1	42.3	39.4	36.6	36.6	33.8	33.8	31.0	31.0	28.2	28.2
15°	50.7	47.9	45.1	42.3	39.4	39.4	36.6	33.8	31.0	31.0	28.2
17.5°	59.2	53.5	50.7	45.1	42.3	39.4	36.6	33.8	33.8	31.0	31.0
20°	62.0	56.4	53.5	47.9	45.1	42.3	39.4	36.6	33.8	33.8	31.0
22.5°	73.3	62.0	59.2	53.5	50.7	47.9	42.3	39.4	36.6	33.8	31.0
25°	90.2	73.3	64.8	56.4	53.5	47.9	45.1	39.4	36.6	33.8	31.0
27.5°	109.9	81.7	73.3	62.0	56.4	50.7	45.1	39.4	36.6	33.8	31.0
30°	135.2	95.8	81.7	67.6	62.0	56.4	47.9	42.3	39.4	36.6	31.0
32.5°	188.8	118.3	95.8	73.3	64.8	59.2	50.7	42.3	39.4	36.6	31.0
35°	228.2	143.7	115.5	84.5	73.3	64.8	53.5	42.3	39.4	36.6	31.0
37.5°	264.8	146.5	118.3	90.2	78.9	67.6	53.5	42.3	39.4	36.6	31.0
40°	324.0	152.1	118.3	84.5	76.1	64.8	56.4	45.1	42.3	36.6	33.8
42.5°	436.7	174.7	126.8	78.9	70.4	64.8	56.4	47.9	42.3	39.4	33.8
45°	726.9	259.2	171.9	81.7	73.3	64.8	56.4	47.9	45.1	39.4	36.6
47.5°	1236.9	450.8	267.7	84.5	76.1	64.8	56.4	45.1	42.3	39.4	33.8
50°	1583.5	577.6	338.1	98.6	84.5	73.3	59.2	45.1	42.3	39.4	36.6
52.5°	1682.1	614.2	366.3	115.5	98.6	81.7	62.0	45.1	42.3	42.3	39.4
55°	1541.2	597.3	366.3	135.2	112.7	93.0	70.4	47.9	45.1	45.1	42.3
57.5°	1310.2	552.2	349.4	146.5	124.0	98.6	76.1	50.7	47.9	47.9	45.1
60°	1079.1	464.9	315.6	163.4	138.1	112.7	87.3	62.0	59.2	56.4	50.7
62.5°	856.5	374.7	276.1	174.7	149.3	121.2	95.8	67.6	64.8	62.0	59.2
65°	645.2	326.8	256.4	183.1	155.0	126.8	98.6	70.4	67.6	67.6	64.8
67.5°	495.9	298.7	245.1	188.8	160.6	132.4	104.2	76.1	73.3	70.4	67.6
70°	391.6	276.1	231.0	186.0	160.6	135.2	107.1	81.7	76.1	73.3	67.6
72.5°	326.8	250.8	214.1	177.5	157.8	138.1	118.3	98.6	87.3	78.9	67.6
75°	273.3	225.4	194.4	160.6	146.5	135.2	121.2	107.1	93.0	78.9	64.8
77.5°	180.3	163.4	149.3	135.2	126.8	118.3	107.1	98.6	84.5	73.3	59.2
80°	76.1	70.4	73.3	73.3	73.3	73.3	70.4	70.4	62.0	53.5	42.3
82.5°	16.9	14.1	16.9	16.9	16.9	16.9	14.1	14.1	14.1	11.3	11.3
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7
5°	22.5	22.5	22.5	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7
7.5°	22.5	22.5	22.5	19.7	19.7	19.7	19.7	16.9	16.9	16.9	16.9
10°	22.5	22.5	22.5	19.7	19.7	19.7	19.7	16.9	16.9	16.9	16.9
12.5°	25.4	25.4	22.5	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
15°	25.4	25.4	22.5	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
17.5°	28.2	25.4	25.4	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
20°	28.2	25.4	25.4	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
22.5°	28.2	25.4	25.4	22.5	19.7	19.7	16.9	16.9	14.1	14.1	11.3
25°	28.2	25.4	25.4	22.5	19.7	19.7	16.9	16.9	14.1	11.3	11.3
27.5°	28.2	25.4	25.4	22.5	19.7	16.9	16.9	14.1	11.3	8.5	8.5
30°	28.2	25.4	25.4	22.5	19.7	16.9	14.1	11.3	8.5	8.5	5.6
32.5°	28.2	25.4	22.5	19.7	16.9	14.1	14.1	11.3	8.5	5.6	5.6
35°	28.2	25.4	22.5	19.7	16.9	14.1	14.1	11.3	8.5	5.6	5.6
37.5°	28.2	25.4	22.5	19.7	16.9	14.1	11.3	8.5	5.6	5.6	2.8
40°	28.2	25.4	22.5	19.7	16.9	14.1	11.3	8.5	5.6	5.6	2.8
42.5°	28.2	25.4	22.5	19.7	16.9	14.1	11.3	8.5	5.6	5.6	2.8
45°	31.0	28.2	25.4	19.7	16.9	14.1	14.1	11.3	8.5	5.6	5.6
47.5°	31.0	28.2	25.4	19.7	16.9	14.1	14.1	11.3	8.5	5.6	5.6
50°	33.8	31.0	28.2	22.5	19.7	16.9	14.1	8.5	5.6	5.6	2.8
52.5°	36.6	33.8	31.0	28.2	25.4	19.7	14.1	8.5	2.8	2.8	2.8
55°	39.4	36.6	36.6	33.8	31.0	22.5	16.9	8.5	0.0	0.0	0.0
57.5°	42.3	39.4	39.4	36.6	33.8	25.4	16.9	8.5	0.0	0.0	0.0
60°	47.9	45.1	42.3	36.6	33.8	25.4	16.9	8.5	0.0	0.0	0.0
62.5°	56.4	50.7	42.3	36.6	28.2	22.5	14.1	8.5	0.0	0.0	0.0
65°	62.0	53.5	45.1	33.8	25.4	19.7	14.1	5.6	0.0	0.0	0.0
67.5°	64.8	53.5	45.1	33.8	22.5	16.9	11.3	5.6	0.0	0.0	0.0
70°	62.0	50.7	42.3	31.0	19.7	14.1	11.3	5.6	0.0	0.0	0.0
72.5°	56.4	47.9	36.6	28.2	16.9	14.1	8.5	5.6	0.0	0.0	0.0
75°	50.7	42.3	31.0	22.5	11.3	8.5	5.6	2.8	0.0	0.0	0.0
77.5°	45.1	36.6	25.4	16.9	5.6	5.6	2.8	2.8	0.0	0.0	0.0
80°	33.8	25.4	16.9	8.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	8.5	5.6	5.6	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9
5°	16.9	16.9	16.9	16.9	14.1	14.1	14.1	14.1	14.1	14.1	14.1
7.5°	16.9	16.9	16.9	16.9	14.1	14.1	14.1	14.1	11.3	11.3	11.3
10°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	11.3	11.3	11.3
12.5°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	11.3	11.3	11.3
15°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	11.3	11.3	8.5	8.5
17.5°	14.1	14.1	14.1	14.1	11.3	11.3	11.3	8.5	8.5	5.6	5.6
20°	14.1	14.1	14.1	11.3	11.3	8.5	8.5	5.6	5.6	2.8	2.8
22.5°	11.3	8.5	8.5	5.6	5.6	2.8	2.8	2.8	0.0	0.0	0.0
25°	8.5	5.6	5.6	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	16.9	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1
5°	14.1	14.1	14.1	14.1	11.3	11.3	11.3	11.3	11.3	11.3	11.3
7.5°	11.3	11.3	11.3	11.3	11.3	11.3	8.5	8.5	8.5	8.5	8.5
10°	11.3	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	5.6	5.6
12.5°	11.3	8.5	8.5	8.5	5.6	5.6	5.6	5.6	5.6	2.8	2.8
15°	8.5	5.6	5.6	5.6	2.8	2.8	2.8	2.8	2.8	0.0	0.0
17.5°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	16.9	16.9
5°	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3
7.5°	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5
10°	5.6	5.6	5.6	5.6	5.6	5.6	2.8	2.8	2.8	2.8	2.8
12.5°	2.8	2.8	2.8	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	16.9	16.9	16.9	16.9	16.9	19.7	19.7	22.5	22.5	25.4	25.4
5°	11.3	11.3	14.1	14.1	14.1	14.1	16.9	16.9	16.9	19.7	19.7
7.5°	8.5	8.5	8.5	8.5	8.5	11.3	11.3	14.1	14.1	16.9	16.9
10°	2.8	2.8	5.6	5.6	5.6	5.6	8.5	8.5	8.5	11.3	14.1
12.5°	0.0	0.0	2.8	2.8	2.8	2.8	5.6	5.6	5.6	8.5	11.3
15°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	5.6	8.5
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	5.6
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	28.2	28.2	31.0	31.0	33.8	33.8	36.6	36.6	36.6	36.6	36.6
5°	22.5	22.5	25.4	28.2	28.2	31.0	33.8	33.8	33.8	33.8	33.8
7.5°	19.7	19.7	22.5	25.4	25.4	28.2	31.0	31.0	33.8	33.8	33.8
10°	14.1	16.9	19.7	22.5	22.5	25.4	28.2	28.2	31.0	31.0	31.0
12.5°	11.3	14.1	16.9	19.7	19.7	22.5	25.4	25.4	28.2	28.2	31.0
15°	8.5	11.3	14.1	16.9	16.9	19.7	22.5	22.5	25.4	28.2	31.0
17.5°	5.6	8.5	11.3	14.1	14.1	16.9	19.7	22.5	25.4	25.4	28.2
20°	5.6	5.6	8.5	11.3	11.3	14.1	16.9	19.7	22.5	22.5	25.4
22.5°	2.8	2.8	5.6	8.5	8.5	11.3	14.1	16.9	19.7	19.7	22.5
25°	0.0	0.0	2.8	5.6	5.6	8.5	11.3	11.3	14.1	14.1	16.9
27.5°	0.0	0.0	2.8	2.8	5.6	5.6	8.5	8.5	11.3	11.3	14.1
30°	0.0	0.0	2.8	2.8	5.6	5.6	8.5	8.5	11.3	11.3	11.3
32.5°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	8.5	8.5	11.3
35°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	8.5	8.5	8.5
37.5°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	5.6	5.6	8.5
40°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
45°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
50°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
55°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
75°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
80°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	5.6
85°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	36.6	36.6
5°	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	33.8	33.8
7.5°	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	33.8	33.8
10°	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
12.5°	31.0	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
15°	31.0	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
17.5°	28.2	31.0	31.0	31.0	33.8	33.8	33.8	33.8	33.8	33.8	33.8
20°	25.4	28.2	28.2	28.2	31.0	31.0	31.0	31.0	33.8	33.8	33.8
22.5°	22.5	25.4	25.4	25.4	28.2	28.2	28.2	28.2	31.0	31.0	31.0
25°	19.7	19.7	22.5	22.5	25.4	25.4	25.4	25.4	25.4	25.4	25.4
27.5°	14.1	16.9	16.9	16.9	19.7	19.7	19.7	19.7	22.5	22.5	22.5
30°	14.1	14.1	14.1	14.1	16.9	16.9	16.9	16.9	19.7	19.7	19.7
32.5°	11.3	14.1	14.1	14.1	16.9	16.9	16.9	16.9	19.7	19.7	19.7
35°	11.3	11.3	11.3	11.3	14.1	14.1	14.1	14.1	16.9	16.9	16.9
37.5°	8.5	11.3	11.3	11.3	14.1	14.1	14.1	14.1	16.9	16.9	16.9
40°	8.5	8.5	8.5	8.5	11.3	11.3	11.3	11.3	14.1	14.1	14.1
42.5°	8.5	8.5	8.5	8.5	11.3	11.3	11.3	11.3	14.1	14.1	14.1
45°	8.5	8.5	8.5	8.5	11.3	11.3	11.3	11.3	14.1	14.1	14.1
47.5°	8.5	8.5	8.5	8.5	11.3	11.3	11.3	11.3	14.1	14.1	14.1
50°	8.5	8.5	8.5	8.5	11.3	11.3	11.3	11.3	14.1	14.1	14.1
52.5°	5.6	5.6	5.6	5.6	8.5	8.5	8.5	8.5	11.3	11.3	11.3
55°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	8.5	8.5	8.5
57.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	8.5	8.5	8.5
60°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
62.5°	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
65°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	2.8	2.8
67.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
70°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
72.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
75°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
77.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
80°	8.5	8.5	8.5	8.5	8.5	5.6	5.6	5.6	5.6	5.6	5.6
82.5°	5.6	8.5	8.5	8.5	8.5	5.6	5.6	5.6	5.6	5.6	5.6
85°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
87.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	36.6	36.6	33.8	33.8	33.8	33.8	33.8	33.8	33.8	36.6	36.6
5°	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	36.6	36.6
7.5°	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	36.6	36.6
10°	33.8	33.8	33.8	33.8	31.0	31.0	33.8	33.8	33.8	36.6	36.6
12.5°	33.8	33.8	33.8	33.8	31.0	31.0	33.8	33.8	36.6	36.6	39.4
15°	33.8	33.8	31.0	31.0	31.0	31.0	33.8	33.8	36.6	36.6	39.4
17.5°	33.8	33.8	31.0	31.0	31.0	31.0	33.8	33.8	36.6	36.6	39.4
20°	33.8	33.8	31.0	31.0	31.0	31.0	31.0	31.0	33.8	36.6	36.6
22.5°	31.0	31.0	31.0	31.0	28.2	28.2	31.0	31.0	33.8	36.6	36.6
25°	25.4	28.2	28.2	28.2	28.2	28.2	31.0	31.0	33.8	36.6	36.6
27.5°	22.5	25.4	25.4	25.4	25.4	28.2	28.2	31.0	33.8	36.6	36.6
30°	19.7	22.5	22.5	22.5	25.4	28.2	28.2	31.0	33.8	36.6	36.6
32.5°	19.7	22.5	22.5	22.5	25.4	25.4	28.2	28.2	31.0	33.8	36.6
35°	19.7	19.7	22.5	22.5	22.5	25.4	25.4	28.2	31.0	33.8	36.6
37.5°	19.7	19.7	22.5	22.5	22.5	25.4	25.4	28.2	31.0	33.8	36.6
40°	16.9	19.7	19.7	22.5	22.5	25.4	25.4	28.2	31.0	36.6	39.4
42.5°	16.9	16.9	19.7	19.7	22.5	25.4	25.4	28.2	31.0	36.6	39.4
45°	16.9	19.7	19.7	22.5	25.4	28.2	28.2	31.0	33.8	36.6	39.4
47.5°	16.9	19.7	19.7	22.5	28.2	28.2	31.0	31.0	33.8	36.6	39.4
50°	16.9	19.7	19.7	22.5	31.0	31.0	31.0	31.0	33.8	36.6	39.4
52.5°	14.1	16.9	16.9	19.7	25.4	28.2	31.0	33.8	36.6	39.4	42.3
55°	11.3	14.1	14.1	16.9	22.5	25.4	31.0	36.6	39.4	42.3	45.1
57.5°	11.3	11.3	14.1	14.1	19.7	25.4	33.8	39.4	42.3	45.1	47.9
60°	8.5	8.5	11.3	11.3	16.9	22.5	31.0	39.4	42.3	47.9	50.7
62.5°	5.6	8.5	8.5	11.3	14.1	22.5	31.0	39.4	45.1	50.7	53.5
65°	5.6	5.6	8.5	8.5	14.1	19.7	28.2	33.8	42.3	50.7	59.2
67.5°	8.5	8.5	11.3	11.3	14.1	19.7	28.2	33.8	42.3	53.5	62.0
70°	8.5	8.5	11.3	11.3	16.9	22.5	28.2	33.8	42.3	53.5	62.0
72.5°	8.5	8.5	11.3	11.3	16.9	19.7	25.4	31.0	39.4	47.9	56.4
75°	5.6	8.5	8.5	8.5	14.1	16.9	22.5	28.2	36.6	45.1	53.5
77.5°	5.6	5.6	5.6	5.6	11.3	14.1	19.7	22.5	31.0	39.4	47.9
80°	5.6	5.6	5.6	5.6	8.5	11.3	16.9	19.7	28.2	36.6	45.1
82.5°	5.6	5.6	2.8	2.8	5.6	8.5	11.3	14.1	22.5	28.2	36.6
85°	5.6	5.6	2.8	2.8	2.8	5.6	5.6	8.5	11.3	14.1	16.9
87.5°	5.6	5.6	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	36.6	36.6	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
5°	36.6	39.4	39.4	42.3	42.3	42.3	45.1	45.1	45.1	45.1	45.1
7.5°	36.6	39.4	39.4	42.3	42.3	42.3	45.1	45.1	45.1	47.9	47.9
10°	36.6	39.4	39.4	42.3	42.3	45.1	47.9	47.9	50.7	50.7	50.7
12.5°	39.4	42.3	42.3	45.1	45.1	47.9	50.7	50.7	53.5	56.4	56.4
15°	39.4	42.3	45.1	45.1	47.9	50.7	53.5	53.5	56.4	59.2	62.0
17.5°	39.4	42.3	45.1	45.1	47.9	50.7	56.4	59.2	62.0	67.6	70.4
20°	39.4	42.3	45.1	45.1	47.9	53.5	56.4	62.0	64.8	70.4	76.1
22.5°	39.4	42.3	45.1	47.9	50.7	56.4	62.0	64.8	70.4	78.9	84.5
25°	39.4	42.3	45.1	47.9	50.7	56.4	62.0	67.6	73.3	84.5	95.8
27.5°	39.4	42.3	47.9	50.7	53.5	59.2	67.6	73.3	78.9	98.6	118.3
30°	39.4	42.3	47.9	50.7	53.5	62.0	70.4	76.1	84.5	118.3	149.3
32.5°	39.4	45.1	47.9	53.5	56.4	64.8	76.1	84.5	93.0	140.9	186.0
35°	39.4	45.1	47.9	53.5	56.4	67.6	78.9	90.2	101.4	171.9	242.3
37.5°	39.4	45.1	47.9	53.5	56.4	73.3	90.2	107.1	124.0	197.2	270.5
40°	42.3	47.9	50.7	56.4	59.2	76.1	93.0	109.9	126.8	200.0	273.3
42.5°	42.3	47.9	50.7	56.4	59.2	73.3	90.2	104.2	118.3	200.0	281.8
45°	42.3	47.9	53.5	56.4	62.0	76.1	90.2	101.4	115.5	219.8	321.2
47.5°	42.3	47.9	53.5	56.4	62.0	76.1	90.2	104.2	118.3	290.2	459.3
50°	42.3	47.9	53.5	56.4	62.0	78.9	95.8	112.7	129.6	433.9	738.2
52.5°	45.1	47.9	53.5	56.4	59.2	78.9	98.6	118.3	138.1	563.5	986.1
55°	47.9	50.7	53.5	56.4	59.2	84.5	109.9	135.2	160.6	605.8	1048.1
57.5°	50.7	53.5	56.4	56.4	59.2	90.2	124.0	155.0	186.0	603.0	1017.1
60°	53.5	56.4	59.2	62.0	64.8	95.8	129.6	160.6	191.6	546.6	901.6
62.5°	59.2	64.8	70.4	73.3	78.9	109.9	138.1	169.1	197.2	448.0	695.9
65°	67.6	73.3	76.1	81.7	84.5	112.7	143.7	171.9	200.0	371.9	541.0
67.5°	70.4	76.1	78.9	84.5	87.3	115.5	143.7	171.9	200.0	315.6	428.3
70°	70.4	76.1	81.7	84.5	90.2	118.3	143.7	171.9	197.2	273.3	349.4
72.5°	64.8	73.3	78.9	87.3	93.0	118.3	140.9	166.2	188.8	242.3	295.8
75°	62.0	73.3	81.7	93.0	101.4	118.3	138.1	155.0	171.9	211.3	250.8
77.5°	56.4	70.4	84.5	98.6	112.7	124.0	132.4	143.7	152.1	177.5	202.9
80°	53.5	67.6	81.7	95.8	109.9	115.5	118.3	124.0	126.8	129.6	132.4
82.5°	42.3	53.5	64.8	73.3	84.5	78.9	76.1	70.4	64.8	62.0	59.2
85°	19.7	22.5	22.5	25.4	25.4	25.4	22.5	22.5	19.7	16.9	14.1
87.5°	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	39.4	39.4	39.4	39.4	36.6	36.6	36.6	36.6	33.8	33.8	33.8
5°	45.1	45.1	45.1	45.1	42.3	42.3	42.3	42.3	39.4	39.4	39.4
7.5°	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9
10°	53.5	53.5	53.5	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4
12.5°	59.2	59.2	62.0	62.0	64.8	64.8	67.6	67.6	70.4	70.4	70.4
15°	64.8	67.6	70.4	73.3	73.3	76.1	78.9	81.7	84.5	87.3	90.2
17.5°	76.1	78.9	84.5	90.2	95.8	101.4	109.9	121.2	129.6	138.1	149.3
20°	84.5	93.0	109.9	129.6	146.5	163.4	205.7	247.9	290.2	332.5	374.7
22.5°	101.4	118.3	174.7	233.9	290.2	346.6	479.0	611.4	741.0	873.4	991.8
25°	135.2	171.9	301.5	431.1	557.9	687.5	924.2	1163.6	1400.3	1637.0	1856.8
27.5°	186.0	253.6	464.9	679.0	890.3	1101.7	1445.4	1792.0	2135.7	2482.3	2789.4
30°	259.2	369.1	684.7	1003.0	1318.6	1634.2	2068.1	2504.8	2938.7	3372.6	3654.4
32.5°	352.2	515.6	915.7	1315.8	1715.9	2116.0	2595.0	3073.9	3550.1	4029.1	4327.8
35°	450.8	659.3	1141.1	1625.7	2107.5	2592.1	3096.5	3600.8	4105.2	4609.5	4975.8
37.5°	507.2	743.8	1315.8	1887.8	2456.9	3028.9	3581.1	4136.2	4688.4	5240.6	5685.8
40°	560.7	845.3	1504.6	2163.9	2823.2	3482.5	4127.7	4772.9	5418.1	6063.4	6635.3
42.5°	639.6	997.4	1766.6	2535.8	3302.2	4071.4	4919.4	5770.3	6618.4	7466.5	8345.6
45°	803.0	1284.8	2282.2	3279.6	4274.2	5271.6	6474.7	7680.6	8883.7	10089.6	11216.7
47.5°	1197.5	1932.8	3293.7	4654.6	6015.5	7376.3	8762.6	10148.8	11535.0	12921.3	14262.4
50°	1853.9	2966.9	4668.7	6370.5	8069.5	9771.3	11154.7	12538.1	13918.7	15302.1	16634.8
52.5°	2471.0	3955.8	5784.4	7615.8	9444.4	11275.8	12501.5	13727.1	14952.7	16178.4	17468.8
55°	2682.3	4313.7	6164.8	8018.7	9869.9	11723.8	12904.4	14087.7	15268.3	16448.9	17787.2
57.5°	2496.3	3975.6	5840.8	7706.0	9568.4	11433.6	12752.2	14073.7	15392.3	16713.7	18147.8
60°	2090.6	3276.8	5235.0	7196.0	9154.2	11112.4	12600.1	14087.7	15575.4	17063.1	18494.4
62.5°	1656.7	2614.7	4688.4	6762.1	8835.8	10909.6	12422.6	13938.4	15451.4	16964.5	18063.3
65°	1270.7	2000.5	4040.4	6083.1	8123.0	10165.7	11405.4	12648.0	13887.7	15130.2	15891.0
67.5°	943.9	1459.5	3243.0	5029.3	6812.8	8596.3	9509.2	10424.9	11337.8	12253.5	12845.2
70°	695.9	1039.7	2254.0	3468.4	4679.9	5894.3	6731.1	7567.9	8401.9	9238.7	9853.0
72.5°	481.8	664.9	1391.9	2121.6	2848.5	3575.5	4423.6	5271.6	6116.9	6965.0	7663.7
75°	329.7	408.5	749.5	1090.4	1431.3	1772.2	2414.6	3057.0	3699.4	4341.8	4710.9
77.5°	245.1	287.4	388.8	493.1	594.5	695.9	819.9	943.9	1067.9	1191.8	1352.4
80°	135.2	135.2	149.3	160.6	174.7	186.0	219.8	256.4	290.2	326.8	371.9
82.5°	62.0	64.8	70.4	76.1	78.9	84.5	90.2	95.8	101.4	107.1	107.1
85°	16.9	19.7	19.7	16.9	16.9	14.1	14.1	16.9	16.9	16.9	16.9
87.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	33.8	31.0	31.0	31.0	28.2	28.2	28.2	28.2	28.2	28.2	28.2
5°	39.4	39.4	39.4	39.4	36.6	36.6	36.6	36.6	36.6	33.8	33.8
7.5°	47.9	45.1	45.1	45.1	45.1	45.1	45.1	45.1	45.1	42.3	42.3
10°	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	53.5	53.5
12.5°	70.4	70.4	70.4	70.4	73.3	73.3	70.4	70.4	70.4	67.6	67.6
15°	93.0	95.8	98.6	98.6	101.4	101.4	101.4	98.6	98.6	95.8	93.0
17.5°	157.8	166.2	177.5	188.8	200.0	208.5	208.5	202.9	197.2	191.6	186.0
20°	419.8	462.1	507.2	552.2	600.1	633.9	611.4	594.5	577.6	557.9	541.0
22.5°	1112.9	1231.3	1352.4	1437.0	1521.5	1580.6	1532.7	1439.8	1346.8	1256.6	1163.6
25°	2076.5	2293.5	2513.3	2603.4	2696.4	2764.0	2733.0	2592.1	2451.3	2313.2	2172.3
27.5°	3096.5	3400.8	3707.9	3786.8	3865.7	3924.8	3913.6	3730.4	3547.3	3364.2	3181.0
30°	3936.1	4217.9	4499.6	4578.5	4657.4	4710.9	4651.8	4468.6	4285.5	4102.4	3919.2
32.5°	4629.2	4927.9	5229.4	5333.6	5437.9	5508.3	5437.9	5218.1	4998.3	4781.4	4561.6
35°	5342.1	5705.5	6071.8	6204.2	6336.7	6421.2	6302.9	6032.4	5761.9	5494.2	5223.7
37.5°	6131.0	6573.3	7018.5	7198.8	7382.0	7508.8	7418.6	7080.5	6739.6	6401.5	6060.5
40°	7210.1	7782.1	8356.9	8680.9	9002.1	9230.3	9069.7	8678.1	8283.6	7892.0	7497.5
42.5°	9227.5	10106.5	10985.6	11450.5	11912.6	12247.9	12067.6	11585.8	11104.0	10622.2	10140.4
45°	12343.7	13467.9	14594.9	15273.9	15955.8	16457.3	16248.8	15643.0	15034.4	14428.7	13822.9
47.5°	15603.6	16944.7	18285.9	18826.9	19370.7	19793.3	19742.6	18987.5	18232.4	17480.1	16725.0
50°	17970.3	19303.0	20635.7	21100.6	21568.3	21914.9	21785.3	20824.5	19860.9	18900.1	17936.5
52.5°	18759.2	20046.9	21337.3	21892.4	22447.4	22861.6	22703.8	21621.9	20539.9	19460.8	18378.9
55°	19125.5	20463.9	21802.2	22478.4	23157.4	23653.3	23425.1	22238.9	21049.9	19863.7	18674.7
57.5°	19582.0	21016.1	22450.2	23191.2	23932.3	24467.6	24163.3	22934.9	21706.4	20480.8	19252.3
60°	19925.7	21354.2	22785.5	23380.0	23977.3	24394.3	24101.3	22906.7	21709.2	20514.6	19319.9
62.5°	19165.0	20263.8	21362.7	21805.0	22247.4	22568.6	22402.3	21269.7	20137.0	19004.4	17871.7
65°	16654.5	17415.3	18178.8	18477.5	18773.3	19001.6	18950.8	17995.7	17040.5	16088.2	15133.1
67.5°	13439.7	14031.4	14625.9	15048.5	15474.0	15803.6	15767.0	14896.4	14025.8	13155.1	12284.5
70°	10470.0	11084.2	11698.5	12231.0	12766.3	13180.5	13127.0	12318.3	11506.9	10698.2	9886.8
72.5°	8365.3	9064.1	9762.8	10067.1	10371.4	10585.5	10427.8	9816.3	9202.1	8590.7	7976.5
75°	5080.0	5446.3	5815.4	5812.6	5812.6	5778.8	5621.0	5271.6	4922.3	4572.9	4223.5
77.5°	1513.0	1673.6	1834.2	1989.2	2147.0	2265.3	2234.3	2051.2	1865.2	1682.1	1496.1
80°	417.0	459.3	504.3	524.1	543.8	569.1	633.9	588.9	543.8	501.5	456.4
82.5°	107.1	107.1	107.1	104.2	101.4	95.8	87.3	81.7	76.1	70.4	64.8
85°	16.9	14.1	14.1	14.1	11.3	11.3	11.3	11.3	8.5	8.5	5.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
2.5°	28.2	28.2	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	22.5
5°	33.8	33.8	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	28.2
7.5°	42.3	42.3	39.4	39.4	39.4	39.4	36.6	36.6	36.6	36.6	33.8
10°	53.5	50.7	50.7	47.9	47.9	47.9	45.1	45.1	45.1	42.3	42.3
12.5°	67.6	64.8	64.8	62.0	59.2	59.2	56.4	53.5	50.7	50.7	47.9
15°	90.2	87.3	84.5	81.7	78.9	73.3	70.4	64.8	62.0	59.2	56.4
17.5°	171.9	157.8	143.7	129.6	118.3	107.1	95.8	84.5	78.9	73.3	67.6
20°	479.0	414.2	352.2	290.2	250.8	211.3	171.9	132.4	115.5	101.4	84.5
22.5°	1036.9	907.3	780.5	650.9	546.6	445.2	340.9	236.7	197.2	160.6	121.2
25°	1927.2	1679.3	1434.1	1186.2	989.0	791.7	594.5	397.3	324.0	250.8	177.5
27.5°	2859.8	2538.6	2217.4	1896.2	1583.5	1267.9	952.3	639.6	512.8	388.8	262.0
30°	3578.3	3237.4	2899.3	2558.3	2163.9	1769.4	1372.1	977.7	777.6	577.6	374.7
32.5°	4195.3	3826.2	3460.0	3090.9	2634.4	2178.0	1721.5	1265.1	1014.3	763.6	510.0
35°	4806.7	4386.9	3969.9	3550.1	3059.9	2569.6	2079.4	1589.1	1270.7	952.3	631.1
37.5°	5550.6	5037.8	4527.8	4017.8	3513.5	3012.0	2507.6	2003.3	1597.6	1194.6	788.9
40°	6846.6	6193.0	5542.1	4888.4	4299.6	3713.5	3124.7	2535.8	2025.8	1515.8	1003.0
42.5°	9320.5	8500.5	7683.5	6863.6	6049.3	5235.0	4417.9	3603.6	2876.7	2152.6	1425.7
45°	12772.0	11721.0	10672.9	9621.9	8618.9	7618.7	6615.6	5612.6	4508.1	3403.6	2296.3
47.5°	15575.4	14423.0	13273.5	12121.1	11008.2	9898.1	8785.1	7672.2	6257.8	4846.2	3431.8
50°	16840.5	15741.6	14645.6	13546.8	12431.0	11312.5	10193.9	9078.1	7455.2	5835.1	4212.2
52.5°	17265.9	16150.2	15037.3	13921.5	12814.2	11706.9	10599.6	9492.3	7804.6	6119.7	4432.0
55°	17499.8	16322.1	15147.1	13969.4	12777.6	11582.9	10388.3	9196.5	7517.2	5840.8	4161.5
57.5°	17973.1	16691.2	15412.0	14130.0	12772.0	11413.9	10053.0	8695.0	7038.2	5381.5	3724.8
60°	18060.5	16798.2	15538.8	14279.3	12777.6	11275.8	9771.3	8269.5	6624.1	4981.4	3336.0
62.5°	16818.0	15764.2	14713.2	13659.5	12154.9	10650.3	9142.9	7638.4	6063.4	4488.4	2910.5
65°	14223.0	13312.9	12405.7	11495.6	10267.1	9041.5	7813.1	6584.6	5178.7	3775.5	2369.6
67.5°	11394.2	10503.8	9616.3	8726.0	7801.8	6880.5	5956.3	5032.1	3947.4	2862.6	1777.9
70°	9033.1	8176.5	7322.8	6466.3	5649.2	4829.3	4009.4	3192.3	2518.9	1848.3	1174.9
72.5°	7159.4	6339.5	5522.4	4702.5	3961.5	3220.5	2479.4	1738.4	1403.1	1070.7	735.4
75°	3798.1	3372.6	2950.0	2524.5	2107.5	1687.7	1267.9	850.9	718.5	586.1	450.8
77.5°	1310.2	1124.2	941.1	755.1	628.3	501.5	374.7	247.9	233.9	222.6	208.5
80°	397.3	338.1	278.9	219.8	194.4	169.1	143.7	118.3	109.9	101.4	90.2
82.5°	62.0	56.4	53.5	47.9	45.1	45.1	42.3	39.4	33.8	31.0	25.4
85°	5.6	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	25.4	25.4
2.5°	22.5	22.5
5°	28.2	28.2
7.5°	33.8	33.8
10°	39.4	39.4
12.5°	45.1	45.1
15°	53.5	50.7
17.5°	62.0	59.2
20°	67.6	62.0
22.5°	81.7	70.4
25°	104.2	87.3
27.5°	135.2	107.1
30°	174.7	135.2
32.5°	259.2	188.8
35°	312.7	228.2
37.5°	383.2	264.8
40°	493.1	321.2
42.5°	698.8	436.7
45°	1191.8	724.1
47.5°	2020.2	1234.1
50°	2589.3	1583.5
52.5°	2747.1	1679.3
55°	2485.1	1541.2
57.5°	2068.1	1310.2
60°	1693.3	1079.1
62.5°	1335.5	853.7
65°	963.6	645.2
67.5°	693.1	495.9
70°	504.3	388.8
72.5°	400.1	324.0
75°	318.4	270.5
77.5°	197.2	180.3
80°	81.7	76.1
82.5°	19.7	16.9
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1067665

CATALOG NUMBER: NAV-SA4A-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-2

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-722-U-5WQ


Data in this report applies to families of products including GSS-SB1A-722-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-722-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2200K CCT 26 LEDS

Spectral Parameters

CCT (K):	2160	CRI (Ra):	71.9		
CIE u':	0.2927	R1:	68.7	R9:	-17.8
CIE v':	0.5388	R2:	82.6	R10:	60.5
Duv:	0.0015	R3:	95.5	R11:	60.2
CIE x:	0.5130	R4:	66.4	R12:	48.2
CIE y:	0.4197	R5:	65.4	R13:	70.7
CIE z:	0.0674	R6:	75.9	R14:	96.8
Peak Wavelength (nm):	609	R7:	77.2	R15:	61.8
Dominant Wavelength (nm):	587	R8:	43.5		
Purity:	79.96089				
Rf:	70.6				
Rg:	97.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-2

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-2

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2200K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-2

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 0.8

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.21

λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			


REPORT NUMBER: SP1-2407-184-2

TM-30-18





Summary

$R_f = 70.6$
 $R_g = 97.6$
 $CIE R_a = 71.9$
 $R_g = -17.8$

Spectral Power Distribution Comparison



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 87	CES26 = 60	CES51 = 74	CES76 = 58
CES02 = 65	CES27 = 77	CES52 = 77	CES77 = 82
CES03 = 32	CES28 = 85	CES53 = 65	CES78 = 65
CES04 = 72	CES29 = 50	CES54 = 77	CES79 = 86
CES05 = 52	CES30 = 49	CES55 = 74	CES80 = 85
CES06 = 53	CES31 = 55	CES56 = 64	CES81 = 61
CES07 = 44	CES32 = 55	CES57 = 60	CES82 = 93
CES08 = 43	CES33 = 55	CES58 = 64	CES83 = 83
CES09 = 29	CES34 = 75	CES59 = 84	CES84 = 93
CES10 = 79	CES35 = 88	CES60 = 89	CES85 = 81
CES11 = 62	CES36 = 78	CES61 = 84	CES86 = 55
CES12 = 68	CES37 = 82	CES62 = 68	CES87 = 79
CES13 = 45	CES38 = 54	CES63 = 68	CES88 = 72
CES14 = 75	CES39 = 90	CES64 = 69	CES89 = 62
CES15 = 72	CES40 = 86	CES65 = 66	CES90 = 67
CES16 = 49	CES41 = 75	CES66 = 64	CES91 = 89
CES17 = 51	CES42 = 83	CES67 = 63	CES92 = 67
CES18 = 57	CES43 = 68	CES68 = 71	CES93 = 78
CES19 = 74	CES44 = 98	CES69 = 81	CES94 = 52
CES20 = 68	CES45 = 76	CES70 = 65	CES95 = 76
CES21 = 89	CES46 = 68	CES71 = 64	CES96 = 78
CES22 = 81	CES47 = 60	CES72 = 88	CES97 = 76
CES23 = 92	CES48 = 47	CES73 = 59	CES98 = 71
CES24 = 92	CES49 = 65	CES74 = 85	CES99 = 65
CES25 = 74	CES50 = 74	CES75 = 66	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)