

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMARK

Report Number: P1067667

Luminaire Tested: **NAV-SA4C-722-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1067667
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMARK
Catalog Number: NAV-SA4C-722-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 4xLight Square PACKAGE
70CRI 2200K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 2200K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13946.1 lumens
Efficiency: N/A
Efficacy: 73.2 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 190.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	82.9	0.0	82.9
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	13863.1	0.0	13863.1
	% Fixture	99.4	0.0	99.4
Total	Lumens	13946.0	0.0	13946.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.1	0.0
10°-20°	20.5	0.1
20°-30°	260.3	1.9
30°-40°	877.3	6.3
40°-50°	2649.3	19.0
50°-60°	4674.2	33.5
60°-70°	4118.0	29.5
70°-80°	1310.8	9.4
80°-90°	31.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13946.0	100.0
0°-180°	13946.1	100.0



REPORT NUMBER: P1067667


CATALOG NUMBER: NAV-SA4C-722-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	272.4	2.0			
FM	(30°-60°)	8168.7	58.6			
FH	(60°-80°)	5396.3	38.7			G3/7500
FVH	(80°-90°)	25.7	0.2			G1/100
BL	(0°-30°)	12.4	0.1	B0/110		
BM	(30°-60°)	32.1	0.2	B0/220		
BH	(60°-80°)	32.5	0.2	B0/110		G0/110
BVH	(80°-90°)	5.9	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	30.6
5°	43.7	43.7	43.7	39.4	39.4	39.4	35.0	35.0	35.0	35.0	35.0
7.5°	52.5	48.1	48.1	43.7	43.7	43.7	39.4	39.4	39.4	39.4	35.0
10°	61.2	56.9	56.9	52.5	52.5	48.1	48.1	43.7	43.7	39.4	39.4
12.5°	70.0	65.6	61.2	56.9	56.9	52.5	52.5	48.1	48.1	43.7	43.7
15°	78.7	74.3	70.0	65.6	61.2	61.2	56.9	52.5	48.1	48.1	43.7
17.5°	91.8	83.1	78.7	70.0	65.6	61.2	56.9	52.5	52.5	48.1	48.1
20°	96.2	87.5	83.1	74.3	70.0	65.6	61.2	56.9	52.5	52.5	48.1
22.5°	113.7	96.2	91.8	83.1	78.7	74.3	65.6	61.2	56.9	52.5	48.1
25°	140.0	113.7	100.6	87.5	83.1	74.3	70.0	61.2	56.9	52.5	48.1
27.5°	170.6	126.8	113.7	96.2	87.5	78.7	70.0	61.2	56.9	52.5	48.1
30°	209.9	148.7	126.8	105.0	96.2	87.5	74.3	65.6	61.2	56.9	48.1
32.5°	293.0	183.7	148.7	113.7	100.6	91.8	78.7	65.6	61.2	56.9	48.1
35°	354.3	223.0	179.3	131.2	113.7	100.6	83.1	65.6	61.2	56.9	48.1
37.5°	411.1	227.4	183.7	140.0	122.5	105.0	83.1	65.6	61.2	56.9	48.1
40°	502.9	236.2	183.7	131.2	118.1	100.6	87.5	70.0	65.6	56.9	52.5
42.5°	677.9	271.2	196.8	122.5	109.3	100.6	87.5	74.3	65.6	61.2	52.5
45°	1128.4	402.4	266.8	126.8	113.7	100.6	87.5	74.3	70.0	61.2	56.9
47.5°	1920.0	699.8	415.5	131.2	118.1	100.6	87.5	70.0	65.6	61.2	52.5
50°	2457.9	896.6	524.8	153.1	131.2	113.7	91.8	70.0	65.6	61.2	56.9
52.5°	2611.0	953.4	568.6	179.3	153.1	126.8	96.2	70.0	65.6	65.6	61.2
55°	2392.3	927.2	568.6	209.9	174.9	144.3	109.3	74.3	70.0	70.0	65.6
57.5°	2033.7	857.2	542.3	227.4	192.4	153.1	118.1	78.7	74.3	74.3	70.0
60°	1675.0	721.6	489.8	253.7	214.3	174.9	135.6	96.2	91.8	87.5	78.7
62.5°	1329.5	581.7	428.6	271.2	231.8	188.1	148.7	105.0	100.6	96.2	91.8
65°	1001.5	507.3	398.0	284.3	240.5	196.8	153.1	109.3	105.0	105.0	100.6
67.5°	769.7	463.6	380.5	293.0	249.3	205.6	161.8	118.1	113.7	109.3	105.0
70°	607.9	428.6	358.6	288.6	249.3	209.9	166.2	126.8	118.1	113.7	105.0
72.5°	507.3	389.2	332.4	275.5	244.9	214.3	183.7	153.1	135.6	122.5	105.0
75°	424.2	349.9	301.8	249.3	227.4	209.9	188.1	166.2	144.3	122.5	100.6
77.5°	279.9	253.7	231.8	209.9	196.8	183.7	166.2	153.1	131.2	113.7	91.8
80°	118.1	109.3	113.7	113.7	113.7	113.7	109.3	109.3	96.2	83.1	65.6
82.5°	26.2	21.9	26.2	26.2	26.2	26.2	21.9	21.9	21.9	17.5	17.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
5°	35.0	35.0	35.0	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
7.5°	35.0	35.0	35.0	30.6	30.6	30.6	30.6	26.2	26.2	26.2	26.2
10°	35.0	35.0	35.0	30.6	30.6	30.6	30.6	26.2	26.2	26.2	26.2
12.5°	39.4	39.4	35.0	35.0	30.6	30.6	30.6	26.2	26.2	26.2	26.2
15°	39.4	39.4	35.0	35.0	30.6	30.6	30.6	26.2	26.2	26.2	26.2
17.5°	43.7	39.4	39.4	35.0	30.6	30.6	30.6	26.2	26.2	26.2	26.2
20°	43.7	39.4	39.4	35.0	30.6	30.6	30.6	26.2	26.2	26.2	26.2
22.5°	43.7	39.4	39.4	35.0	30.6	30.6	26.2	26.2	21.9	21.9	17.5
25°	43.7	39.4	39.4	35.0	30.6	30.6	26.2	26.2	21.9	17.5	17.5
27.5°	43.7	39.4	39.4	35.0	30.6	26.2	26.2	21.9	17.5	13.1	13.1
30°	43.7	39.4	39.4	35.0	30.6	26.2	21.9	17.5	13.1	13.1	8.7
32.5°	43.7	39.4	35.0	30.6	26.2	21.9	21.9	17.5	13.1	8.7	8.7
35°	43.7	39.4	35.0	30.6	26.2	21.9	21.9	17.5	13.1	8.7	8.7
37.5°	43.7	39.4	35.0	30.6	26.2	21.9	17.5	13.1	8.7	8.7	4.4
40°	43.7	39.4	35.0	30.6	26.2	21.9	17.5	13.1	8.7	8.7	4.4
42.5°	43.7	39.4	35.0	30.6	26.2	21.9	17.5	13.1	8.7	8.7	4.4
45°	48.1	43.7	39.4	30.6	26.2	21.9	21.9	17.5	13.1	8.7	8.7
47.5°	48.1	43.7	39.4	30.6	26.2	21.9	21.9	17.5	13.1	8.7	8.7
50°	52.5	48.1	43.7	35.0	30.6	26.2	21.9	13.1	8.7	8.7	4.4
52.5°	56.9	52.5	48.1	43.7	39.4	30.6	21.9	13.1	4.4	4.4	4.4
55°	61.2	56.9	56.9	52.5	48.1	35.0	26.2	13.1	0.0	0.0	0.0
57.5°	65.6	61.2	61.2	56.9	52.5	39.4	26.2	13.1	0.0	0.0	0.0
60°	74.3	70.0	65.6	56.9	52.5	39.4	26.2	13.1	0.0	0.0	0.0
62.5°	87.5	78.7	65.6	56.9	43.7	35.0	21.9	13.1	0.0	0.0	0.0
65°	96.2	83.1	70.0	52.5	39.4	30.6	21.9	8.7	0.0	0.0	0.0
67.5°	100.6	83.1	70.0	52.5	35.0	26.2	17.5	8.7	0.0	0.0	0.0
70°	96.2	78.7	65.6	48.1	30.6	21.9	17.5	8.7	0.0	0.0	0.0
72.5°	87.5	74.3	56.9	43.7	26.2	21.9	13.1	8.7	0.0	0.0	0.0
75°	78.7	65.6	48.1	35.0	17.5	13.1	8.7	4.4	0.0	0.0	0.0
77.5°	70.0	56.9	39.4	26.2	8.7	8.7	4.4	4.4	0.0	0.0	0.0
80°	52.5	39.4	26.2	13.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.1	8.7	8.7	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
5°	26.2	26.2	26.2	26.2	21.9	21.9	21.9	21.9	21.9	21.9	21.9
7.5°	26.2	26.2	26.2	26.2	21.9	21.9	21.9	21.9	17.5	17.5	17.5
10°	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	17.5	17.5	17.5
12.5°	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	17.5	17.5	17.5
15°	21.9	21.9	21.9	21.9	21.9	21.9	21.9	17.5	17.5	13.1	13.1
17.5°	21.9	21.9	21.9	21.9	17.5	17.5	17.5	13.1	13.1	8.7	8.7
20°	21.9	21.9	21.9	17.5	17.5	13.1	13.1	8.7	8.7	4.4	4.4
22.5°	17.5	13.1	13.1	8.7	8.7	4.4	4.4	4.4	0.0	0.0	0.0
25°	13.1	8.7	8.7	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.7	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.7	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	26.2	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
5°	21.9	21.9	21.9	21.9	17.5	17.5	17.5	17.5	17.5	17.5	17.5
7.5°	17.5	17.5	17.5	17.5	17.5	17.5	13.1	13.1	13.1	13.1	13.1
10°	17.5	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	8.7	8.7
12.5°	17.5	13.1	13.1	13.1	8.7	8.7	8.7	8.7	8.7	4.4	4.4
15°	13.1	8.7	8.7	8.7	4.4	4.4	4.4	4.4	4.4	0.0	0.0
17.5°	8.7	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	26.2	26.2
5°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
7.5°	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1
10°	8.7	8.7	8.7	8.7	8.7	8.7	4.4	4.4	4.4	4.4	4.4
12.5°	4.4	4.4	4.4	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	26.2	26.2	26.2	26.2	26.2	30.6	30.6	35.0	35.0	39.4	39.4
5°	17.5	17.5	21.9	21.9	21.9	21.9	26.2	26.2	26.2	30.6	30.6
7.5°	13.1	13.1	13.1	13.1	13.1	17.5	17.5	21.9	21.9	26.2	26.2
10°	4.4	4.4	8.7	8.7	8.7	8.7	13.1	13.1	13.1	17.5	21.9
12.5°	0.0	0.0	4.4	4.4	4.4	4.4	8.7	8.7	8.7	13.1	17.5
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	8.7	13.1
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	8.7
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	43.7	43.7	48.1	48.1	52.5	52.5	56.9	56.9	56.9	56.9	56.9
5°	35.0	35.0	39.4	43.7	43.7	48.1	52.5	52.5	52.5	52.5	52.5
7.5°	30.6	30.6	35.0	39.4	39.4	43.7	48.1	48.1	52.5	52.5	52.5
10°	21.9	26.2	30.6	35.0	35.0	39.4	43.7	43.7	48.1	48.1	48.1
12.5°	17.5	21.9	26.2	30.6	30.6	35.0	39.4	39.4	43.7	43.7	48.1
15°	13.1	17.5	21.9	26.2	26.2	30.6	35.0	35.0	39.4	43.7	48.1
17.5°	8.7	13.1	17.5	21.9	21.9	26.2	30.6	35.0	39.4	39.4	43.7
20°	8.7	8.7	13.1	17.5	17.5	21.9	26.2	30.6	35.0	35.0	39.4
22.5°	4.4	4.4	8.7	13.1	13.1	17.5	21.9	26.2	30.6	30.6	35.0
25°	0.0	0.0	4.4	8.7	8.7	13.1	17.5	17.5	21.9	21.9	26.2
27.5°	0.0	0.0	4.4	4.4	8.7	8.7	13.1	13.1	17.5	17.5	21.9
30°	0.0	0.0	4.4	4.4	8.7	8.7	13.1	13.1	17.5	17.5	17.5
32.5°	0.0	0.0	0.0	4.4	4.4	4.4	8.7	8.7	13.1	13.1	17.5
35°	0.0	0.0	0.0	4.4	4.4	4.4	8.7	8.7	13.1	13.1	13.1
37.5°	0.0	0.0	0.0	4.4	4.4	4.4	8.7	8.7	8.7	8.7	13.1
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.7	8.7	8.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	8.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	56.9	56.9
5°	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	52.5	52.5
7.5°	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	52.5	52.5
10°	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5
12.5°	48.1	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5
15°	48.1	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5
17.5°	43.7	48.1	48.1	48.1	52.5	52.5	52.5	52.5	52.5	52.5	52.5
20°	39.4	43.7	43.7	43.7	48.1	48.1	48.1	48.1	52.5	52.5	52.5
22.5°	35.0	39.4	39.4	39.4	43.7	43.7	43.7	43.7	48.1	48.1	48.1
25°	30.6	30.6	35.0	35.0	39.4	39.4	39.4	39.4	39.4	39.4	39.4
27.5°	21.9	26.2	26.2	26.2	30.6	30.6	30.6	30.6	35.0	35.0	35.0
30°	21.9	21.9	21.9	21.9	26.2	26.2	26.2	26.2	30.6	30.6	30.6
32.5°	17.5	21.9	21.9	21.9	26.2	26.2	26.2	26.2	30.6	30.6	30.6
35°	17.5	17.5	17.5	17.5	21.9	21.9	21.9	21.9	26.2	26.2	26.2
37.5°	13.1	17.5	17.5	17.5	21.9	21.9	21.9	21.9	26.2	26.2	26.2
40°	13.1	13.1	13.1	13.1	17.5	17.5	17.5	17.5	21.9	21.9	21.9
42.5°	13.1	13.1	13.1	13.1	17.5	17.5	17.5	17.5	21.9	21.9	21.9
45°	13.1	13.1	13.1	13.1	17.5	17.5	17.5	17.5	21.9	21.9	21.9
47.5°	13.1	13.1	13.1	13.1	17.5	17.5	17.5	17.5	21.9	21.9	21.9
50°	13.1	13.1	13.1	13.1	17.5	17.5	17.5	17.5	21.9	21.9	21.9
52.5°	8.7	8.7	8.7	8.7	13.1	13.1	13.1	13.1	17.5	17.5	17.5
55°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	13.1	13.1	13.1
57.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	13.1	13.1	13.1
60°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
62.5°	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
65°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	4.4	4.4
67.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
70°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
72.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
75°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
77.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
80°	13.1	13.1	13.1	13.1	13.1	8.7	8.7	8.7	8.7	8.7	8.7
82.5°	8.7	13.1	13.1	13.1	13.1	8.7	8.7	8.7	8.7	8.7	8.7
85°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
87.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	56.9	56.9	52.5	52.5	52.5	52.5	52.5	52.5	52.5	56.9	56.9
5°	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	56.9	56.9
7.5°	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	56.9	56.9
10°	52.5	52.5	52.5	52.5	48.1	48.1	52.5	52.5	52.5	56.9	56.9
12.5°	52.5	52.5	52.5	52.5	48.1	48.1	52.5	52.5	56.9	56.9	61.2
15°	52.5	52.5	48.1	48.1	48.1	48.1	52.5	52.5	56.9	56.9	61.2
17.5°	52.5	52.5	48.1	48.1	48.1	48.1	52.5	52.5	56.9	56.9	61.2
20°	52.5	52.5	48.1	48.1	48.1	48.1	48.1	48.1	52.5	56.9	56.9
22.5°	48.1	48.1	48.1	48.1	43.7	43.7	48.1	48.1	52.5	56.9	56.9
25°	39.4	43.7	43.7	43.7	43.7	43.7	48.1	48.1	52.5	56.9	56.9
27.5°	35.0	39.4	39.4	39.4	39.4	43.7	43.7	48.1	52.5	56.9	56.9
30°	30.6	35.0	35.0	35.0	39.4	43.7	43.7	48.1	52.5	56.9	56.9
32.5°	30.6	35.0	35.0	35.0	39.4	39.4	43.7	43.7	48.1	52.5	56.9
35°	30.6	30.6	35.0	35.0	35.0	39.4	39.4	43.7	48.1	52.5	56.9
37.5°	30.6	30.6	35.0	35.0	35.0	39.4	39.4	43.7	48.1	52.5	56.9
40°	26.2	30.6	30.6	35.0	35.0	39.4	39.4	43.7	48.1	56.9	61.2
42.5°	26.2	26.2	30.6	30.6	35.0	39.4	39.4	43.7	48.1	56.9	61.2
45°	26.2	30.6	30.6	35.0	39.4	43.7	43.7	48.1	52.5	56.9	61.2
47.5°	26.2	30.6	30.6	35.0	43.7	43.7	48.1	48.1	52.5	56.9	61.2
50°	26.2	30.6	30.6	35.0	48.1	48.1	48.1	48.1	52.5	56.9	61.2
52.5°	21.9	26.2	26.2	30.6	39.4	43.7	48.1	52.5	56.9	61.2	65.6
55°	17.5	21.9	21.9	26.2	35.0	39.4	48.1	56.9	61.2	65.6	70.0
57.5°	17.5	17.5	21.9	21.9	30.6	39.4	52.5	61.2	65.6	70.0	74.3
60°	13.1	13.1	17.5	17.5	26.2	35.0	48.1	61.2	65.6	74.3	78.7
62.5°	8.7	13.1	13.1	17.5	21.9	35.0	48.1	61.2	70.0	78.7	83.1
65°	8.7	8.7	13.1	13.1	21.9	30.6	43.7	52.5	65.6	78.7	91.8
67.5°	13.1	13.1	17.5	17.5	21.9	30.6	43.7	52.5	65.6	83.1	96.2
70°	13.1	13.1	17.5	17.5	26.2	35.0	43.7	52.5	65.6	83.1	96.2
72.5°	13.1	13.1	17.5	17.5	26.2	30.6	39.4	48.1	61.2	74.3	87.5
75°	8.7	13.1	13.1	13.1	21.9	26.2	35.0	43.7	56.9	70.0	83.1
77.5°	8.7	8.7	8.7	8.7	17.5	21.9	30.6	35.0	48.1	61.2	74.3
80°	8.7	8.7	8.7	8.7	13.1	17.5	26.2	30.6	43.7	56.9	70.0
82.5°	8.7	8.7	4.4	4.4	8.7	13.1	17.5	21.9	35.0	43.7	56.9
85°	8.7	8.7	4.4	4.4	4.4	8.7	8.7	13.1	17.5	21.9	26.2
87.5°	8.7	8.7	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	56.9	56.9	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
5°	56.9	61.2	61.2	65.6	65.6	65.6	70.0	70.0	70.0	70.0	70.0
7.5°	56.9	61.2	61.2	65.6	65.6	65.6	70.0	70.0	70.0	74.3	74.3
10°	56.9	61.2	61.2	65.6	65.6	70.0	74.3	74.3	78.7	78.7	78.7
12.5°	61.2	65.6	65.6	70.0	70.0	74.3	78.7	78.7	83.1	87.5	87.5
15°	61.2	65.6	70.0	70.0	74.3	78.7	83.1	83.1	87.5	91.8	96.2
17.5°	61.2	65.6	70.0	70.0	74.3	78.7	87.5	91.8	96.2	105.0	109.3
20°	61.2	65.6	70.0	70.0	74.3	83.1	87.5	96.2	100.6	109.3	118.1
22.5°	61.2	65.6	70.0	74.3	78.7	87.5	96.2	100.6	109.3	122.5	131.2
25°	61.2	65.6	70.0	74.3	78.7	87.5	96.2	105.0	113.7	131.2	148.7
27.5°	61.2	65.6	74.3	78.7	83.1	91.8	105.0	113.7	122.5	153.1	183.7
30°	61.2	65.6	74.3	78.7	83.1	96.2	109.3	118.1	131.2	183.7	231.8
32.5°	61.2	70.0	74.3	83.1	87.5	100.6	118.1	131.2	144.3	218.7	288.6
35°	61.2	70.0	74.3	83.1	87.5	105.0	122.5	140.0	157.4	266.8	376.1
37.5°	61.2	70.0	74.3	83.1	87.5	113.7	140.0	166.2	192.4	306.1	419.9
40°	65.6	74.3	78.7	87.5	91.8	118.1	144.3	170.6	196.8	310.5	424.2
42.5°	65.6	74.3	78.7	87.5	91.8	113.7	140.0	161.8	183.7	310.5	437.3
45°	65.6	74.3	83.1	87.5	96.2	118.1	140.0	157.4	179.3	341.1	498.6
47.5°	65.6	74.3	83.1	87.5	96.2	118.1	140.0	161.8	183.7	450.5	712.9
50°	65.6	74.3	83.1	87.5	96.2	122.5	148.7	174.9	201.2	673.5	1145.8
52.5°	70.0	74.3	83.1	87.5	91.8	122.5	153.1	183.7	214.3	874.7	1530.7
55°	74.3	78.7	83.1	87.5	91.8	131.2	170.6	209.9	249.3	940.3	1626.9
57.5°	78.7	83.1	87.5	87.5	91.8	140.0	192.4	240.5	288.6	935.9	1578.8
60°	83.1	87.5	91.8	96.2	100.6	148.7	201.2	249.3	297.4	848.5	1399.5
62.5°	91.8	100.6	109.3	113.7	122.5	170.6	214.3	262.4	306.1	695.4	1080.2
65°	105.0	113.7	118.1	126.8	131.2	174.9	223.0	266.8	310.5	577.3	839.7
67.5°	109.3	118.1	122.5	131.2	135.6	179.3	223.0	266.8	310.5	489.8	664.8
70°	109.3	118.1	126.8	131.2	140.0	183.7	223.0	266.8	306.1	424.2	542.3
72.5°	100.6	113.7	122.5	135.6	144.3	183.7	218.7	258.0	293.0	376.1	459.2
75°	96.2	113.7	126.8	144.3	157.4	183.7	214.3	240.5	266.8	328.0	389.2
77.5°	87.5	109.3	131.2	153.1	174.9	192.4	205.6	223.0	236.2	275.5	314.9
80°	83.1	105.0	126.8	148.7	170.6	179.3	183.7	192.4	196.8	201.2	205.6
82.5°	65.6	83.1	100.6	113.7	131.2	122.5	118.1	109.3	100.6	96.2	91.8
85°	30.6	35.0	35.0	39.4	39.4	39.4	35.0	35.0	30.6	26.2	21.9
87.5°	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	61.2	61.2	61.2	61.2	56.9	56.9	56.9	56.9	52.5	52.5	52.5
5°	70.0	70.0	70.0	70.0	65.6	65.6	65.6	65.6	61.2	61.2	61.2
7.5°	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3
10°	83.1	83.1	83.1	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5
12.5°	91.8	91.8	96.2	96.2	100.6	100.6	105.0	105.0	109.3	109.3	109.3
15°	100.6	105.0	109.3	113.7	113.7	118.1	122.5	126.8	131.2	135.6	140.0
17.5°	118.1	122.5	131.2	140.0	148.7	157.4	170.6	188.1	201.2	214.3	231.8
20°	131.2	144.3	170.6	201.2	227.4	253.7	319.3	384.9	450.5	516.1	581.7
22.5°	157.4	183.7	271.2	363.0	450.5	537.9	743.5	949.0	1150.2	1355.8	1539.5
25°	209.9	266.8	468.0	669.1	865.9	1067.1	1434.5	1806.2	2173.6	2541.0	2882.1
27.5°	288.6	393.6	721.6	1054.0	1382.0	1710.0	2243.6	2781.5	3315.1	3853.0	4329.7
30°	402.4	572.9	1062.8	1557.0	2046.8	2536.6	3210.1	3888.0	4561.5	5235.0	5672.4
32.5°	546.7	800.3	1421.4	2042.4	2663.4	3284.5	4028.0	4771.5	5510.6	6254.1	6717.7
35°	699.8	1023.4	1771.3	2523.5	3271.4	4023.6	4806.4	5589.3	6372.1	7155.0	7723.6
37.5°	787.2	1154.6	2042.4	2930.2	3813.7	4701.5	5558.7	6420.3	7277.5	8134.7	8825.7
40°	870.3	1312.0	2335.4	3358.8	4382.2	5405.6	6407.1	7408.7	8410.2	9411.7	10299.5
42.5°	992.8	1548.2	2742.2	3936.1	5125.7	6319.7	7636.1	8956.9	10273.3	11589.7	12954.2
45°	1246.4	1994.3	3542.5	5090.7	6634.6	8182.8	10050.2	11922.1	13789.6	15661.4	17410.8
47.5°	1858.7	3000.2	5112.6	7225.0	9337.4	11449.8	13601.5	15753.2	17905.0	20056.7	22138.5
50°	2877.7	4605.3	7246.8	9888.4	12525.6	15167.2	17314.6	19462.0	21605.0	23752.3	25821.0
52.5°	3835.5	6140.4	8978.7	11821.5	14659.9	17502.6	19405.1	21307.6	23210.0	25112.5	27115.5
55°	4163.5	6695.8	9569.2	12446.9	15320.3	18198.0	20030.5	21867.4	23699.8	25532.3	27609.7
57.5°	3874.9	6171.0	9066.2	11961.4	14852.3	17747.6	19794.3	21845.5	23892.3	25943.4	28169.5
60°	3245.1	5086.3	8125.9	11169.8	14209.4	17249.0	19558.2	21867.4	24176.6	26485.7	28707.5
62.5°	2571.6	4058.6	7277.5	10496.3	13715.2	16934.1	19282.6	21635.6	23984.1	26332.7	28038.3
65°	1972.4	3105.2	6271.6	9442.3	12608.7	15779.5	17703.8	19632.5	21556.8	23485.5	24666.4
67.5°	1465.1	2265.5	5033.9	7806.6	10575.1	13343.5	14760.5	16181.8	17598.9	19020.2	19938.7
70°	1080.2	1613.8	3498.8	5383.7	7264.3	9149.3	10448.2	11747.1	13041.7	14340.6	15294.0
72.5°	747.9	1032.1	2160.5	3293.2	4421.6	5549.9	6866.4	8182.8	9494.8	10811.2	11895.8
75°	511.7	634.2	1163.3	1692.5	2221.7	2750.9	3748.1	4745.2	5742.4	6739.5	7312.4
77.5°	380.5	446.1	603.5	765.4	922.8	1080.2	1272.7	1465.1	1657.5	1850.0	2099.3
80°	209.9	209.9	231.8	249.3	271.2	288.6	341.1	398.0	450.5	507.3	577.3
82.5°	96.2	100.6	109.3	118.1	122.5	131.2	140.0	148.7	157.4	166.2	166.2
85°	26.2	30.6	30.6	26.2	26.2	21.9	21.9	26.2	26.2	26.2	26.2
87.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	52.5	48.1	48.1	48.1	43.7	43.7	43.7	43.7	43.7	43.7	43.7
5°	61.2	61.2	61.2	61.2	56.9	56.9	56.9	56.9	56.9	52.5	52.5
7.5°	74.3	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	65.6	65.6
10°	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	83.1	83.1
12.5°	109.3	109.3	109.3	109.3	113.7	113.7	109.3	109.3	109.3	105.0	105.0
15°	144.3	148.7	153.1	153.1	157.4	157.4	157.4	153.1	153.1	148.7	144.3
17.5°	244.9	258.0	275.5	293.0	310.5	323.6	323.6	314.9	306.1	297.4	288.6
20°	651.6	717.2	787.2	857.2	931.5	984.0	949.0	922.8	896.6	865.9	839.7
22.5°	1727.5	1911.2	2099.3	2230.5	2361.7	2453.5	2379.2	2234.8	2090.5	1950.6	1806.2
25°	3223.2	3560.0	3901.1	4041.1	4185.4	4290.4	4242.3	4023.6	3804.9	3590.6	3371.9
27.5°	4806.4	5278.8	5755.5	5877.9	6000.4	6092.2	6074.8	5790.5	5506.2	5221.9	4937.7
30°	6109.7	6547.1	6984.4	7106.9	7229.3	7312.4	7220.6	6936.3	6652.1	6367.8	6083.5
32.5°	7185.6	7649.2	8117.2	8279.0	8440.8	8550.1	8440.8	8099.7	7758.5	7421.8	7080.7
35°	8292.1	8856.3	9424.8	9630.4	9835.9	9967.1	9783.5	9363.6	8943.8	8528.3	8108.4
37.5°	9516.7	10203.3	10894.3	11174.2	11458.5	11655.3	11515.4	10990.5	10461.3	9936.5	9407.3
40°	11191.7	12079.5	12971.7	13474.7	13973.2	14327.5	14078.2	13470.3	12858.0	12250.1	11637.8
42.5°	14323.1	15687.6	17052.2	17773.8	18491.0	19011.5	18731.6	17983.7	17235.9	16488.0	15740.1
45°	19160.2	20905.2	22654.6	23708.6	24767.0	25545.5	25221.8	24281.5	23336.8	22396.6	21456.3
47.5°	24220.3	26302.1	28383.8	29223.5	30067.6	30723.6	30644.9	29472.8	28300.7	27133.0	25960.9
50°	27894.0	29962.7	32031.3	32752.9	33478.9	34016.9	33815.7	32324.3	30828.6	29337.3	27841.5
52.5°	29118.6	31117.3	33120.3	33981.9	34843.5	35486.4	35241.4	33562.0	31882.6	30207.6	28528.2
55°	29687.1	31764.5	33841.9	34891.6	35945.6	36715.3	36361.0	34519.8	32674.2	30833.0	28987.4
57.5°	30395.6	32621.7	34847.8	35998.1	37148.3	37979.2	37506.9	35600.1	33693.2	31790.8	29883.9
60°	30929.2	33146.5	35368.3	36291.1	37218.3	37865.5	37410.7	35556.3	33697.6	31843.3	29988.9
62.5°	29748.4	31454.0	33159.7	33846.3	34532.9	35031.5	34773.5	33015.3	31257.2	29499.1	27740.9
65°	25851.6	27032.4	28217.6	28681.2	29140.4	29494.7	29416.0	27933.4	26450.8	24972.5	23489.9
67.5°	20861.5	21779.9	22702.7	23358.7	24019.1	24530.8	24474.0	23122.5	21771.1	20419.7	19068.3
70°	16251.8	17205.2	18158.7	18985.2	19816.2	20459.1	20376.0	19120.8	17861.3	16606.1	15346.5
72.5°	12984.8	14069.5	15154.1	15626.4	16098.8	16431.1	16186.2	15237.2	14283.8	13334.7	12381.3
75°	7885.4	8453.9	9026.8	9022.5	9022.5	8970.0	8725.1	8182.8	7640.5	7098.1	6555.8
77.5°	2348.6	2597.8	2847.1	3087.7	3332.6	3516.3	3468.2	3183.9	2895.2	2611.0	2322.3
80°	647.3	712.9	782.9	813.5	844.1	883.4	984.0	914.1	844.1	778.5	708.5
82.5°	166.2	166.2	166.2	161.8	157.4	148.7	135.6	126.8	118.1	109.3	100.6
85°	26.2	21.9	21.9	21.9	17.5	17.5	17.5	17.5	13.1	13.1	8.7
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
2.5°	43.7	43.7	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	35.0
5°	52.5	52.5	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	43.7
7.5°	65.6	65.6	61.2	61.2	61.2	61.2	56.9	56.9	56.9	56.9	52.5
10°	83.1	78.7	78.7	74.3	74.3	74.3	70.0	70.0	70.0	65.6	65.6
12.5°	105.0	100.6	100.6	96.2	91.8	91.8	87.5	83.1	78.7	78.7	74.3
15°	140.0	135.6	131.2	126.8	122.5	113.7	109.3	100.6	96.2	91.8	87.5
17.5°	266.8	244.9	223.0	201.2	183.7	166.2	148.7	131.2	122.5	113.7	105.0
20°	743.5	642.9	546.7	450.5	389.2	328.0	266.8	205.6	179.3	157.4	131.2
22.5°	1609.4	1408.3	1211.5	1010.3	848.5	691.0	529.2	367.4	306.1	249.3	188.1
25°	2991.5	2606.6	2226.1	1841.2	1535.1	1228.9	922.8	616.7	502.9	389.2	275.5
27.5°	4439.1	3940.5	3441.9	2943.3	2457.9	1968.1	1478.2	992.8	796.0	603.5	406.7
30°	5554.3	5025.1	4500.3	3971.1	3358.8	2746.5	2129.9	1517.6	1207.1	896.6	581.7
32.5°	6512.1	5939.2	5370.6	4797.7	4089.2	3380.7	2672.2	1963.7	1574.5	1185.2	791.6
35°	7461.1	6809.5	6162.2	5510.6	4749.6	3988.6	3227.6	2466.6	1972.4	1478.2	979.7
37.5°	8615.7	7819.8	7028.2	6236.6	5453.7	4675.2	3892.4	3109.5	2479.8	1854.4	1224.6
40°	10627.5	9612.9	8602.6	7588.0	6673.9	5764.2	4850.2	3936.1	3144.5	2352.9	1557.0
42.5°	14467.4	13194.8	11926.5	10653.8	9389.8	8125.9	6857.6	5593.7	4465.3	3341.3	2213.0
45°	19825.0	18193.6	16566.7	14935.4	13378.5	11825.9	10268.9	8712.0	6997.6	5283.2	3564.4
47.5°	24176.6	22387.8	20603.4	18814.7	17087.2	15364.0	13636.5	11909.0	9713.5	7522.4	5326.9
50°	26140.2	24434.6	22733.3	21027.7	19295.8	17559.5	15823.2	14091.3	11572.2	9057.5	6538.3
52.5°	26800.6	25068.7	23341.2	21609.3	19890.6	18171.8	16453.0	14734.2	12114.5	9499.2	6879.5
55°	27163.6	25335.5	23511.8	21683.7	19833.7	17979.3	16125.0	14275.0	11668.4	9066.2	6459.6
57.5°	27898.4	25908.5	23922.9	21933.0	19825.0	17716.9	15604.5	13496.5	10924.9	8353.3	5781.7
60°	28034.0	26074.6	24119.7	22164.8	19833.7	17502.6	15167.2	12836.1	10282.0	7732.3	5178.2
62.5°	26105.3	24469.6	22838.3	21202.6	18867.2	16531.7	14191.9	11856.5	9411.7	6966.9	4517.8
65°	22077.3	20664.7	19256.4	17843.8	15936.9	14034.5	12127.6	10220.8	8038.4	5860.5	3678.1
67.5°	17686.3	16304.3	14926.7	13544.6	12110.1	10680.0	9245.5	7811.0	6127.2	4443.4	2759.7
70°	14021.4	12691.8	11366.7	10037.1	8768.8	7496.1	6223.5	4955.1	3909.9	2869.0	1823.7
72.5°	11113.0	9840.3	8572.0	7299.3	6149.1	4998.9	3848.7	2698.4	2178.0	1661.9	1141.5
75°	5895.4	5235.0	4579.0	3918.6	3271.4	2619.7	1968.1	1320.8	1115.2	909.7	699.8
77.5°	2033.7	1745.0	1460.7	1172.1	975.3	778.5	581.7	384.9	363.0	345.5	323.6
80°	616.7	524.8	433.0	341.1	301.8	262.4	223.0	183.7	170.6	157.4	140.0
82.5°	96.2	87.5	83.1	74.3	70.0	70.0	65.6	61.2	52.5	48.1	39.4
85°	8.7	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	39.4	39.4
2.5°	35.0	35.0
5°	43.7	43.7
7.5°	52.5	52.5
10°	61.2	61.2
12.5°	70.0	70.0
15°	83.1	78.7
17.5°	96.2	91.8
20°	105.0	96.2
22.5°	126.8	109.3
25°	161.8	135.6
27.5°	209.9	166.2
30°	271.2	209.9
32.5°	402.4	293.0
35°	485.5	354.3
37.5°	594.8	411.1
40°	765.4	498.6
42.5°	1084.6	677.9
45°	1850.0	1124.0
47.5°	3135.8	1915.6
50°	4019.2	2457.9
52.5°	4264.1	2606.6
55°	3857.4	2392.3
57.5°	3210.1	2033.7
60°	2628.5	1675.0
62.5°	2073.0	1325.2
65°	1495.7	1001.5
67.5°	1075.9	769.7
70°	782.9	603.5
72.5°	621.0	502.9
75°	494.2	419.9
77.5°	306.1	279.9
80°	126.8	118.1
82.5°	30.6	26.2
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1067667

CATALOG NUMBER: NAV-SA4C-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-2

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-722-U-5WQ

Data in this report applies to families of products including GSS-SB1A-722-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-722-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2200K CCT 26 LEDS

Spectral Parameters

CCT (K):	2160	CRI (Ra):	71.9		
CIE u':	0.2927	R1:	68.7	R9:	-17.8
CIE v':	0.5388	R2:	82.6	R10:	60.5
Duv:	0.0015	R3:	95.5	R11:	60.2
CIE x:	0.5130	R4:	66.4	R12:	48.2
CIE y:	0.4197	R5:	65.4	R13:	70.7
CIE z:	0.0674	R6:	75.9	R14:	96.8
Peak Wavelength (nm):	609	R7:	77.2	R15:	61.8
Dominant Wavelength (nm):	587	R8:	43.5		
Purity:	79.96089				
Rf:	70.6				
Rg:	97.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-2

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-2

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2200K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-2

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 0.8

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.21

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2



TM-30-18

Summary

$R_f = 70.6$
 $R_g = 97.6$
 $CIE\ R_a = 71.9$
 $R_g = -17.8$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 87	CES26 = 60	CES51 = 74	CES76 = 58
CES02 = 65	CES27 = 77	CES52 = 77	CES77 = 82
CES03 = 32	CES28 = 85	CES53 = 65	CES78 = 65
CES04 = 72	CES29 = 50	CES54 = 77	CES79 = 86
CES05 = 52	CES30 = 49	CES55 = 74	CES80 = 85
CES06 = 53	CES31 = 55	CES56 = 64	CES81 = 61
CES07 = 44	CES32 = 55	CES57 = 60	CES82 = 93
CES08 = 43	CES33 = 55	CES58 = 64	CES83 = 83
CES09 = 29	CES34 = 75	CES59 = 84	CES84 = 93
CES10 = 79	CES35 = 88	CES60 = 89	CES85 = 81
CES11 = 62	CES36 = 78	CES61 = 84	CES86 = 55
CES12 = 68	CES37 = 82	CES62 = 68	CES87 = 79
CES13 = 45	CES38 = 54	CES63 = 68	CES88 = 72
CES14 = 75	CES39 = 90	CES64 = 69	CES89 = 62
CES15 = 72	CES40 = 86	CES65 = 66	CES90 = 67
CES16 = 49	CES41 = 75	CES66 = 64	CES91 = 89
CES17 = 51	CES42 = 83	CES67 = 63	CES92 = 67
CES18 = 57	CES43 = 68	CES68 = 71	CES93 = 78
CES19 = 74	CES44 = 98	CES69 = 81	CES94 = 52
CES20 = 68	CES45 = 76	CES70 = 65	CES95 = 76
CES21 = 89	CES46 = 68	CES71 = 64	CES96 = 78
CES22 = 81	CES47 = 60	CES72 = 88	CES97 = 76
CES23 = 92	CES48 = 47	CES73 = 59	CES98 = 71
CES24 = 92	CES49 = 65	CES74 = 85	CES99 = 65
CES25 = 74	CES50 = 74	CES75 = 66	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)