

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P220519

Luminaire Tested: **1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220519
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29473)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV
Description: LUMIERE LANTERRA 1003 LED ACCENT/SIGN LUMINAIRE, RECESSED LENS, MEDIUM FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) 3000K CCT, 90 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 624.2 lumens
Efficiency: N/A
Efficacy: 63.7 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.4
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct


Input Watts (W): 9.8
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P220519

CATALOG NUMBER: 1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P220519

CATALOG NUMBER: 1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97
2	111	108	105	102	109	106	103	101	103	101	99	100	98	97	98	96	95	94
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	93	92	91
4	105	99	96	93	103	98	95	92	96	93	91	95	92	90	93	91	89	88
5	102	96	92	89	100	95	91	88	93	90	88	92	89	87	91	88	86	85
6	99	93	89	86	98	92	88	85	91	87	85	89	87	84	88	86	84	83
7	96	90	86	83	95	89	85	83	88	85	82	87	84	82	86	83	81	80
8	94	87	83	80	93	87	83	80	86	82	80	85	82	80	84	81	79	78
9	91	85	81	78	90	84	80	78	83	80	78	83	80	77	82	79	77	76
10	89	82	78	76	88	82	78	76	81	78	76	81	78	75	80	77	75	74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	656307
5°	588134
10°	413197
15°	221749
20°	116630
25°	52140
30°	10077
35°	3694
40°	2118
45°	1737
50°	1467
55°	1147
60°	965
65°	675
70°	256
75°	0
80°	0
85°	0



TEST NUMBER: P220519

CATALOG NUMBER: 1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	228.6	36.6
10°-20°	275.5	44.1
20°-30°	100.5	16.1
30°-40°	11.1	1.8
40°-50°	4.4	0.7
50°-60°	2.8	0.4
60°-70°	1.3	0.2
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	604.6	96.9
0°-40°	615.7	98.6
0°-60°	622.8	99.8
0°-90°	624.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	624.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2993	
5°	2672	229
15°	977	275
25°	216	101
35°	14	11
45°	6	4
55°	3	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P220519

CATALOG NUMBER: 1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	2993.0
1°	2968.8
2°	2926.4
3°	2864.1
4°	2778.0
5°	2671.9
6°	2545.1
7°	2396.3
8°	2227.5
9°	2044.4
10°	1855.7
11°	1665.7
12°	1477.5
13°	1299.6
14°	1130.0
15°	976.8
16°	836.1
17°	721.4
18°	628.4
19°	554.8
20°	499.8
21°	454.8
22°	403.3
23°	342.3
24°	278.7
25°	215.5
26°	155.4
27°	101.7
28°	64.1
29°	46.7
30°	39.8
32.5°	26.8
35°	13.8
37.5°	9.1
40°	7.4
42.5°	6.5
45°	5.6
47.5°	4.8
50°	4.3
52.5°	3.5
55°	3.0
57.5°	2.6
60°	2.2
62.5°	1.7
65°	1.3



TEST NUMBER: P220519

CATALOG NUMBER: 1003-[A1, S1, SU1]-[RW, RI]-LED3090-M-BK-L1-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.9
70°	0.4
72.5°	0.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)