

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: LUMIERE

Report Number: P220673

Luminaire Tested: **1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P220673  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29477)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: LUMIERE  
Catalog Number: 1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV  
Description: LUMIERE LANTERRA 1003 LED ACCENT/SIGN LUMINAIRE, FLUSH LENS, MEDIUM FLOOD OPTIC, BLACK HOUSING.  
Light Source: (1) 3500K CCT, 97 CRI LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1299.5 lumens  
Efficiency: N/A  
Efficacy: 64.7 lumens/watt  
Spacing Criteria (0/90/45): 0.41 / 0.41 / 0.41  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct


Input Watts (W): 20.1  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P220673

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P220673

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	111	109	107	107	105	104	103	102	101	99	99	98	96
2	111	107	104	101	109	105	103	100	102	100	98	99	98	96	97	95	94	93
3	107	102	99	96	105	101	98	95	98	96	93	96	94	92	94	92	91	89
4	104	98	94	91	102	97	93	90	95	92	89	93	90	88	91	89	87	86
5	100	94	90	87	99	93	89	86	92	88	86	90	87	85	89	86	84	83
6	97	91	86	83	96	90	86	83	89	85	82	87	84	82	86	84	81	80
7	94	88	83	80	93	87	83	80	86	82	80	85	82	79	84	81	79	78
8	92	85	80	77	91	84	80	77	83	80	77	82	79	77	82	79	76	75
9	89	82	78	75	88	82	78	75	81	77	75	80	77	74	79	76	74	73
10	86	79	75	73	86	79	75	72	78	75	72	78	74	72	77	74	72	71

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1205561
5°	1095441
10°	774223
15°	418391
20°	222503
25°	163679
30°	66086
35°	12635
40°	6641
45°	2977
50°	2456
55°	2141
60°	1754
65°	1660
70°	1539
75°	1356
80°	1010
85°	2013



TEST NUMBER: P220673

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	426.4	32.8
10°-20°	520.2	40.0
20°-30°	286.3	22.0
30°-40°	47.5	3.7
40°-50°	8.7	0.7
50°-60°	5.0	0.4
60°-70°	3.2	0.2
70°-80°	1.7	0.1
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1232.9	94.9
0°-40°	1280.4	98.5
0°-60°	1294.1	99.6
0°-90°	1299.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1299.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	5498	
5°	4977	426
15°	1843	520
25°	676	286
35°	47	47
45°	10	9
55°	6	5
65°	3	3
75°	2	2
85°	1	1
90°	0	



TEST NUMBER: P220673

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	5497.8
1°	5464.2
2°	5407.3
3°	5317.7
4°	5165.6
5°	4976.6
6°	4748.4
7°	4477.0
8°	4168.0
9°	3829.3
10°	3477.1
11°	3121.6
12°	2772.5
13°	2438.7
14°	2130.4
15°	1843.0
16°	1594.8
17°	1371.5
18°	1196.9
19°	1057.6
20°	953.5
21°	874.3
22°	816.6
23°	775.8
24°	735.0
25°	676.5
26°	603.7
27°	522.0
28°	433.1
29°	345.9
30°	261.0
32.5°	94.5
35°	47.2
37.5°	33.6
40°	23.2
42.5°	12.0
45°	9.6
47.5°	8.8
50°	7.2
52.5°	6.4
55°	5.6
57.5°	4.8
60°	4.0
62.5°	4.0
65°	3.2



TEST NUMBER: P220673

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED3597-M-BK-L2-UNV

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	2.4
70°	2.4
72.5°	1.6
75°	1.6
77.5°	1.6
80°	0.8
82.5°	0.8
85°	0.8
87.5°	0.0
90°	0.0

(END OF REPORT)